

# Package ‘xfun’

March 25, 2024

**Type** Package

**Title** Supporting Functions for Packages Maintained by 'Yihui Xie'

**Version** 0.43

**Description** Miscellaneous functions commonly used in other packages maintained by 'Yihui Xie'.

**Imports** grDevices, stats, tools

**Suggests** testit, parallel, codetools, rstudioapi, tinytex (>= 0.30),  
mime, markdown (>= 1.5), knitr (>= 1.42), htmltools, remotes,  
pak, rhub, renv, curl, xml2, jsonlite, magick, yaml, rmarkdown

**License** MIT + file LICENSE

**URL** <https://github.com/yihui/xfun>

**BugReports** <https://github.com/yihui/xfun/issues>

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**VignetteBuilder** knitr

**NeedsCompilation** yes

**Author** Yihui Xie [aut, cre, cph] (<<https://orcid.org/0000-0003-0645-5666>>),  
Wush Wu [ctb],  
Daijiang Li [ctb],  
Xianying Tan [ctb],  
Salim Brüggemann [ctb] (<<https://orcid.org/0000-0002-5329-5987>>),  
Christophe Dervieux [ctb],  
Posit Software, PBC [cph, fnd]

**Maintainer** Yihui Xie <xie@yihui.name>

**Repository** CRAN

**Date/Publication** 2024-03-25 17:00:02 UTC

## R topics documented:

alnum_id . . . . .	4
attr . . . . .	4

base64_encode . . . . .	5
base64_uri . . . . .	6
base_pkgs . . . . .	6
bg_process . . . . .	7
broken_packages . . . . .	8
bump_version . . . . .	8
cache_rds . . . . .	9
crandalf_check . . . . .	11
csv_options . . . . .	12
decimal_dot . . . . .	13
del_empty_dir . . . . .	13
dir_create . . . . .	14
dir_exists . . . . .	14
divide_chunk . . . . .	15
download_cache . . . . .	16
download_file . . . . .	17
do_once . . . . .	17
embed_file . . . . .	18
env_option . . . . .	20
existing_files . . . . .	21
exit_call . . . . .	21
fenced_block . . . . .	22
file_ext . . . . .	23
file_string . . . . .	24
format_bytes . . . . .	25
from_root . . . . .	25
github_releases . . . . .	26
grep_sub . . . . .	27
gsub_file . . . . .	27
install_dir . . . . .	28
install_github . . . . .	29
in_dir . . . . .	29
is_abs_path . . . . .	30
is_ascii . . . . .	30
is_blank . . . . .	31
is_sub_path . . . . .	31
is_web_path . . . . .	32
is_windows . . . . .	33
magic_path . . . . .	33
mark_dirs . . . . .	34
msg_cat . . . . .	35
native_encode . . . . .	36
news2md . . . . .	36
normalize_path . . . . .	37
numbers_to_words . . . . .	38
optipng . . . . .	39
parse_only . . . . .	39
pkg_attach . . . . .	40

process_file . . . . .	41
proc_kill . . . . .	42
proj_root . . . . .	43
prose_index . . . . .	44
protect_math . . . . .	44
raw_string . . . . .	45
read_all . . . . .	46
read_bin . . . . .	47
read_utf8 . . . . .	47
record . . . . .	48
relative_path . . . . .	50
rename_seq . . . . .	51
rest_api . . . . .	52
retry . . . . .	53
rev_check . . . . .	54
Rscript . . . . .	56
Rscript_call . . . . .	57
rstudio_type . . . . .	58
same_path . . . . .	58
session_info . . . . .	59
set_envvar . . . . .	60
shrink_images . . . . .	60
split_lines . . . . .	61
split_source . . . . .	62
strict_list . . . . .	63
strip_html . . . . .	64
submit_cran . . . . .	64
system3 . . . . .	65
tinify . . . . .	66
tojson . . . . .	67
tree . . . . .	68
try_error . . . . .	69
try_silent . . . . .	70
upload_ftp . . . . .	70
upload_imgur . . . . .	71
url_accessible . . . . .	73
url_filename . . . . .	73
valid_syntax . . . . .	74
yaml_body . . . . .	75
yaml_load . . . . .	75

---

alnum_id	<i>Generate ID strings</i>
----------	----------------------------

---

### Description

Substitute certain (by default, non-alphanumeric) characters with dashes and remove extra dashes at both ends to generate ID strings. This function is intended for generating IDs for HTML elements, so HTML tags in the input text will be removed first.

### Usage

```
alnum_id(x, exclude = "[^[:alnum:]]+")
```

### Arguments

x	A character vector.
exclude	A (Perl) regular expression to detect characters to be replaced by dashes. By default, non-alphanumeric characters are replaced.

### Value

A character vector of IDs.

### Examples

```
x = c("Hello world 123!", "a &b*^##c 456")
xfun::alnum_id(x)
xfun::alnum_id(x, "[^[:alpha:]]+") # only keep alphabetical chars
# when text contains HTML tags
xfun::alnum_id("<h1>Hello <strong>world</strong>!")
```

---

attr	<i>Obtain an attribute of an object without partial matching</i>
------	--

---

### Description

An abbreviation of `base::attr(exact = TRUE)`.

### Usage

```
attr(...)
```

### Arguments

...	Passed to <code>base::attr()</code> (without the exact argument).
-----	---

## Examples

```
z = structure(list(a = 1), foo = 2)
base::attr(z, "f") # 2
xfun::attr(z, "f") # NULL
xfun::attr(z, "foo") # 2
```

---

base64_encode	<i>Encode/decode data into/from base64 encoding.</i>
---------------	--

---

## Description

The function `base64_encode()` encodes a file or a raw vector into the base64 encoding. The function `base64_decode()` decodes data from the base64 encoding.

## Usage

```
base64_encode(x)
```

```
base64_decode(x, from = NA)
```

## Arguments

<code>x</code>	For <code>base64_encode()</code> , a raw vector. If not raw, it is assumed to be a file or a connection to be read via <code>readBin()</code> . For <code>base64_decode()</code> , a string.
<code>from</code>	If provided (and <code>x</code> is not provided), a connection or file to be read via <code>readChar()</code> , and the result will be passed to the argument <code>x</code> .

## Value

`base64_encode()` returns a character string. `base64_decode()` returns a raw vector.

## Examples

```
xfun::base64_encode(as.raw(1:10))
logo = xfun::R_logo()
xfun::base64_encode(logo)
xfun::base64_decode("AQIDBAUGBwgJCg==")
```

base64\_uri                      *Generate the Data URI for a file*

---

### Description

Encode the file in the base64 encoding, and add the media type. The data URI can be used to embed data in HTML documents, e.g., in the src attribute of the <img /> tag.

### Usage

```
base64_uri(x, type = mime::guess_type(x))
```

### Arguments

x                                  A file path.  
type                                The MIME type of the file, e.g., "image/png" for a PNG image file.

### Value

A string of the form data:<media type>;base64,<data>.

### Note

This function requires the **mime** package to determine the MIME type of the file except for a few common MIME types.

### Examples

```
logo = xfun::R_logo()  
img = htmltools::img(src = xfun::base64_uri(logo), alt = "R logo")  
if (interactive()) htmltools::browsable(img)
```

---

base\_pkgs                      *Get base R package names*

---

### Description

Return names of packages from `installed.packages()` of which the priority is "base".

### Usage

```
base_pkgs()
```

### Value

A character vector of base R package names.

## Examples

```
xfun::base_pkgs()
```

---

bg_process	<i>Start a background process</i>
------------	-----------------------------------

---

## Description

Start a background process using the PowerShell cmdlet `Start-Process-PassThru` on Windows or the ampersand `&` on Unix, and return the process ID.

## Usage

```
bg_process(  
  command,  
  args = character(),  
  verbose = getOption("xfun.bg_process.verbose", FALSE)  
)
```

## Arguments

command, args	The system command and its arguments. They do not need to be quoted, since they will be quoted via <code>shQuote()</code> internally.
verbose	If FALSE, suppress the output from stdout (and also stderr on Windows). The default value of this argument can be set via a global option, e.g., <code>options(xfun.bg_process.verbose = TRUE)</code> .

## Value

The process ID as a character string.

## Note

On Windows, if PowerShell is not available, try to use `system2(wait = FALSE)` to start the background process instead. The process ID will be identified from the output of the command `tasklist`. This method of looking for the process ID may not be reliable. If the search is not successful in 30 seconds, it will throw an error (timeout). If a longer time is needed, you may set `options(xfun.bg_process.timeout)` to a larger value, but it should be very rare that a process cannot be started in 30 seconds. When you reach the timeout, it is more likely that the command actually failed.

## See Also

[proc\\_kill\(\)](#) to kill a process.

---

broken_packages	<i>Find out broken packages and reinstall them</i>
-----------------	--

---

**Description**

If a package is broken (i.e., not `loadable()`), reinstall it.

**Usage**

```
broken_packages(reinstall = TRUE)
```

**Arguments**

`reinstall` Whether to reinstall the broken packages, or only list their names.

**Details**

Installed R packages could be broken for several reasons. One common reason is that you have upgraded R to a newer `x.y` version, e.g., from `4.0.5` to `4.1.0`, in which case you need to reinstall previously installed packages.

**Value**

A character vector of names of broken package.

---

bump_version	<i>Bump version numbers</i>
--------------	-----------------------------

---

**Description**

Increase the last digit of version numbers, e.g., from `0.1` to `0.2`, or `7.23.9` to `7.23.10`.

**Usage**

```
bump_version(x)
```

**Arguments**

`x` A vector of version numbers (of the class `"numeric_version"`), or values that can be coerced to version numbers via `as.numeric_version()`.

**Value**

A vector of new version numbers.

**Examples**

```
xfun::bump_version(c("0.1", "91.2.14"))
```



---

cache_rds	<i>Cache the value of an R expression to an RDS file</i>
-----------	--

---

## Description

Save the value of an expression to a cache file (of the RDS format). Next time the value is loaded from the file if it exists.

## Usage

```
cache_rds(
  expr = {
  },
  rerun = FALSE,
  file = "cache.rds",
  dir = "cache/",
  hash = NULL,
  clean = getOption("xfun.cache_rds.clean", TRUE),
  ...
)
```

## Arguments

expr	An R expression.
rerun	Whether to delete the RDS file, rerun the expression, and save the result again (i.e., invalidate the cache if it exists).
file	The <i>base</i> (see Details) cache filename under the directory specified by the <code>dir</code> argument. If not specified and this function is called inside a code chunk of a <b>knitr</b> document (e.g., an R Markdown document), the default is the current chunk label plus the extension <code>‘.rds’</code> .
dir	The path of the RDS file is partially determined by <code>paste0(dir, file)</code> . If not specified and the <b>knitr</b> package is available, the default value of <code>dir</code> is the <b>knitr</b> chunk option <code>cache.path</code> (so if you are compiling a <b>knitr</b> document, you do not need to provide this <code>dir</code> argument explicitly), otherwise the default is <code>‘cache/’</code> . If you do not want to provide a <code>dir</code> but simply a valid path to the <code>file</code> argument, you may use <code>dir = “”</code> .
hash	A list object that contributes to the MD5 hash of the cache filename (see Details). It can also take a special character value <code>“auto”</code> . Other types of objects are ignored.
clean	Whether to clean up the old cache files automatically when <code>expr</code> has changed.
...	Other arguments to be passed to <code>saveRDS()</code> .

## Details

Note that the `file` argument does not provide the full cache filename. The actual name of the cache file is of the form `'BASENAME_HASH.rds'`, where `'BASENAME'` is the base name provided via the `'file'` argument (e.g., if `file = 'foo.rds'`, `BASENAME` would be `'foo'`), and `'HASH'` is the MD5 hash (also called the 'checksum') calculated from the R code provided to the `expr` argument and the value of the `hash` argument, which means when the code or the `hash` argument changes, the `'HASH'` string may also change, and the old cache will be invalidated (if it exists). If you want to find the cache file, look for `'.rds'` files that contain 32 hexadecimal digits (consisting of 0-9 and a-z) at the end of the filename.

The possible ways to invalidate the cache are: 1) change the code in `expr` argument; 2) delete the cache file manually or automatically through the argument `rerun = TRUE`; and 3) change the value of the `hash` argument. The first two ways should be obvious. For the third way, it makes it possible to automatically invalidate the cache based on changes in certain R objects. For example, when you run `cache_rds({ x + y })`, you may want to invalidate the cache to rerun `{ x + y }` when the value of `x` or `y` has been changed, and you can tell `cache_rds()` to do so by `cache_rds({ x + y }, hash = list(x, y))`. The value of the argument `hash` is expected to be a list, but it can also take a special value, `"auto"`, which means `cache_rds(expr)` will try to automatically figure out the global variables in `expr`, return a list of their values, and use this list as the actual value of `hash`. This behavior is most likely to be what you really want: if the code in `expr` uses an external global variable, you may want to invalidate the cache if the value of the global variable has changed. Here a "global variable" means a variable not created locally in `expr`, e.g., for `cache_rds({ x <- 1; x + y })`, `x` is a local variable, and `y` is (most likely to be) a global variable, so changes in `y` should invalidate the cache. However, you know your own code the best. If you want to be completely sure when to invalidate the cache, you can always provide a list of objects explicitly rather than relying on `hash = "auto"`.

By default (the argument `clean = TRUE`), old cache files will be automatically cleaned up. Sometimes you may want to use `clean = FALSE` (set the R global option `options(xfun.cache_rds.clean = FALSE)` if you want `FALSE` to be the default). For example, you may not have decided which version of code to use, and you can keep the cache of both versions with `clean = FALSE`, so when you switch between the two versions of code, it will still be fast to run the code.

## Value

If the cache file does not exist, run the expression and save the result to the file, otherwise read the cache file and return the value.

## Note

Changes in the code in the `expr` argument do not necessarily always invalidate the cache, if the changed code is [parsed](#) to the same expression as the previous version of the code. For example, if you have run `cache_rds({ Sys.sleep(5); 1+1 })` before, running `cache_rds({ Sys.sleep( 5 ); 1 + 1 })` will use the cache, because the two expressions are essentially the same (they only differ in white spaces). Usually you can add/delete white spaces or comments to your code in `expr` without invalidating the cache. See the package vignette `vignette('xfun', package = 'xfun')` for more examples.

When this function is called in a code chunk of a **knitr** document, you may not want to provide the filename or directory of the cache file, because they have reasonable defaults.

Side-effects (such as plots or printed output) will not be cached. The cache only stores the last value of the expression in `expr`.

### Examples

```
f = tempfile() # the cache file
compute = function(...) {
  res = xfun::cache_rds({
    Sys.sleep(1)
    1:10
  }, file = f, dir = "", ...)
  res
}
compute() # takes one second
compute() # returns 1:10 immediately
compute() # fast again
compute(rerun = TRUE) # one second to rerun
compute()
file.remove(f)
```

---

crandalf\_check

*Submit check jobs to crandalf*


---

### Description

Check the reverse dependencies of a package using the crandalf service: <https://github.com/yihui/crandalf>. If the number of reverse dependencies is large, they will be split into batches and pushed to crandalf one by one.

### Usage

```
crandalf_check(pkg, size = 400, jobs = Inf, which = "all")
```

```
crandalf_results(pkg, repo = NA, limit = 200, wait = 5 * 60)
```

### Arguments

<code>pkg</code>	The package name of which the reverse dependencies are to be checked.
<code>size</code>	The number of reverse dependencies to be checked in each job.
<code>jobs</code>	The number of jobs to run in Github Actions (by default, all jobs are submitted, but you can choose to submit the first few jobs).
<code>which</code>	The type of dependencies (see <a href="#">rev_check()</a> ).
<code>repo</code>	The crandalf repo on Github (of the form <code>user/repo</code> such as <code>"yihui/crandalf"</code> ). Usually you do not need to specify it, unless you are not calling this function inside the crandalf project, because <code>gh</code> should be able to figure out the repo automatically.

limit	The maximum of records for <code>gh run list</code> to retrieve. You only need a larger number if the check results are very early in the Github Action history.
wait	Number of seconds to wait if not all jobs have been completed on Github. By default, this function checks the status every 5 minutes until all jobs are completed. Set <code>wait</code> to 0 to disable waiting (and throw an error immediately when any jobs are not completed).

### Details

Due to the time limit of a single job on Github Actions (6 hours), you will have to split the large number of reverse dependencies into batches and check them sequentially on Github (at most 5 jobs in parallel). The function `crandalf_check()` does this automatically when necessary. It requires the `git` command to be available.

The function `crandalf_results()` fetches check results from Github after all checks are completed, merge the results, and show a full summary of check results. It requires `gh` (Github CLI: <https://cli.github.com/manual/>) to be installed and you also need to authenticate with your Github account beforehand.

---

csv\_options

*Parse comma-separated chunk options*

---

### Description

For **knitr** and R Markdown documents, code chunk options can be written using the comma-separated syntax (e.g., `opt1=value1, opt2=value2`). This function parses these options and returns a list. If an option is not named, it will be treated as the chunk label.

### Usage

```
csv_options(x)
```

### Arguments

`x` The chunk options as a string.

### Value

A list of chunk options.

### Examples

```
xfun::csv_options("foo, eval=TRUE, fig.width=5, echo=if (TRUE) FALSE")
```

---

decimal_dot	<i>Evaluate an expression after forcing the decimal point to be a dot</i>
-------------	---

---

**Description**

Sometimes it is necessary to use the dot character as the decimal separator. In R, this could be affected by two settings: the global option `options(OutDec)` and the `LC_NUMERIC` locale. This function sets the former to `.` and the latter to `C` before evaluating an expression, such as coercing a number to character.

**Usage**

```
decimal_dot(x)
```

**Arguments**

x	An expression.
---	----------------

**Value**

The value of x.

**Examples**

```
opts = options(OutDec = ",")
as.character(1.234) # using ',' as the decimal separator
print(1.234) # same
xfun::decimal_dot(as.character(1.234)) # using dot
xfun::decimal_dot(print(1.234)) # using dot
options(opts)
```

---

del_empty_dir	<i>Delete an empty directory</i>
---------------	----------------------------------

---

**Description**

Use `list.file()` to check if there are any files or subdirectories under a directory. If not, delete this empty directory.

**Usage**

```
del_empty_dir(dir)
```

**Arguments**

dir	Path to a directory. If NULL or the directory does not exist, no action will be performed.
-----	--

---

dir_create	<i>Create a directory recursively by default</i>
------------	--

---

**Description**

First check if a directory exists. If it does, return TRUE, otherwise create it with `dir.create(recursive = TRUE)` by default.

**Usage**

```
dir_create(x, recursive = TRUE, ...)
```

**Arguments**

x	A path name.
recursive	Whether to create all directory components in the path.
...	Other arguments to be passed to <code>dir.create()</code> .

**Value**

A logical value indicating if the directory either exists or is successfully created.

---

dir_exists	<i>Test the existence of files and directories</i>
------------	--

---

**Description**

These are wrapper functions of `[utils::file_test()]` to test the existence of directories and files. Note that `file_exists()` only tests files but not directories, which is the main difference between `file.exists()` in base R. If you use are using the R version 3.2.0 or above, `dir_exists()` is the same as `dir.exists()` in base R.

**Usage**

```
dir_exists(x)
```

```
file_exists(x)
```

**Arguments**

x	A vector of paths.
---	--------------------

**Value**

A logical vector.

---

`divide_chunk`*Divide chunk options from the code chunk body*

---

## Description

Chunk options can be written in special comments (e.g., after `#|` for R code chunks) inside a code chunk. This function partitions these options from the chunk body.

## Usage

```
divide_chunk(engine, code)
```

## Arguments

<code>engine</code>	The name of the language engine (to determine the appropriate comment character).
<code>code</code>	A character vector (lines of code).

## Value

A list with the following items:

- `options`: The parsed options (if there are any) as a list.
- `src`: The part of the input that contains the options.
- `code`: The part of the input that contains the code.

## Note

Chunk options must be written on *continuous* lines (i.e., all lines must start with the special comment prefix such as `#|`) at the beginning of the chunk body.

## Examples

```
# parse yaml-like items
yaml_like = c("#| label: mine", "#| echo: true", "#| fig.width: 8", "#| foo: bar",
             "1 + 1")
writeLines(yaml_like)
xfun::divide_chunk("r", yaml_like)

# parse CSV syntax
csv_like = c("#| mine, echo = TRUE, fig.width = 8, foo = 'bar'", "1 + 1")
writeLines(csv_like)
xfun::divide_chunk("r", csv_like)
```

---

download_cache	<i>Download a file from a URL and cache it on disk</i>
----------------	--

---

## Description

This object provides methods to download files and cache them on disk.

## Usage

```
download_cache
```

## Format

A list of methods:

- `$get(url, type, handler)` downloads a URL, caches it, and returns the file content according to the value of `type` (possible values: "text" means the text content; "base64" means the base64 encoded data; "raw" means the raw binary content; "auto" is the default and means the type is determined by the content type in the URL headers). Optionally a `handler` function can be applied to the content.
- `$list()` gives the list of cache files.
- `$summary()` gives a summary of existing cache files.
- `$remove(url, type)` removes a single cache file.
- `$purge()` deletes all cache files.

## Examples

```
# the first time it may take a few seconds
x1 = xfun::download_cache$get("https://www.r-project.org/")
head(x1)

# now you can get the cached content
x2 = xfun::download_cache$get("https://www.r-project.org/")
identical(x1, x2) # TRUE

# a binary file
x3 = xfun::download_cache$get("https://yihui.org/images/logo.png", "raw")
length(x3)

# show a summary
xfun::download_cache$summary()
# remove a specific cache file
xfun::download_cache$remove("https://yihui.org/images/logo.png", "raw")
# remove all cache files
xfun::download_cache$purge()
```



---

download_file	<i>Try various methods to download a file</i>
---------------	---

---

### Description

Try all possible methods in `download.file()` (e.g., `libcurl`, `curl`, `wget`, and `wininet`) and see if any method can succeed. The reason to enumerate all methods is that sometimes the default method does not work, e.g., <https://stat.ethz.ch/pipermail/r-devel/2016-June/072852.html>.

### Usage

```
download_file(  
  url,  
  output = url_filename(url),  
  ...,  
  .error = "No download method works (auto/wininet/wget/curl/lynx)"  
)
```

### Arguments

<code>url</code>	The URL of the file.
<code>output</code>	Path to the output file. By default, it is determined by <code>url_filename()</code> .
<code>...</code>	Other arguments to be passed to <code>download.file()</code> (except <code>method</code> ).
<code>.error</code>	An error message to signal when the download fails.

### Value

The integer code `0` for success, or an error if none of the methods work.

### Note

To allow downloading large files, the `timeout` option in `options()` will be temporarily set to one hour (3600 seconds) inside this function when this option has the default value of 60 seconds. If you want a different `timeout` value, you may set it via `options(timeout = N)`, where `N` is the number of seconds (not 60).

---

do_once	<i>Perform a task once in an R session</i>
---------	--

---

### Description

Perform a task once in an R session, e.g., emit a message or warning. Then give users an optional hint on how not to perform this task at all.

**Usage**

```
do_once(
  task,
  option,
  hint = c("You will not see this message again in this R session.",
           "If you never want to see this message,",
           sprintf("you may set options(%s = FALSE) in your .Rprofile.", option))
)
```

**Arguments**

task	Any R code expression to be evaluated once to perform a task, e.g., <code>warning('Danger!')</code> or <code>message('Today is ', Sys.Date())</code> .
option	An R option name. This name should be as unique as possible in <code>options()</code> . After the task has been successfully performed, this option will be set to FALSE in the current R session, to prevent the task from being performed again the next time when <code>do_once()</code> is called.
hint	A character vector to provide a hint to users on how not to perform the task or see the message again in the current R session. Set <code>hint = ""</code> if you do not want to provide the hint.

**Value**

The value returned by the task, invisibly.

**Examples**

```
do_once(message("Today's date is ", Sys.Date()), "xfun.date.reminder")
# if you run it again, it will not emit the message again
do_once(message("Today's date is ", Sys.Date()), "xfun.date.reminder")

do_once({
  Sys.sleep(2)
  1 + 1
}, "xfun.task.1plus1")
do_once({
  Sys.sleep(2)
  1 + 1
}, "xfun.task.1plus1")
```

## Description

For a file, first encode it into base64 data (a character string). Then generate a hyperlink of the form ‘<a href="base64 data" download="filename">Download filename</a>’. The file can be downloaded when the link is clicked in modern web browsers. For a directory, it will be compressed as a zip archive first, and the zip file is passed to `embed_file()`. For multiple files, they are also compressed to a zip file first.

## Usage

```
embed_file(path, name = basename(path), text = paste("Download", name), ...)
```

```
embed_dir(path, name = paste0(normalize_path(path), ".zip"), ...)
```

```
embed_files(path, name = with_ext(basename(path[1]), ".zip"), ...)
```

## Arguments

<code>path</code>	Path to the file(s) or directory.
<code>name</code>	The default filename to use when downloading the file. Note that for <code>embed_dir()</code> , only the base name (of the zip filename) will be used.
<code>text</code>	The text for the hyperlink.
<code>...</code>	For <code>embed_file()</code> , additional arguments to be passed to <code>htmltools::a()</code> (e.g., <code>class = 'foo'</code> ). For <code>embed_dir()</code> and <code>embed_files()</code> , arguments passed to <code>embed_file()</code> .

## Details

These functions can be called in R code chunks in R Markdown documents with HTML output formats. You may embed an arbitrary file or directory in the HTML output file, so that readers of the HTML page can download it from the browser. A common use case is to embed data files for readers to download.

## Value

An HTML tag ‘<a>’ with the appropriate attributes.

## Note

Windows users may need to install Rtools to obtain the zip command to use `embed_dir()` and `embed_files()`.

These functions require R packages **mime** and **htmltools**. If you have installed the **rmarkdown** package, these packages should be available, otherwise you need to install them separately.

Currently Internet Explorer does not support downloading embedded files (<https://caniuse.com/#feat=download>). Chrome has a 2MB limit on the file size.

**Examples**

```
logo = xfun::R_logo()
link = xfun::embed_file(logo, text = "Download R logo")
link
if (interactive()) htmltools::browsable(link)
```

---

env_option	<i>Retrieve a global option from both options() and environment variables</i>
------------	---

---

**Description**

If the option exists in `options()`, use its value. If not, query the environment variable with the name `R_NAME` where `NAME` is the capitalized option name with dots substituted by underscores. For example, for an option `xfun.foo`, first we try `getOption('xfun.foo')`; if it does not exist, we check the environment variable `R_XFUN_FOO`.

**Usage**

```
env_option(name, default = NULL)
```

**Arguments**

name	The option name.
default	The default value if the option is not found in <code>options()</code> or environment variables.

**Details**

This provides two possible ways, whichever is more convenient, for users to set an option. For example, global options can be set in the [.Rprofile](#) file, and environment variables can be set in the [.Renviron](#) file.

**Value**

The option value.

**Examples**

```
xfun::env_option("xfun.test.option") # NULL

Sys.setenv(R_XFUN_TEST_OPTION = "1234")
xfun::env_option("xfun.test.option") # 1234

options(xfun.test.option = TRUE)
xfun::env_option("xfun.test.option") # TRUE (from options())
options(xfun.test.option = NULL) # reset the option
xfun::env_option("xfun.test.option") # 1234 (from env var)
```

```

Sys.unsetenv("R_XFUN_TEST_OPTION")
xfun::env_option("xfun.test.option") # NULL again

xfun::env_option("xfun.test.option", FALSE) # use default

```

---

existing\_files      *Find file paths that exist*

---

### Description

This is a shorthand of `x[file.exists(x)]`, and optionally returns the first existing file path.

### Usage

```
existing_files(x, first = FALSE, error = TRUE)
```

### Arguments

<code>x</code>	A vector of file paths.
<code>first</code>	Whether to return the first existing path. If TRUE and no specified files exist, it will signal an error unless the argument <code>error = FALSE</code> .
<code>error</code>	Whether to throw an error when <code>first = TRUE</code> but no files exist. It can also take a character value, which will be used as the error message.

### Value

A vector of existing file paths.

### Examples

```
xfun::existing_files(c("foo.txt", system.file("DESCRIPTION", package = "xfun")))
```

---

exit\_call      *Call on.exit() in a parent function*

---

### Description

The function `on.exit()` is often used to perform tasks when the current function exits. This `exit_call()` function allows calling a function when a parent function exits (thinking of it as inserting an `on.exit()` call into the parent function).

### Usage

```
exit_call(fun, n = 2, ...)
```

**Arguments**

fun	A function to be called when the parent function exits.
n	The parent frame number. For n = 1, <code>exit_call(fun)</code> is the same as <code>on.exit(fun())</code> ; n = 2 means adding <code>on.exit(fun())</code> in the parent function; n = 3 means the grandparent, etc.
...	Other arguments to be passed to <code>on.exit()</code> .

**References**

This function was inspired by Kevin Ushey: <https://yihui.org/en/2017/12/on-exit-parent/>

**Examples**

```
f = function(x) {
  print(x)
  xfun::exit_call(function() print("The parent function is exiting!"))
}
g = function(y) {
  f(y)
  print("f() has been called!")
}
g("An argument of g()!")
```

---

fenced\_block

*Create a fenced block in Markdown*


---

**Description**

Wrap content with fence delimiters such as backticks (code blocks) or colons (fenced Div). Optionally the fenced block can have attributes.

**Usage**

```
fenced_block(x, attrs = NULL, fence = make_fence(x, char), char = "`")
```

```
make_fence(x, char = "`")
```

**Arguments**

x	A character vector of the block content.
attrs	A vector of block attributes.
fence	The fence string, e.g., <code>:::</code> or <code>```</code> . This will be generated from the <code>char</code> argument by default.
char	The fence character to be used to generate the fence string by default.

**Value**

fenced\_block() returns a character vector that contains both the fences and content.

make\_fence() returns a character string. If the block content contains N fence characters (e.g., backticks), use N + 1 characters as the fence.

**Examples**

```
# code block with class 'r' and ID 'foo'
xfun::fenced_block("1+1", c(".r", "#foo"))
# fenced Div
xfun::fenced_block("This is a Div.", char = ":")
# three backticks by default
xfun::make_fence("1+1")
# needs five backticks for the fences because content has four
xfun::make_fence(c("````r", "1+1", "````"))
```

---

file\_ext

*Manipulate filename extensions*


---

**Description**

Functions to obtain (file\_ext()), remove (sans\_ext()), and change (with\_ext()) extensions in filenames.

**Usage**

```
file_ext(x, extra = "")
```

```
sans_ext(x, extra = "")
```

```
with_ext(x, ext, extra = "")
```

**Arguments**

x	A character of file paths.
extra	Extra characters to be allowed in the extensions. By default, only alphanumeric characters are allowed (and also some special cases in ‘Details’). If other characters should be allowed, they can be specified in a character string, e.g., “-+!_#”.
ext	A vector of new extensions. It must be either of length 1, or the same length as x.

**Details**

file\_ext() is similar to [tools::file\\_ext\(\)](#), and sans\_ext() is similar to [tools::file\\_path\\_sans\\_ext\(\)](#). The main differences are that they treat tar.(gz|bz2|xz) and nb.html as extensions (but functions in the **tools** package doesn’t allow double extensions by default), and allow characters ~ and # to be present at the end of a filename.

**Value**

A character vector of the same length as `x`.

**Examples**

```
library(xfun)
p = c("abc.doc", "def123.tex", "path/to/foo.Rmd", "backup.ppt~", "pkg.tar.xz")
file_ext(p)
sans_ext(p)
with_ext(p, ".txt")
with_ext(p, c(".ppt", ".sty", ".Rnw", "doc", "zip"))
with_ext(p, "html")

# allow for more characters in extensions
p = c("a.c++", "b.c--", "c.e##")
file_ext(p) # -/+/# not recognized by default
file_ext(p, extra = "-+#")
```

---

file\_string

*Read a text file and concatenate the lines by '\n'*


---

**Description**

The source code of this function should be self-explanatory.

**Usage**

```
file_string(file)
```

**Arguments**

`file` Path to a text file (should be encoded in UTF-8).

**Value**

A character string of text lines concatenated by '\n'.

**Examples**

```
xfun::file_string(system.file("DESCRIPTION", package = "xfun"))
```



---

format_bytes	<i>Format numbers of bytes using a specified unit</i>
--------------	---

---

**Description**

Call the S3 method `format.object_size()` to format numbers of bytes.

**Usage**

```
format_bytes(x, units = "auto", ...)
```

**Arguments**

`x` A numeric vector (each element represents a number of bytes).  
`units, ...` Passed to `format()`.

**Value**

A character vector.

**Examples**

```
xfun::format_bytes(c(1, 1024, 2000, 1e+06, 2e+08))
xfun::format_bytes(c(1, 1024, 2000, 1e+06, 2e+08), units = "KB")
```

---

from_root	<i>Get the relative path of a path in a project relative to the current working directory</i>
-----------	---

---

**Description**

First compose an absolute path using the project root directory and the relative path components, i.e., `file.path(root, ...)`. Then convert it to a relative path with `relative_path()`, which is relative to the current working directory.

**Usage**

```
from_root(..., root = proj_root(), error = TRUE)
```

**Arguments**

`...` A character vector of path components *relative to the root directory of the project*.  
`root` The root directory of the project.  
`error` Whether to signal an error if the path cannot be converted to a relative path.

**Details**

This function was inspired by `here::here()`, and the major difference is that it returns a relative path by default, which is more portable.

**Value**

A relative path, or an error when the project root directory cannot be determined or the conversion failed and `error = TRUE`.

**Examples**

```
## Not run:
xfun::from_root("data", "mtcars.csv")

## End(Not run)
```

---

github_releases	<i>Get the tags of Github releases of a repository</i>
-----------------	--

---

**Description**

Use the Github API (`github_api()`) to obtain the tags of the releases.

**Usage**

```
github_releases(
  repo,
  tag = "",
  pattern = "v[0-9.]+",
  use_jsonlite = loadable("jsonlite")
)
```

**Arguments**

repo	The repository name of the form <code>user/repo</code> , e.g., <code>"yihui/xfun"</code> .
tag	A tag as a character string. If provided, it will be returned if the tag exists. If <code>tag = "latest"</code> , the tag of the latest release is returned.
pattern	A regular expression to match the tags.
use_jsonlite	Whether to use <b>jsonlite</b> to parse the releases info.

**Value**

A character vector of (GIT) tags.

**Examples**

```
xfun::github_releases("yihui/xfun")
xfun::github_releases("gohugoio/hugo")
```

---

grep_sub	<i>Perform replacement with gsub() on elements matched from grep()</i>
----------	--

---

**Description**

This function is a shorthand of `gsub(pattern, replacement, grep(pattern, x, value = TRUE))`.

**Usage**

```
grep_sub(pattern, replacement, x, ...)
```

**Arguments**

pattern, replacement, x, ...  
 Passed to `grep()` and `gsub()`.

**Value**

A character vector.

**Examples**

```
# find elements that matches 'a[b]+c' and capitalize 'b' with perl regex
xfun::grep_sub("a([b]+)c", "a\\U\\1c", c("abc", "abbbc", "addc", "123"), perl = TRUE)
```

---

gsub_file	<i>Search and replace strings in files</i>
-----------	--

---

**Description**

These functions provide the "file" version of `gsub()`, i.e., they perform searching and replacement in files via `gsub()`.

**Usage**

```
gsub_file(file, ..., rw_error = TRUE)

gsub_files(files, ...)

gsub_dir(..., dir = ".", recursive = TRUE, ext = NULL, mimetype = ".*")

gsub_ext(ext, ..., dir = ".", recursive = TRUE)
```

**Arguments**

file	Path of a single file.
...	For gsub_file(), arguments passed to gsub(). For other functions, arguments passed to gsub_file(). Note that the argument x of gsub() is the content of the file.
rw_error	Whether to signal an error if the file cannot be read or written. If FALSE, the file will be ignored (with a warning).
files	A vector of file paths.
dir	Path to a directory (all files under this directory will be replaced).
recursive	Whether to find files recursively under a directory.
ext	A vector of filename extensions (without the leading periods).
mimetype	A regular expression to filter files based on their MIME types, e.g., '^text/' for plain text files. This requires the <b>mime</b> package.

**Note**

These functions perform in-place replacement, i.e., the files will be overwritten. Make sure you backup your files in advance, or use version control!

**Examples**

```
library(xfun)
f = tempfile()
writeLines(c("hello", "world"), f)
gsub_file(f, "world", "woRld", fixed = TRUE)
readLines(f)
```

---

install\_dir

*Install a source package from a directory*


---

**Description**

Run R CMD build to build a tarball from a source directory, and run R CMD INSTALL to install it.

**Usage**

```
install_dir(pkg, build = TRUE, build_opts = NULL, install_opts = NULL)
```

**Arguments**

pkg	The package source directory.
build	Whether to build a tarball from the source directory. If FALSE, run R CMD INSTALL on the directory directly (note that vignettes will not be automatically built).
build_opts	The options for R CMD build.
install_opts	The options for R CMD INSTALL.

**Value**

Invisible status from R CMD INSTALL.

---

install_github	<i>An alias of</i> <code>remotes::install_github()</code>
----------------	---

---

**Description**

This alias is to make autocomplete faster via `xfun::install_github`, because most `remotes::install_*` functions are never what I want. I only use `install_github` and it is inconvenient to autocomplete it, e.g. `install_git` always comes before `install_github`, but I never use it. In RStudio, I only need to type `xfun::ig` to get `xfun::install_github`.

**Usage**

```
install_github(...)
```

**Arguments**

... Arguments to be passed to `remotes::install_github()`.

---

in_dir	<i>Evaluate an expression under a specified working directory</i>
--------	---

---

**Description**

Change the working directory, evaluate the expression, and restore the working directory.

**Usage**

```
in_dir(dir, expr)
```

**Arguments**

`dir` Path to a directory.  
`expr` An R expression.

**Examples**

```
library(xfun)
in_dir(tempdir(), {
  print(getwd())
  list.files()
})
```

---

is_abs_path	<i>Test if paths are relative or absolute</i>
-------------	---

---

**Description**

On Unix, check if the paths start with '/' or '~' (if they do, they are absolute paths). On Windows, check if a path remains the same (via [same\\_path\(\)](#)) if it is prepended with './' (if it does, it is a relative path).

**Usage**

```
is_abs_path(x)
```

```
is_rel_path(x)
```

**Arguments**

x                   A vector of paths.

**Value**

A logical vector.

**Examples**

```
xfun::is_abs_path(c("C:/foo", "foo.txt", "/Users/john/", tempdir()))
xfun::is_rel_path(c("C:/foo", "foo.txt", "/Users/john/", tempdir()))
```

---

is_ascii	<i>Check if a character vector consists of entirely ASCII characters</i>
----------	--

---

**Description**

Converts the encoding of a character vector to 'ascii', and check if the result is NA.

**Usage**

```
is_ascii(x)
```

**Arguments**

x                   A character vector.

**Value**

A logical vector indicating whether each element of the character vector is ASCII.

**Examples**

```
library(xfun)
is_ascii(letters) # yes
is_ascii(intToUtf8(8212)) # no
```

---

is_blank	<i>Test if a character vector consists of blank strings</i>
----------	---

---

**Description**

Return a logical vector indicating if elements of a character vector are blank (white spaces or empty strings).

**Usage**

```
is_blank(x)
```

**Arguments**

x                    A character vector.

**Value**

TRUE for blank elements, or FALSE otherwise.

**Examples**

```
xfun::is_blank("")
xfun::is_blank("abc")
xfun::is_blank(c("", " ", "\n\t"))
xfun::is_blank(c("", " ", "abc"))
```

---

is_sub_path	<i>Test if a path is a subpath of a dir</i>
-------------	---

---

**Description**

Check if the path starts with the dir path.

**Usage**

```
is_sub_path(x, dir, n = nchar(dir))
```

**Arguments**

x                    A vector of paths.  
 dir                  A vector of directory paths.  
 n                    The length of dir paths.

**Value**

A logical vector.

**Note**

You may want to normalize the values of the x and dir arguments first (with `normalize_path()`), to make sure the path separators are consistent.

**Examples**

```
xfun::is_sub_path("a/b/c.txt", "a/b") # TRUE
xfun::is_sub_path("a/b/c.txt", "d/b") # FALSE
xfun::is_sub_path("a/b/c.txt", "a\\b") # FALSE (even on Windows)
```

---

 is\_web\_path

*Test if a path is a web path*


---

**Description**

Check if a path starts with 'http://' or 'https://' or 'ftp://' or 'ftps://'.

**Usage**

```
is_web_path(x)
```

**Arguments**

x                    A vector of paths.

**Value**

A logical vector.

**Examples**

```
xfun::is_web_path("https://www.r-project.org") # TRUE
xfun::is_web_path("www.r-project.org") # FALSE
```



---

is_windows	<i>Test for types of operating systems</i>
------------	--

---

**Description**

Functions based on `.Platform$OS.type` and `Sys.info()` to test if the current operating system is Windows, macOS, Unix, or Linux.

**Usage**

```
is_windows()

is_unix()

is_macos()

is_linux()

is_arm64()
```

**Examples**

```
library(xfun)
# only one of the following statements should be true
is_windows()
is_unix() && is_macos()
is_linux()
# In newer Macs, CPU can be either Intel or Apple
is_arm64() # TRUE on Apple silicone machines
```

---

magic_path	<i>Find a file or directory under a root directory</i>
------------	--

---

**Description**

Given a path, try to find it recursively under a root directory. The input path can be an incomplete path, e.g., it can be a base filename, and `magic_path()` will try to find this file under subdirectories.

**Usage**

```
magic_path(
  ...,
  root = proj_root(),
  relative = TRUE,
  error = TRUE,
  message = getOption("xfun.magic_path.message", TRUE),
  n_dirs = getOption("xfun.magic_path.n_dirs", 10000)
)
```

**Arguments**

...	A character vector of path components.
root	The root directory under which to search for the path. If NULL, the current working directory is used.
relative	Whether to return a relative path.
error	Whether to signal an error if the path is not found, or multiple paths are found.
message	Whether to emit a message when multiple paths are found and error = FALSE.
n_dirs	The number of subdirectories to recursively search. The recursive search may be time-consuming when there are a large number of subdirectories under the root directory. If you really want to search for all subdirectories, you may try n_dirs = Inf.

**Value**

The path found under the root directory, or an error when error = TRUE and the path is not found (or multiple paths are found).

**Examples**

```
## Not run:
xfun::magic_path("mtcars.csv") # find any file that has the base name mtcars.csv

## End(Not run)
```

---

mark_dirs	<i>Mark some paths as directories</i>
-----------	---------------------------------------

---

**Description**

Add a trailing backlash to a file path if this is a directory. This is useful in messages to the console for example to quickly identify directories from files.

**Usage**

```
mark_dirs(x)
```

**Arguments**

x	Character vector of paths to files and directories.
---	---

**Details**

If x is a vector of relative paths, directory test is done with path relative to the current working dir. Use `in_dir()` or use absolute paths.

**Examples**

```
mark_dirs(list.files(find.package("xfun"), full.names = TRUE))
```

---

`msg_cat`*Generate a message with `cat()`*

---

## Description

This function is similar to `message()`, and the difference is that `msg_cat()` uses `cat()` to write out the message, which is sent to `stdout()` instead of `stderr()`. The message can be suppressed by `suppressMessages()`.

## Usage

```
msg_cat(...)
```

## Arguments

... Character strings of messages, which will be concatenated into one string via `paste(c(...), collapse = '')`.

## Value

Invisible NULL, with the side-effect of printing the message.

## Note

By default, a newline will not be appended to the message. If you need a newline, you have to explicitly add it to the message (see 'Examples').

## See Also

This function was inspired by `rlang::inform()`.

## Examples

```
{
  # a message without a newline at the end
  xfun::msg_cat("Hello world!")
  # add a newline at the end
  xfun::msg_cat(" This message appears right after the previous one.\n")
}
suppressMessages(xfun::msg_cat("Hello world!"))
```

---

native_encode	<i>Try to use the system native encoding to represent a character vector</i>
---------------	--

---

### Description

Apply `enc2native()` to the character vector, and check if `enc2utf8()` can convert it back without a loss. If it does, return `enc2native(x)`, otherwise return the original vector with a warning.

### Usage

```
native_encode(x)
```

### Arguments

`x`                    A character vector.

### Note

On platforms that supports UTF-8 as the native encoding (`l10n_info()[['UTF-8']]` returns TRUE), the conversion will be skipped.

### Examples

```
library(xfun)
s = intToUtf8(c(20320, 22909))
Encoding(s)

s2 = native_encode(s)
Encoding(s2)
```

---

news2md	<i>Convert package news to the Markdown format</i>
---------	--

---

### Description

Read the package news with `news()`, convert the result to Markdown, and write to an output file (e.g., 'NEWS.md'). Each package version appears in a first-level header, each category (e.g., 'NEW FEATURES' or 'BUG FIXES') is in a second-level header, and the news items are written into bullet lists.

### Usage

```
news2md(package, ..., output = "NEWS.md", category = TRUE)
```

**Arguments**

package, ... Arguments to be passed to `news()`.  
output The output file path.  
category Whether to keep the category names.

**Value**

If `output = NA`, returns the Markdown content as a character vector, otherwise the content is written to the output file.

**Examples**

```
# news for the current version of R  
xfun::news2md("R", Version == getRversion(), output = NA)
```

---

normalize_path	<i>Normalize paths</i>
----------------	------------------------

---

**Description**

A wrapper function of `normalizePath()` with different defaults.

**Usage**

```
normalize_path(x, winslash = "/", must_work = FALSE, resolve_symlink = TRUE)
```

**Arguments**

x, winslash, must\_work Arguments passed to `normalizePath()`.  
resolve\_symlink Whether to resolve symbolic links.

**Examples**

```
library(xfun)  
normalize_path("~/")
```

---

numbers\_to\_words      *Convert numbers to English words*

---

### Description

This can be helpful when writing reports with **knitr/rmarkdown** if we want to print numbers as English words in the output. The function `n2w()` is an alias of `numbers_to_words()`.

### Usage

```
numbers_to_words(x, cap = FALSE, hyphen = TRUE, and = FALSE)
```

```
n2w(x, cap = FALSE, hyphen = TRUE, and = FALSE)
```

### Arguments

<code>x</code>	A numeric vector. The absolute values should be less than $1e15$ .
<code>cap</code>	Whether to capitalize the first letter of the word. This can be useful when the word is at the beginning of a sentence. Default is <code>FALSE</code> .
<code>hyphen</code>	Whether to insert hyphen (-) when the number is between 21 and 99 (except 30, 40, etc.).
<code>and</code>	Whether to insert and between hundreds and tens, e.g., write 110 as “one hundred and ten” if <code>TRUE</code> instead of “one hundred ten”.

### Value

A character vector.

### Author(s)

Daijiang Li

### Examples

```
library(xfun)
n2w(0, cap = TRUE)
n2w(0:121, and = TRUE)
n2w(1e+06)
n2w(1e+11 + 12345678)
n2w(-987654321)
n2w(1e+15 - 1)
n2w(123.456)
n2w(123.45678901)
n2w(123.456789098765)
```

---

optipng	<i>Run OptiPNG on all PNG files under a directory</i>
---------	---

---

**Description**

Call the command `optipng` via `system2()` to optimize all PNG files under a directory.

**Usage**

```
optipng(dir = ".", files = all_files("[.]png$", dir), ...)
```

**Arguments**

<code>dir</code>	Path to a directory.
<code>files</code>	Alternatively, you can choose the specific files to optimize.
<code>...</code>	Arguments to be passed to <code>system2()</code> .

**References**

OptiPNG: <https://optipng.sourceforge.net>.

---

<code>parse_only</code>	<i>Parse R code and do not keep the source</i>
-------------------------	--

---

**Description**

An abbreviation of `parse(keep.source = FALSE)`.

**Usage**

```
parse_only(code)
```

**Arguments**

<code>code</code>	A character vector of the R source code.
-------------------	--

**Value**

R `expression()`s.

**Examples**

```
library(xfun)
parse_only("1+1")
parse_only(c("y~x", "1:5 # a comment"))
parse_only(character(0))
```

---

pkg_attach	<i>Attach or load packages, and automatically install missing packages if requested</i>
------------	---

---

## Description

pkg\_attach() is a vectorized version of `library()` over the package argument to attach multiple packages in a single function call. pkg\_load() is a vectorized version of `requireNamespace()` to load packages (without attaching them). The functions `pkg_attach2()` and `pkg_load2()` are wrappers of `pkg_attach(install = TRUE)` and `pkg_load(install = TRUE)`, respectively. `loadable()` is an abbreviation of `requireNamespace(quietly = TRUE)`. `pkg_available()` tests if a package with a minimal version is available.

## Usage

```
pkg_attach(
  ...,
  install = FALSE,
  message = getOption("xfun.pkg_attach.message", TRUE)
)
```

```
pkg_load(..., error = TRUE, install = FALSE)
```

```
loadable(pkg, strict = TRUE, new_session = FALSE)
```

```
pkg_available(pkg, version = NULL)
```

```
pkg_attach2(...)
```

```
pkg_load2(...)
```

## Arguments

...	Package names (character vectors, and must always be quoted).
install	Whether to automatically install packages that are not available using <code>install.packages()</code> . Besides TRUE and FALSE, the value of this argument can also be a function to install packages ( <code>install = TRUE</code> is equivalent to <code>install = install.packages</code> ), or a character string "pak" (equivalent to <code>install = pak::pkg_install</code> , which requires the <b>pak</b> package). You are recommended to set a CRAN mirror in the global option <code>repos</code> via <code>options()</code> if you want to automatically install packages.
message	Whether to show the package startup messages (if any startup messages are provided in a package).
error	Whether to signal an error when certain packages cannot be loaded.
pkg	A single package name.



strict	If TRUE, use <code>requireNamespace()</code> to test if a package is loadable; otherwise only check if the package is in <code>.packages(TRUE)</code> (this does not really load the package, so it is less rigorous but on the other hand, it can keep the current R session clean).
new_session	Whether to test if a package is loadable in a new R session. Note that <code>new_session = TRUE</code> implies <code>strict = TRUE</code> .
version	A minimal version number. If NULL, only test if a package is available and do not check its version.

### Details

These are convenience functions that aim to solve these common problems: (1) We often need to attach or load multiple packages, and it is tedious to type several `library()` calls; (2) We are likely to want to install the packages when attaching/loading them but they have not been installed.

### Value

`pkg_attach()` returns NULL invisibly. `pkg_load()` returns a logical vector, indicating whether the packages can be loaded.

### See Also

`pkg_attach2()` is similar to `pacman::p_load()`, but does not allow non-standard evaluation (NSE) of the `...` argument, i.e., you must pass a real character vector of package names to it, and all names must be quoted. Allowing NSE adds too much complexity with too little gain (the only gain is that it saves your effort in typing two quotes).

### Examples

```
library(xfun)
pkg_attach("stats", "graphics")
# pkg_attach2('servr') # automatically install servr if it is not installed

(pkg_load("stats", "graphics"))
```

---

process_file	<i>Read a text file, process the text with a function, and write the text back</i>
--------------	--

---

### Description

Read a text file with the UTF-8 encoding, apply a function to the text, and write back to the original file if the processed text is different with the original input.

### Usage

```
process_file(file, fun = identity, x = read_utf8(file))

sort_file(..., fun = sort)
```

**Arguments**

file	Path to a text file.
fun	A function to process the text.
x	The content of the file.
...	Arguments to be passed to process_file().

**Details**

sort\_file() is an application of process\_file(), with the processing function being `sort()`, i.e., it sorts the text lines in a file and write back the sorted text.

**Value**

If file is provided, invisible NULL (the file is updated as a side effect), otherwise the processed content (as a character vector).

**Examples**

```
f = tempfile()
xfun::write_utf8("Hello World", f)
xfun::process_file(f, function(x) gsub("World", "woRld", x))
xfun::read_utf8(f) # see if it has been updated
file.remove(f)
```

---

proc\_kill

*Kill a process and (optionally) all its child processes*


---

**Description**

Run the command `taskkill /f /pid` on Windows and `kill` on Unix, respectively, to kill a process.

**Usage**

```
proc_kill(pid, recursive = TRUE, ...)
```

**Arguments**

pid	The process ID.
recursive	Whether to kill the child processes of the process.
...	Arguments to be passed to <code>system2()</code> to run the command to kill the process.

**Value**

The status code returned from `system2()`.

---

proj_root	<i>Return the (possible) root directory of a project</i>
-----------	--

---

### Description

Given a path of a file (or dir) in a potential project (e.g., an R package or an RStudio project), return the path to the project root directory.

### Usage

```
proj_root(path = "./", rules = root_rules)
```

```
root_rules
```

### Arguments

**path** The initial path to start the search. If it is a file path, its parent directory will be used.

**rules** A matrix of character strings of two columns: the first column contains regular expressions to look for filenames that match the patterns, and the second column contains regular expressions to match the content of the matched files. The regular expression can be an empty string, meaning that it will match anything.

### Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

### Details

The search for the root directory is performed by a series of tests, currently including looking for a 'DESCRIPTION' file that contains `Package: *` (which usually indicates an R package), and a '\*.Rproj' file that contains `Version: *` (which usually indicates an RStudio project). If files with the expected patterns are not found in the initial directory, the search will be performed recursively in upper-level directories.

### Value

Path to the root directory if found, otherwise `NULL`.

### Note

This function was inspired by the **rprojroot** package, but is much less sophisticated. It is a rather simple function designed to be used in some of packages that I maintain, and may not meet the need of general users until this note is removed in the future (which should be unlikely). If you are sure that you are working on the types of projects mentioned in the 'Details' section, this function may be helpful to you, otherwise please consider using **rprojroot** instead.

---

prose_index	<i>Find the indices of lines in Markdown that are prose (not code blocks)</i>
-------------	---

---

### Description

Filter out the indices of lines between code block fences such as ````` (could be three or four or more backticks).

### Usage

```
prose_index(x, warn = TRUE)
```

### Arguments

x	A character vector of text in Markdown.
warn	Whether to emit a warning when code fences are not balanced.

### Value

An integer vector of indices of lines that are prose in Markdown.

### Note

If the code fences are not balanced (e.g., a starting fence without an ending fence), this function will treat all lines as prose.

### Examples

```
library(xfun)
prose_index(c("a", "```", "b", "```", "c"))
prose_index(c("a", "```", "```r", "1+1", "```", "```", "c"))
```

---

protect_math	<i>Protect math expressions in pairs of backticks in Markdown</i>
--------------	---

---

### Description

For Markdown renderers that do not support LaTeX math, we need to protect math expressions as verbatim code (in a pair of backticks), because some characters in the math expressions may be interpreted as Markdown syntax (e.g., a pair of underscores may make text italic). This function detects math expressions in Markdown (by heuristics), and wrap them in backticks.

### Usage

```
protect_math(x, token = "")
```

**Arguments**

x	A character vector of text in Markdown.
token	A character string to wrap math expressions at both ends. This can be a unique token so that math expressions can be reliably identified and restored after the Markdown text is converted.

**Details**

Expressions in pairs of dollar signs or double dollar signs are treated as math, if there are no spaces after the starting dollar sign, or before the ending dollar sign. There should be spaces before the starting dollar sign, unless the math expression starts from the very beginning of a line. For a pair of single dollar signs, the ending dollar sign should not be followed by a number. With these assumptions, there should not be too many false positives when detecting math expressions.

Besides, LaTeX environments (`\begin{*}` and `\end{*}`) are also protected in backticks.

**Value**

A character vector with math expressions in backticks.

**Note**

If you are using Pandoc or the **rmarkdown** package, there is no need to use this function, because Pandoc's Markdown can recognize math expressions.

**Examples**

```
library(xfun)
protect_math(c("hi $a+b$", "hello $$\\alpha$$", "no math here: $x is $10 dollars"))
protect_math(c("hi $$", "\\begin{equation}", "x + y = z", "\\end{equation}"))
protect_math("$a+b$", "===")
```

---

raw\_string

---

*Print a character vector in its raw form*


---

**Description**

The function `raw_string()` assigns the class `xfun_raw_string` to the character vector, and the corresponding printing function `print.xfun_raw_string()` uses `cat(x, sep = '\n')` to write the character vector to the console, which will suppress the leading indices (such as `[1]`) and double quotes, and it may be easier to read the characters in the raw form (especially when there are escape sequences).

**Usage**

```
raw_string(x)

## S3 method for class 'xfun_raw_string'
print(x, ...)
```

**Arguments**

`x` For `raw_string()`, a character vector. For the print method, the `raw_string()` object.

`...` Other arguments (currently ignored).

**Examples**

```
library(xfun)
raw_string(head(LETTERS))
raw_string(c("a\b", "hello\tworld!"))
```

---

read\_all

*Read all text files and concatenate their content*

---

**Description**

Read files one by one, and optionally add text before/after the content. Then combine all content into one character vector.

**Usage**

```
read_all(files, before = function(f) NULL, after = function(f) NULL)
```

**Arguments**

`files` A vector of file paths.

`before`, `after` A function that takes one file path as the input and returns values to be added before or after the content of the file. Alternatively, they can be constant values to be added.

**Value**

A character vector.

**Examples**

```
# two files in this package
fs = system.file("scripts", c("call-fun.R", "child-pids.sh"), package = "xfun")
xfun::read_all(fs)

# add file paths before file content and an empty line after content
xfun::read_all(fs, before = function(f) paste("#-----", f, "-----"), after = "")

# add constants
xfun::read_all(fs, before = "/*", after = c("*/", ""))
```

---

read_bin	<i>Read all records of a binary file as a raw vector by default</i>
----------	---

---

### Description

This is a wrapper function of `readBin()` with default arguments `what = "raw"` and `n = file.size(file)`, which means it will read the full content of a binary file as a raw vector by default.

### Usage

```
read_bin(file, what = "raw", n = file.info(file)$size, ...)
```

### Arguments

`file`, `what`, `n`, ...  
Arguments to be passed to `readBin()`.

### Value

A vector returned from `readBin()`.

### Examples

```
f = tempfile()
cat("abc", file = f)
xfun::read_bin(f)
unlink(f)
```

---

read_utf8	<i>Read / write files encoded in UTF-8</i>
-----------	--

---

### Description

Read or write files, assuming they are encoded in UTF-8. `read_utf8()` is roughly `readLines(encoding = 'UTF-8')` (a warning will be issued if non-UTF8 lines are found), and `write_utf8()` calls `writeLines(enc2utf8(text), useBytes = TRUE)`.

### Usage

```
read_utf8(con, error = FALSE)

write_utf8(text, con, ...)

append_utf8(text, con, sort = TRUE)

append_unique(text, con, sort = function(x) base::sort(unique(x)))
```

**Arguments**

con	A connection or a file path.
error	Whether to signal an error when non-UTF8 characters are detected (if FALSE, only a warning message is issued).
text	A character vector (will be converted to UTF-8 via <code>enc2utf8()</code> ).
...	Other arguments passed to <code>writelnLines()</code> (except <code>useBytes</code> , which is TRUE in <code>write_utf8()</code> ).
sort	Logical (FALSE means not to sort the content) or a function to sort the content; TRUE is equivalent to <code>base::sort</code> .

**Details**

The function `append_utf8()` appends UTF-8 content to a file or connection based on `read_utf8()` and `write_utf8()`, and optionally sort the content. The function `append_unique()` appends unique lines to a file or connection.

---

record	<i>Run R code and record the results</i>
--------	--

---

**Description**

Run R code and capture various types of output, including text output, plots, messages, warnings, and errors.

**Usage**

```
record(
  code = NULL,
  dev = "png",
  dev.path = tempfile("record-", "."),
  dev.ext = dev_ext(dev),
  dev.args = list(),
  error = FALSE,
  verbose = getOption("xfun.record.verbose", 0),
  envir = parent.frame()
)

## S3 method for class 'xfun_record_results'
format(x, to = c("text", "html"), encode = FALSE, template = FALSE, ...)

## S3 method for class 'xfun_record_results'
print(
  x,
  browse = interactive(),
  to = if (browse) "html" else "text",
```



```

    template = TRUE,
    ...
  )

```

### Arguments

<code>code</code>	A character vector of R source code.
<code>dev</code>	A graphics device. It can be a function name, a function, or a character string that can be evaluated to a function to open a graphics device.
<code>dev.path</code>	A base file path for plots (by default, a temporary path under the current working directory). Actual plot filenames will be this base path plus incremental suffixes. For example, if <code>dev.path = "foo"</code> , the plot files will be <code>foo-1.png</code> , <code>foo-2.png</code> , and so on. If <code>dev.path</code> is not character (e.g., <code>FALSE</code> ), plots will not be recorded.
<code>dev.ext</code>	The file extension for plot files. By default, it will be inferred from the first argument of the device function if possible.
<code>dev.args</code>	Extra arguments to be passed to the device. The default arguments are <code>list(units = 'in', onefile = FALSE, width = 7, height = 7, res = 96)</code> . If any of these arguments is not present in the device function, it will be dropped.
<code>error</code>	Whether to record errors. If <code>TRUE</code> , errors will not stop the execution and error messages will be recorded. If <code>FALSE</code> , errors will be thrown normally.
<code>verbose</code>	2 means to always print the value of each expression in the code, no matter if the value is <code>invisible()</code> or not; 1 means to always print the value of the last expression; 0 means no special handling (i.e., print only when the value is visible).
<code>envir</code>	An environment in which the code is evaluated.
<code>x</code>	An object returned by <code>record()</code> .
<code>to</code>	The output format (text or html).
<code>encode</code>	For HTML output, whether to base64 encode plots.
<code>template</code>	For HTML output, whether to embed the formatted results in an HTML template. Alternatively, this argument can take a file path, i.e., path to an HTML template that contains the variable <code>\$body\$</code> . If <code>TRUE</code> , the default template in this package will be used ( <code>xfun::pkg_file('resources', 'record.html')</code> ).
<code>...</code>	Currently ignored.
<code>browse</code>	Whether to browse the results on an HTML page.

### Value

`record()` returns a list of the class `xfun_record_results` that contains elements with these possible classes: `record_source` (source code), `record_output` (text output), `record_plot` (plot file paths), `record_message` (messages), `record_warning` (warnings), and `record_error` (errors, only when the argument `error = TRUE`).

The `format()` method returns a character vector of plain-text output or HTML code for displaying the results.

The `print()` method prints the results as plain text or HTML to the console or displays the HTML page.

**Examples**

```
code = c("# a message test", "1:2 + 1:3", "par(mar = c(4, 4, 1, .2))",
        "barplot(5:1, col = 2:6, horiz = TRUE)", "head(iris)",
        "sunflowerplot(iris[, 3:4], seg.col = 'purple')",
        "if (TRUE) {\n  message('Hello, xfun::record()!')\n}",
        "# throw an error", "1 + 'a'")
res = xfun::record(code, dev.args = list(width = 9, height = 6.75),
                  error = TRUE)
xfun::tree(res)
format(res)
# find and clean up plot files
plots = Filter(function(x) inherits(x, "record_plot"),
               res)
file.remove(unlist(plots))
```

---

relative\_path

*Get the relative path of a path relative to a directory*


---

**Description**

Given a directory, return the relative path that is relative to this directory. For example, the path 'foo/bar.txt' relative to the directory 'foo/' is 'bar.txt', and the path '/a/b/c.txt' relative to '/d/e/' is '.././a/b/c.txt'.

**Usage**

```
relative_path(x, dir = ".", use.. = TRUE, error = TRUE)
```

**Arguments**

x	A vector of paths to be converted to relative paths.
dir	Path to a directory.
use..	Whether to use double-dots ('..') in the relative path. A double-dot indicates the parent directory (starting from the directory provided by the dir argument).
error	Whether to signal an error if a path cannot be converted to a relative path.

**Value**

A vector of relative paths if the conversion succeeded; otherwise the original paths when error = FALSE, and an error when error = TRUE.

**Examples**

```
xfun::relative_path("foo/bar.txt", "foo/")
xfun::relative_path("foo/bar/a.txt", "foo/haha/")
xfun::relative_path(getwd())
```

---

 rename\_seq

*Rename files with a sequential numeric prefix*


---

### Description

Rename a series of files and add an incremental numeric prefix to the filenames. For example, files 'a.txt', 'b.txt', and 'c.txt' can be renamed to '1-a.txt', '2-b.txt', and '3-c.txt'.

### Usage

```
rename_seq(
  pattern = "[0-9]+-[.]Rmd$",
  format = "auto",
  replace = TRUE,
  start = 1,
  dry_run = TRUE
)
```

### Arguments

pattern	A regular expression for <code>list.files()</code> to obtain the files to be renamed. For example, to rename .jpeg files, use <code>pattern = "[.]jpeg\$"</code> .
format	The format for the numeric prefix. This is passed to <code>sprintf()</code> . The default format is <code>"\%0Nd"</code> where $N = \text{floor}(\log_{10}(n)) + 1$ and $n$ is the number of files, which means the prefix may be padded with zeros. For example, if there are 150 files to be renamed, the format will be <code>"\%03d"</code> and the prefixes will be 001, 002, ..., 150.
replace	Whether to remove existing numeric prefixes in filenames.
start	The starting number for the prefix (it can start from 0).
dry_run	Whether to not really rename files. To be safe, the default is TRUE. If you have looked at the new filenames and are sure the new names are what you want, you may rerun <code>rename_seq()</code> with <code>dry_run = FALSE</code> to actually rename files.

### Value

A named character vector. The names are original filenames, and the vector itself is the new filenames.

### Examples

```
xfun::rename_seq()
xfun::rename_seq("[.](jpeg|png)$", format = "%04d")
```

rest\_api

*Get data from a REST API***Description**

Read data from a REST API and optionally with an authorization token in the request header. The function `rest_api_raw()` returns the raw text of the response, and `rest_api()` will parse the response with `jsonlite::fromJSON()` (assuming that the response is in the JSON format).

**Usage**

```
rest_api(...)

rest_api_raw(root, endpoint, token = "", params = list(), headers = NULL)

github_api(
  endpoint,
  token = "",
  params = list(),
  headers = NULL,
  raw = !loadable("jsonlite")
)
```

**Arguments**

<code>...</code>	Arguments to be passed to <code>rest_api_raw()</code> .
<code>root</code>	The API root URL.
<code>endpoint</code>	The API endpoint.
<code>token</code>	A named character string (e.g., <code>c(token = "xxxx")</code> ), which will be used to create an authorization header of the form 'Authorization: NAME TOKEN' for the API call, where 'NAME' is the name of the string and 'TOKEN' is the string. If the string does not have a name, 'Basic' will be used as the default name.
<code>params</code>	A list of query parameters to be sent with the API call.
<code>headers</code>	A named character vector of HTTP headers, e.g., <code>c(Accept = "application/vnd.github.v3+json")</code> .
<code>raw</code>	Whether to return the raw response or parse the response with <b>jsonlite</b> .

**Details**

These functions are simple wrappers based on `url()` and `read_utf8()`. Specifically, the `headers` argument is passed to `url()`, and `read_utf8()` will send a 'GET' request to the API server. This means these functions only support the 'GET' method. If you need to use other HTTP methods (such as 'POST'), you have to use other packages such as **curl** and **httr**.

`github_api()` is a wrapper function based on `rest_api_raw()` to obtain data from the Github API: <https://docs.github.com/en/rest>. You can provide a personal access token (PAT) via the `token` argument, or via one of the environment variables `GITHUB_PAT`, `GITHUB_TOKEN`, `GH_TOKEN`. A PAT allows for a much higher rate limit in API calls. Without a token, you can only make 60 calls in an hour.

**Value**

A character vector (the raw JSON response) or an R object parsed from the JSON text.

**Examples**

```
# a normal GET request
xfun::rest_api("https://httpbin.org", "/get")
xfun::rest_api_raw("https://httpbin.org", "/get")

# send the request with an auth header
xfun::rest_api("https://httpbin.org", "/headers", "OPEN SESAME!")

# with query parameters
xfun::rest_api("https://httpbin.org", "/response-headers", params = list(foo = "bar"))

# get the rate limit info from Github
xfun::github_api("/rate_limit")
```

---

retry

*Retry calling a function for a number of times*

---

**Description**

If the function returns an error, retry it for the specified number of times, with a pause between attempts.

**Usage**

```
retry(fun, ..., .times = 3, .pause = 5)
```

**Arguments**

<code>fun</code>	A function.
<code>...</code>	Arguments to be passed to the function.
<code>.times</code>	The number of times.
<code>.pause</code>	The number of seconds to wait before the next attempt.

**Details**

One application of this function is to download a web resource. Since the download might fail sometimes, you may want to retry it for a few more times.

## Examples

```
# read the Github releases info of the repo yihui/xfun
xfun::retry(xfun::github_releases, "yihui/xfun")
```

---

 rev\_check

*Run R CMD check on the reverse dependencies of a package*


---

## Description

Install the source package, figure out the reverse dependencies on CRAN, download all of their source packages, and run R CMD check on them in parallel.

## Usage

```
rev_check(
  pkg,
  which = "all",
  recheck = NULL,
  ignore = NULL,
  update = TRUE,
  timeout = getOption("xfun.rev_check.timeout", 15 * 60),
  src = file.path(src_dir, pkg),
  src_dir = getOption("xfun.rev_check.src_dir")
)

compare_Rcheck(status_only = TRUE, output = "00check_diffs.md")
```

## Arguments

pkg	The package name.
which	Which types of reverse dependencies to check. See <a href="#">tools::package_dependencies()</a> for possible values. The special value 'hard' means the hard dependencies, i.e., <code>c('Depends', 'Imports', 'LinkingTo')</code> .
recheck	A vector of package names to be (re)checked. If not provided and there are any <code>*.Rcheck</code> directories left by certain packages (this often means these packages failed the last time), recheck will be these packages; if there are no <code>*.Rcheck</code> directories but a text file <code>recheck</code> exists, recheck will be the character vector read from this file. This provides a way for you to manually specify the packages to be checked. If there are no packages to be rechecked, all reverse dependencies will be checked.
ignore	A vector of package names to be ignored in R CMD check. If this argument is missing and a file <code>00ignore</code> exists, the file will be read as a character vector and passed to this argument.
update	Whether to update all packages before the check.

timeout	Timeout in seconds for R CMD check to check each package. The (approximate) total time can be limited by the global option <code>xfun.rev_check.timeout_total</code> .
src	The path of the source package directory.
src_dir	The parent directory of the source package directory. This can be set in a global option if all your source packages are under a common parent directory.
status_only	If TRUE, only compare the final statuses of the checks (the last line of <code>'@@check.log'</code> ), and delete <code>'*.Rcheck'</code> and <code>'*.Rcheck2'</code> if the statuses are identical, otherwise write out the full diffs of the logs. If FALSE, compare the full logs under <code>'*.Rcheck'</code> and <code>'*.Rcheck2'</code> .
output	The output Markdown file to which the diffs in check logs will be written. If the <b>markdown</b> package is available, the Markdown file will be converted to HTML, so you can see the diffs more clearly.

## Details

Everything occurs under the current working directory, and you are recommended to call this function under a designated directory, especially when the number of reverse dependencies is large, because all source packages will be downloaded to this directory, and all `'*.Rcheck'` directories will be generated under this directory, too.

If a source tarball of the expected version has been downloaded before (under the `'tarball'` directory), it will not be downloaded again (to save time and bandwidth).

After a package has been checked, the associated `'*.Rcheck'` directory will be deleted if the check was successful (no warnings or errors or notes), which means if you see a `'*.Rcheck'` directory, it means the check failed, and you need to take a look at the log files under that directory.

The time to finish the check is recorded for each package. As the check goes on, the total remaining time will be roughly estimated via  $n * \text{mean}(\text{times})$ , where  $n$  is the number of packages remaining to be checked, and `times` is a vector of elapsed time of packages that have been checked.

If a check on a reverse dependency failed, its `'*.Rcheck'` directory will be renamed to `'*.Rcheck2'`, and another check will be run against the CRAN version of the package unless `options(xfun.rev_check.compare = FALSE)` is set. If the logs of the two checks are the same, it means no new problems were introduced in the package, and you can probably ignore this particular reverse dependency. The function `compare_Rcheck()` can be used to create a summary of all the differences in the check logs under `'*.Rcheck'` and `'*.Rcheck2'`. This will be done automatically if `options(xfun.rev_check.summary = TRUE)` has been set.

A recommended workflow is to use a special directory to run `rev_check()`, set the global `options()` `xfun.rev_check.src_dir` and `repos` in the R startup (see [?Startup](#)) profile file `.Rprofile` under this directory, and (optionally) set `R_LIBS_USER` in `'.Renviro`n' to use a special library path (so that your usual library will not be cluttered). Then run `xfun::rev_check(pkg)` once, investigate and fix the problems or (if you believe it was not your fault) ignore broken packages in the file `'@@ignore'`, and run `xfun::rev_check(pkg)` again to recheck the failed packages. Repeat this process until all `'*.Rcheck'` directories are gone.

As an example, I set `options(repos = c(CRAN = 'https://cran.rstudio.com'))`, `xfun.rev_check.src_dir = '~/Dropbox/repo'` in `'.Rprofile'`, and `R_LIBS_USER=~ /R-tmp` in `'.Renviro`n'. Then I can run, for example, `xfun::rev_check('knitr')` repeatedly under a special directory `'~/Downloads/revcheck'`. Reverse dependencies and their dependencies will be installed to `'~/R-tmp'`, and **knitr** will be installed from `'~/Dropbox/repo/kintr'`.

**Value**

A named numeric vector with the names being package names of reverse dependencies; 0 indicates check success, 1 indicates failure, and 2 indicates that a package was not checked due to global timeout.

**See Also**

`devtools::revdep_check()` is more sophisticated, but currently has a few major issues that affect me: (1) It always deletes the `*.Rcheck` directories (<https://github.com/r-lib/devtools/issues/1395>), which makes it difficult to know more information about the failures; (2) It does not fully install the source package before checking its reverse dependencies (<https://github.com/r-lib/devtools/pull/1397>); (3) I feel it is fairly difficult to iterate the check (ignore the successful packages and only check the failed packages); by comparison, `xfun::rev_check()` only requires you to run a short command repeatedly (failed packages are indicated by the existing `*.Rcheck` directories, and automatically checked again the next time).

`xfun::rev_check()` borrowed a very nice feature from `devtools::revdep_check()`: estimating and displaying the remaining time. This is particularly useful for packages with huge numbers of reverse dependencies.

---

Rscript

*Run the commands Rscript and R CMD*


---

**Description**

Wrapper functions to run the commands Rscript and R CMD.

**Usage**

```
Rscript(args, ...)
```

```
Rcmd(args, ...)
```

**Arguments**

`args` A character vector of command-line arguments.  
`...` Other arguments to be passed to `system2()`.

**Value**

A value returned by `system2()`.

**Examples**

```
library(xfun)
Rscript(c("-e", "1+1"))
Rcmd(c("build", "--help"))
```



---

Rscript_call	<i>Call a function in a new R session via Rscript()</i>
--------------	---

---

### Description

Save the argument values of a function in a temporary RDS file, open a new R session via `Rscript()`, read the argument values, call the function, and read the returned value back to the current R session.

### Usage

```
Rscript_call(
  fun,
  args = list(),
  options = NULL,
  ...,
  wait = TRUE,
  fail = sprintf("Failed to run '%s' in a new R session.", deparse(substitute(fun))[1])
)
```

### Arguments

<code>fun</code>	A function, or a character string that can be parsed and evaluated to a function.
<code>args</code>	A list of argument values.
<code>options</code>	A character vector of options to be passed to <code>Rscript()</code> , e.g., <code>"--vanilla"</code> .
<code>..., wait</code>	Arguments to be passed to <code>system2()</code> .
<code>fail</code>	The desired error message when an error occurred in calling the function.

### Value

The returned value of the function in the new R session.

### Examples

```
factorial(10)
# should return the same value
xfun::Rscript_call("factorial", list(10))

# the first argument can be either a character string or a function
xfun::Rscript_call(factorial, list(10))

# Run Rscript starting a vanilla R session
xfun::Rscript_call(factorial, list(10), options = c("--vanilla"))
```

---

rstudio_type	<i>Type a character vector into the RStudio source editor</i>
--------------	---

---

### Description

Use the **rstudioapi** package to insert characters one by one into the RStudio source editor, as if they were typed by a human.

### Usage

```
rstudio_type(x, pause = function() 0.1, mistake = 0, save = 0)
```

### Arguments

x	A character vector.
pause	A function to return a number in seconds to pause after typing each character.
mistake	The probability of making random mistakes when typing the next character. A random mistake is a random string typed into the editor and deleted immediately.
save	The probability of saving the document after typing each character. Note that If a document is not opened from a file, it will never be saved.

### Examples

```
library(xfun)
if (loadable("rstudioapi") && rstudioapi::isAvailable()) {
  rstudio_type("Hello, RStudio! xfun::rstudio_type() looks pretty cool!",
    pause = function() runif(1, 0, 0.5), mistake = 0.1)
}
```

---

same_path	<i>Test if two paths are the same after they are normalized</i>
-----------	---

---

### Description

Compare two paths after normalizing them with the same separator (/).

### Usage

```
same_path(p1, p2, ...)
```

### Arguments

p1, p2	Two vectors of paths.
...	Arguments to be passed to <a href="#">normalize_path()</a> .

## Examples

```
library(xfun)
same_path("~/foo", file.path(Sys.getenv("HOME"), "foo"))
```

---

session\_info

*An alternative to sessionInfo() to print session information*

---

## Description

This function tweaks the output of `sessionInfo()`: (1) It adds the RStudio version information if running in the RStudio IDE; (2) It removes the information about matrix products, BLAS, and LAPACK; (3) It removes the names of base R packages; (4) It prints out package versions in a single group, and does not differentiate between loaded and attached packages.

## Usage

```
session_info(packages = NULL, dependencies = TRUE)
```

## Arguments

`packages` A character vector of package names, of which the versions will be printed. If not specified, it means all loaded and attached packages in the current R session.

`dependencies` Whether to print out the versions of the recursive dependencies of packages.

## Details

It also allows you to only print out the versions of specified packages (via the `packages` argument) and optionally their recursive dependencies. For these specified packages (if provided), if a function `xfun_session_info()` exists in a package, it will be called and expected to return a character vector to be appended to the output of `session_info()`. This provides a mechanism for other packages to inject more information into the `session_info` output. For example, **rmarkdown** ( $\geq 1.20.2$ ) has a function `xfun_session_info()` that returns the version of Pandoc, which can be very useful information for diagnostics.

## Value

A character vector of the session information marked as `raw_string()`.

## Examples

```
xfun::session_info()
if (xfun::loadable("MASS")) xfun::session_info("MASS")
```

---

set_envvar	<i>Set environment variables</i>
------------	----------------------------------

---

**Description**

Set environment variables from a named character vector, and return the old values of the variables, so they could be restored later.

**Usage**

```
set_envvar(vars)
```

**Arguments**

vars	A named character vector of the form <code>c(VARIABLE = VALUE)</code> . If any value is NA, this function will try to unset the variable.
------	---

**Details**

The motivation of this function is that `Sys.setenv()` does not return the old values of the environment variables, so it is not straightforward to restore the variables later.

**Value**

Old values of the variables (if not set, NA).

**Examples**

```
vars = xfun::set_envvar(c(F00 = "1234"))
Sys.getenv("F00")
xfun::set_envvar(vars)
Sys.getenv("F00")
```

---

shrink_images	<i>Shrink images to a maximum width</i>
---------------	---

---

**Description**

Use `magick::image_resize()` to shrink an image if its width is larger than the value specified by the argument width, and optionally call `tinify()` to compress it.

**Usage**

```
shrink_images(
  width = 800,
  dir = ".",
  files = all_files("[.](png|jpe?g|webp)$", dir),
  tinify = FALSE
)
```

**Arguments**

width	The desired maximum width of images.
dir	The directory of images.
files	A vector of image file paths. By default, this is all <code>‘.png’</code> , <code>‘.jpeg’</code> , and <code>‘.webp’</code> images under <code>dir</code> .
tinify	Whether to compress images using <code>tinify()</code> .

**Examples**

```
f = xfun::all_files("[.](png|jpe?g)$", R.home("doc"))
file.copy(f, tempdir())
f = file.path(tempdir(), basename(f))
magick::image_info(magick::image_read(f)) # some widths are larger than 300
xfun::shrink_images(300, files = f)
magick::image_info(magick::image_read(f)) # all widths <= 300 now
file.remove(f)
```

---

split\_lines

*Split a character vector by line breaks*


---

**Description**

Call `unlist(strsplit(x, '\n'))` on the character vector `x` and make sure it works in a few edge cases: `split_lines('')` returns `''` instead of `character(0)` (which is the returned value of `strsplit('', '\n')`); `split_lines('a\n')` returns `c('a', '')` instead of `c('a')` (which is the returned value of `strsplit('a\n', '\n')`).

**Usage**

```
split_lines(x)
```

**Arguments**

x	A character vector.
---	---------------------

**Value**

All elements of the character vector are split by `'\n'` into lines.

**Examples**

```
xfun::split_lines(c("a", "b\nc"))
```

---

split_source	<i>Split source lines into complete expressions</i>
--------------	---

---

## Description

Parse the lines of code one by one to find complete expressions in the code, and put them in a list.

## Usage

```
split_source(  
  x,  
  merge_comments = FALSE,  
  line_number = FALSE,  
  skip = getOption("xfun.split_source.skip")  
)
```

## Arguments

x	A character vector of R source code.
merge_comments	Whether to merge consecutive lines of comments as a single expression to be combined with the next non-comment expression (if any).
line_number	Whether to store the starting line number of each expression in the returned value.
skip	A token to skip the rest of code. When provided as a character string, the split will stop at the this token.

## Value

A list of character vectors, and each vector contains a complete R expression, with an attribute `line_start` indicating the starting line number of the expression if the argument `line_number = TRUE`.

## Examples

```
xfun::split_source(c("if (TRUE) {", "1 + 1", "}", "print(1:5)"))  
xfun::split_source(c("print(1:5)", "#--#", "if (TRUE) {", "1 + 1", "}" ), skip = "#--#")
```

---

strict_list	<i>Strict lists</i>
-------------	---------------------

---

### Description

A strict list is essentially a normal `list()` but it does not allow partial matching with `$`.

### Usage

```
strict_list(...)
as_strict_list(x)

## S3 method for class 'xfun_strict_list'
x$name

## S3 method for class 'xfun_strict_list'
print(x, ...)
```

### Arguments

<code>...</code>	Objects (list elements), possibly named. Ignored in the <code>print()</code> method.
<code>x</code>	For <code>as_strict_list()</code> , the object to be coerced to a strict list. For <code>print()</code> , a strict list.
<code>name</code>	The name (a character string) of the list element.

### Details

To me, partial matching is often more annoying and surprising than convenient. It can lead to bugs that are very hard to discover, and I have been bitten by it many times. When I write `x$name`, I always mean precisely `name`. You should use a modern code editor to autocomplete the name if it is too long to type, instead of using partial names.

### Value

Both `strict_list()` and `as_strict_list()` return a list with the class `xfun_strict_list`. Whereas `as_strict_list()` attempts to coerce its argument `x` to a list if necessary, `strict_list()` just wraps its argument `...` in a list, i.e., it will add another list level regardless if `...` already is of type list.

### Examples

```
library(xfun)
(z = strict_list(aaa = "I am aaa", b = 1:5))
z$a # NULL!
z$aaa # I am aaa
z$b
```

```
z$c = "create a new element"

z2 = unclass(z) # a normal list
z2$a # partial matching

z3 = as_strict_list(z2) # a strict list again
z3$a # NULL again!
```

---

strip\_html

*Strip HTML tags*

---

### Description

Remove HTML tags and comments from text.

### Usage

```
strip_html(x)
```

### Arguments

x                   A character vector.

### Value

A character vector with HTML tags and comments stripped off.

### Examples

```
xfun::strip_html("<a href=\"#\">Hello <!-- comment -->world!</a>")
```

---

submit\_cran

*Submit a source package to CRAN*

---

### Description

Build a source package and submit it to CRAN with the **curl** package.

### Usage

```
submit_cran(file = pkg_build(), comment = "")
```



**Arguments**

file	The path to the source package tarball. By default, the current working directory is treated as the package root directory, and automatically built into a tarball, which is deleted after submission. This means you should run <code>xfun::submit_cran()</code> in the root directory of a package project, unless you want to pass a path explicitly to the <code>file</code> argument.
comment	Submission comments for CRAN. By default, if a file <code>'cran-comments.md'</code> exists, its content will be read and used as the comment.

**See Also**

`devtools::submit_cran()` does the same job, with a few more dependencies in addition to **curl** (such as **cli**); `xfun::submit_cran()` only depends on **curl**.

---

system3

*Run system2() and mark its character output as UTF-8 if appropriate*


---

**Description**

This is a wrapper function based on `system2()`. If `system2()` returns character output (e.g., with the argument `stdout = TRUE`), check if the output is encoded in UTF-8. If it is, mark it with UTF-8 explicitly.

**Usage**

```
system3(...)
```

**Arguments**

... Passed to `system2()`.

**Value**

The value returned by `system2()`.

**Examples**

```
a = shQuote(c("-e", "print(intToUtf8(c(20320, 22909)))"))
x2 = system2("Rscript", a, stdout = TRUE)
Encoding(x2) # unknown

x3 = xfun::system3("Rscript", a, stdout = TRUE)
# encoding of x3 should be UTF-8 if the current locale is UTF-8
!l10n_info()[["UTF-8"]] || Encoding(x3) == "UTF-8" # should be TRUE
```

tinify

*Use the Tinify API to compress PNG and JPEG images***Description**

Compress PNG/JPEG images with ‘api.tinify.com’, and download the compressed images. These functions require R packages **curl** and **jsonlite**. `tinify_dir()` is a wrapper function of `tinify()` to compress images under a directory.

**Usage**

```
tinify(
  input,
  output,
  quiet = FALSE,
  force = FALSE,
  key = env_option("xfun.tinify.key"),
  history = env_option("xfun.tinify.history")
)

tinify_dir(dir = ".", ...)
```

**Arguments**

<code>input</code>	A vector of input paths of images.
<code>output</code>	A vector of output paths or a function that takes <code>input</code> and returns a vector of output paths (e.g., <code>output = identity</code> means <code>output = input</code> ). By default, if the <code>history</code> argument is not a provided, <code>output</code> is <code>input</code> with a suffix <code>-min</code> (e.g., when <code>input = 'foo.png'</code> , <code>output = 'foo-min.png'</code> ), otherwise <code>output</code> is the same as <code>input</code> , which means the original image files will be overwritten.
<code>quiet</code>	Whether to suppress detailed information about the compression, which is of the form ‘input.png (10 Kb) ==> output.png (5 Kb, 50%); compression count: 42’. The percentage after <code>output.png</code> stands for the compression ratio, and the compression count shows the number of compressions used for the current month.
<code>force</code>	Whether to compress an image again when it appears to have been compressed before. This argument only makes sense when the <code>history</code> argument is provided.
<code>key</code>	The Tinify API key. It can be set via either the global option <code>xfun.tinify.key</code> or the environment variable <code>R_XFUN_TINIFY_KEY</code> (see <code>env_option()</code> ).
<code>history</code>	Path to a history file to record the MD5 checksum of compressed images. If the checksum of an expected output image exists in this file and <code>force = FALSE</code> , the compression will be skipped. This can help you avoid unnecessary API calls.
<code>dir</code>	A directory under which all ‘.png’, ‘.jpeg’, and ‘.webp’ files are to be compressed.
<code>...</code>	Arguments passed to <code>tinify()</code> .

## Details

You are recommended to set the API key in `‘.Rprofile’` or `‘.Renviron’`. After that, the only required argument of this function is `input`. If the original images can be overwritten by the compressed images, you may either use `output = identity`, or set the value of the `history` argument in `‘.Rprofile’` or `‘.Renviron’`.

## Value

The output file paths.

## References

Tinify API: <https://tinypng.com/developers>.

## See Also

The **tinieR** package (<https://github.com/jmablog/tinieR/>) is a more comprehensive implementation of the Tinify API, whereas `xfun::tinify()` has only implemented the feature of shrinking images.

## Examples

```
f = xfun:::R_logo("jpg$")
xfun::tinify(f) # remember to set the API key before trying this
```

---

tojson

*A simple JSON serializer*

---

## Description

A JSON serializer that only works on a limited types of R data (NULL, lists, logical scalars, character/numeric vectors). A character string of the class `JS_EVAL` is treated as raw JavaScript, so will not be quoted. The function `json_vector()` converts an atomic R vector to JSON.

## Usage

```
tojson(x)
```

```
json_vector(x, to_array = FALSE, quote = TRUE)
```

## Arguments

<code>x</code>	An R object.
<code>to_array</code>	Whether to convert a vector to a JSON array (use <code>[]</code> ).
<code>quote</code>	Whether to double quote the elements.

**Value**

A character string.

**See Also**

The `jsonlite` package provides a full JSON serializer.

**Examples**

```
library(xfun)
tojson(NULL)
tojson(1:10)
tojson(TRUE)
tojson(FALSE)
cat(tojson(list(a = 1, b = list(c = 1:3, d = "abc"))))
cat(tojson(list(c("a", "b"), 1:5, TRUE)))

# the class JS_EVAL is originally from htmlwidgets::JS()
JS = function(x) structure(x, class = "JS_EVAL")
cat(tojson(list(a = 1:5, b = JS("function() {return true;}"))))
```

---

tree

*Turn the output of `str()` into a tree diagram*


---

**Description**

The super useful function `str()` uses `..` to indicate the level of sub-elements of an object, which may be difficult to read. This function uses vertical pipes to connect all sub-elements on the same level, so it is clearer which elements belong to the same parent element in an object with a nested structure (such as a nested list).

**Usage**

```
tree(...)
```

**Arguments**

`...` Arguments to be passed to `str()` (note that the `comp.str` is hardcoded inside this function, and it is the only argument that you cannot customize).

**Value**

A character string as a `raw_string()`.

**Examples**

```
fit = lsfit(1:9, 1:9)
str(fit)
xfun::tree(fit)

fit = lm(dist ~ speed, data = cars)
str(fit)
xfun::tree(fit)

# some trivial examples
xfun::tree(1:10)
xfun::tree(iris)
```

---

try\_error

*Try an expression and see if it throws an error*

---

**Description**

Use `tryCatch()` to check if an expression throws an error.

**Usage**

```
try_error(expr)
```

**Arguments**

expr            An R expression.

**Value**

TRUE (error) or FALSE (success).

**Examples**

```
xfun::try_error(stop("foo")) # TRUE
xfun::try_error(1:10) # FALSE
```

---

try_silent	<i>Try to evaluate an expression silently</i>
------------	---

---

### Description

An abbreviation of `try(silent = TRUE)`.

### Usage

```
try_silent(expr)
```

### Arguments

`expr` An R expression.

### Examples

```
library(xfun)
z = try_silent(stop("Wrong!"))
inherits(z, "try-error")
```

---

upload_ftp	<i>Upload to an FTP server via curl</i>
------------	---

---

### Description

The function `upload_ftp()` runs the command `curl -T file server` to upload a file to an FTP server if the system command `curl` is available, otherwise it uses the R package **curl**. The function `upload_win_builder()` uses `upload_ftp()` to upload packages to the win-builder server.

### Usage

```
upload_ftp(file, server, dir = "")

upload_win_builder(
  file = pkg_build(),
  version = c("R-devel", "R-release", "R-oldrelease"),
  server = c("ftp", "https"),
  solaris = pkg_available("rhub")
)
```

**Arguments**

file	Path to a local file.
server	The address of the FTP server. For <code>upload_win_builder()</code> , <code>server = 'https'</code> means uploading to <code>'https://win-builder.r-project.org/upload.aspx'</code> .
dir	The remote directory to which the file should be uploaded.
version	The R version(s) on win-builder.
solaris	Whether to also upload the package to the Rhub server to check it on Solaris.

**Details**

These functions were written mainly to save package developers the trouble of going to the win-builder web page and uploading packages there manually.

**Value**

Status code returned from `system2()` or `curl::curl_fetch_memory()`.

---

upload_imgur	<i>Upload an image to imgur.com</i>
--------------	-------------------------------------

---

**Description**

This function uses the **curl** package or the system command `curl` (whichever is available) to upload a image to <https://imgur.com>.

**Usage**

```
upload_imgur(
  file,
  key = env_option("xfun.upload_imgur.key", "9f3460e67f308f6"),
  use_curl = loadable("curl"),
  include_xml = FALSE
)
```

**Arguments**

file	Path to the image file to be uploaded.
key	Client ID for Imgur. It can be set via either the global option <code>xfun.upload_imgur.key</code> or the environment variable <code>R_XFUN_UPLOAD_IMGUR_KEY</code> (see <code>env_option()</code> ). If neither is set, this uses a client ID registered by Yihui Xie.
use_curl	Whether to use the R package <b>curl</b> to upload the image. If <code>FALSE</code> , the system command <code>curl</code> will be used.
include_xml	Whether to include the XML response in the returned value.

## Details

One application is to upload local image files to Imgur when knitting a document with **knitr**: you can set the `knitr::opts_knit$set(upload.fun = xfun::upload_imgur)`, so the output document does not need local image files any more, and it is ready to be published online.

## Value

A character string of the link to the image. If `include_xml = TRUE`, this string carries an attribute named `XML`, which is the XML response from Imgur (it will be parsed by **xml2** if available). See Imgur API in the references.

## Note

Please register your own Imgur application to get your client ID; you can certainly use mine, but this ID is in the public domain so everyone has access to all images associated to it.

## Author(s)

Yihui Xie, adapted from the **imguR** package by Aaron Statham

## References

A demo: <https://yihui.org/knitr/demo/upload/>

## Examples

```
## Not run:
f = tempfile(fileext = ".png")
png(f)
plot(rnorm(100), main = R.version.string)
dev.off()

res = imgur_upload(f, include_xml = TRUE)
res # link to original URL of the image
attr(res, "XML") # all information
if (interactive())
  browseURL(res)

# to use your own key
options(xfun.upload_imgur.key = "your imgur key")

## End(Not run)
```



---

url_accessible	<i>Test if a URL is accessible</i>
----------------	------------------------------------

---

### Description

Try to send a HEAD request to a URL using `curlGetHeaders()` or the **curl** package, and see if it returns a successful status code.

### Usage

```
url_accessible(x, use_curl = !capabilities("libcurl"), ...)
```

### Arguments

x	A URL as a character string.
use_curl	Whether to use the <b>curl</b> package or the <code>curlGetHeaders()</code> function in base R to send the request to the URL. By default, <b>curl</b> will be used when base R does not have the <code>libcurl</code> capability (which should be rare).
...	Arguments to be passed to <code>curlGetHeaders()</code> .

### Value

TRUE or FALSE.

### Examples

```
xfun::url_accessible("https://yihui.org")
```

---

url_filename	<i>Extract filenames from a URLs</i>
--------------	--------------------------------------

---

### Description

Get the base names of URLs via `basename()`, and remove the possible query parameters or hash from the names.

### Usage

```
url_filename(x, default = "index.html")
```

### Arguments

x	A character vector of URLs.
default	The default filename when it cannot be determined from the URL, e.g., when the URL ends with a slash.

**Value**

A character vector of filenames at the end of URLs.

**Examples**

```
xfun::url_filename("https://yihui.org/images/logo.png")
xfun::url_filename("https://yihui.org/index.html")
xfun::url_filename("https://yihui.org/index.html?foo=bar")
xfun::url_filename("https://yihui.org/index.html#about")
xfun::url_filename("https://yihui.org")
xfun::url_filename("https://yihui.org/")
```

---

valid\_syntax

*Check if the syntax of the code is valid*

---

**Description**

Try to `parse()` the code and see if an error occurs.

**Usage**

```
valid_syntax(code, silent = TRUE)
```

**Arguments**

`code` A character vector of R source code.

`silent` Whether to suppress the error message when the code is not valid.

**Value**

TRUE if the code could be parsed, otherwise FALSE.

**Examples**

```
xfun::valid_syntax("1+1")
xfun::valid_syntax("1+")
xfun::valid_syntax(c("if(T){1+1}", "else {2+2}"), silent = FALSE)
```

---

yaml_body	<i>Partition the YAML metadata and the body in a document</i>
-----------	---

---

### Description

Split a document into the YAML metadata (which starts with `---` in the beginning of the document) and the body. The YAML metadata will be parsed.

### Usage

```
yaml_body(x, ...)
```

### Arguments

x	A character vector of the document content.
...	Arguments to be passed to <code>yaml_load()</code> .

### Value

A list of components `yaml` and `body`.

### Examples

```
xfun::yaml_body(c("---", "title: Hello", "output: markdown::html_document", "---",  
  "", "Content."))
```

---

yaml_load	<i>Read YAML data</i>
-----------	-----------------------

---

### Description

If the **yaml** package is installed, use `yaml::yaml.load()` to read the data. If not, use a simple parser instead, which only supports a limited number of data types (see “Examples”). In particular, it does not support values that span across multiple lines (such as multi-line text).

### Usage

```
yaml_load(  
  x,  
  ...,  
  handlers = NULL,  
  envir = parent.frame(),  
  use_yaml = loadable("yaml")  
)
```

**Arguments**

x	A character vector of YAML data.
..., handlers	Arguments to be passed to <code>yaml::yaml.load()</code> .
envir	The environment in which R expressions in YAML are evaluated. To disable the evaluation, use <code>envir = FALSE</code> .
use_yaml	Whether to use the <b>yaml</b> package.

**Value**

An R object (typically a list).

**Note**

R expressions in YAML will be returned as [expressions](#) when they are not evaluated. This is different with `yaml::yaml.load()`, which returns character strings for expressions.

**Examples**

```
# test the simple parser without using the yaml package
read_yaml = function(...) xfun::yaml_load(..., use_yaml = FALSE)
read_yaml("a: 1")
read_yaml("a: 1\nb: \"foo\"\nc: null")
read_yaml("a:\n b: false\n c: true\n d: 1.234\ne: bar")
read_yaml("a: !expr paste(1:10, collapse = \", \")")
read_yaml("a: [1, 3, 4, 2]")
read_yaml("a: [1, \"abc\", 4, 2]")
read_yaml("a: [\"foo\", \"bar\"]")
read_yaml("a: [true, false, true]")
# the other form of array is not supported
read_yaml("a:\n - b\n - c")
# and you must use the yaml package
if (loadable("yaml")) yaml_load("a:\n - b\n - c")
```

# Index

- \* **datasets**
  - download\_cache, 16
  - proj\_root, 43
- .Renviron, 20
- .Rprofile, 20
- .packages, 41
- \$.xfun\_strict\_list(strict\_list), 63
  
- alnum\_id, 4
- append\_unique(read\_utf8), 47
- append\_utf8(read\_utf8), 47
- as\_strict\_list(strict\_list), 63
- attr, 4
  
  
- base64\_decode(base64\_encode), 5
- base64\_encode, 5
- base64\_uri, 6
- base::attr, 4
- base::attr(), 4
- base\_pkgs, 6
- basename(), 73
- bg\_process, 7
- broken\_packages, 8
- bump\_version, 8
  
  
- cache\_rds, 9
- cat(), 35
- compare\_Rcheck(rev\_check), 54
- crandalf\_check, 11
- crandalf\_results(crandalf\_check), 11
- csv\_options, 12
- curlGetHeaders(), 73
  
  
- decimal\_dot, 13
- del\_empty\_dir, 13
- dir.create, 14
- dir.create(), 14
- dir.exists(), 14
- dir\_create, 14
- dir\_exists, 14
  
  
- divide\_chunk, 15
- do\_once, 17
- download.file(), 17
- download\_cache, 16
- download\_file, 17
  
  
- embed\_dir(embed\_file), 18
- embed\_file, 18
- embed\_files(embed\_file), 18
- enc2utf8(), 48
- env\_option, 20
- env\_option(), 66, 71
- existing\_files, 21
- exit\_call, 21
- expression, 76
- expression(), 39
  
  
- fenced\_block, 22
- file.exists(), 14
- file.path, 25
- file.size, 47
- file\_exists(dir\_exists), 14
- file\_ext, 23
- file\_string, 24
- format(), 25
- format.xfun\_record\_results(record), 48
- format\_bytes, 25
- from\_root, 25
  
  
- github\_api(rest\_api), 52
- github\_api(), 26
- github\_releases, 26
- grep(), 27
- grep\_sub, 27
- gsub(), 27
- gsub\_dir(gsub\_file), 27
- gsub\_ext(gsub\_file), 27
- gsub\_file, 27
- gsub\_files(gsub\_file), 27
  
  
- identity, 66

- in\_dir, 29
- in\_dir(), 34
- install.packages(), 40
- install\_dir, 28
- install\_github, 29
- installed.packages(), 6
- invisible(), 49
- is\_abs\_path, 30
- is\_arm64 (is\_windows), 33
- is\_ascii, 30
- is\_blank, 31
- is\_linux (is\_windows), 33
- is\_macos (is\_windows), 33
- is\_rel\_path (is\_abs\_path), 30
- is\_sub\_path, 31
- is\_unix (is\_windows), 33
- is\_web\_path, 32
- is\_windows, 33
  
- json\_vector (tojson), 67
  
- l10n\_info(), 36
- library(), 40
- list(), 63
- list.files(), 51
- loadable (pkg\_attach), 40
- loadable(), 8
  
- magic\_path, 33
- magick::image\_resize(), 60
- make\_fence (fenced\_block), 22
- mark\_dirs, 34
- message(), 35
- msg\_cat, 35
  
- n2w (numbers\_to\_words), 38
- native\_encode, 36
- news(), 36, 37
- news2md, 36
- normalize\_path, 37
- normalize\_path(), 32, 58
- normalizePath(), 37
- numbers\_to\_words, 38
  
- on.exit(), 21
- options(), 17, 18, 20, 40, 55
- optipng, 39
  
- parse, 10
- parse(), 74
  
- parse\_only, 39
- pkg\_attach, 40
- pkg\_attach2 (pkg\_attach), 40
- pkg\_available (pkg\_attach), 40
- pkg\_load (pkg\_attach), 40
- pkg\_load2 (pkg\_attach), 40
- print.xfun\_raw\_string (raw\_string), 45
- print.xfun\_record\_results (record), 48
- print.xfun\_strict\_list (strict\_list), 63
- proc\_kill, 42
- proc\_kill(), 7
- process\_file, 41
- proj\_root, 43
- prose\_index, 44
- protect\_math, 44
  
- raw\_string, 45
- raw\_string(), 59, 68
- Rcmd (Rscript), 56
- read\_all, 46
- read\_bin, 47
- read\_utf8, 47
- read\_utf8(), 52
- readBin(), 47
- record, 48
- relative\_path, 50
- relative\_path(), 25
- remotes::install\_github(), 29
- rename\_seq, 51
- requireNamespace(), 40, 41
- rest\_api, 52
- rest\_api\_raw (rest\_api), 52
- retry, 53
- rev\_check, 54
- rev\_check(), 11
- root\_rules (proj\_root), 43
- Rscript, 56
- Rscript(), 57
- Rscript\_call, 57
- rstudio\_type, 58
  
- same\_path, 58
- same\_path(), 30
- sans\_ext (file\_ext), 23
- saveRDS(), 9
- session\_info, 59
- sessionInfo(), 59
- set\_envvar, 60
- shQuote(), 7

shrink\_images, 60  
sort(), 42  
sort\_file (process\_file), 41  
split\_lines, 61  
split\_source, 62  
sprintf(), 51  
Startup, 55  
stderr(), 35  
stdout(), 35  
str(), 68  
strict\_list, 63  
strip\_html, 64  
submit\_cran, 64  
suppressMessages(), 35  
Sys.setenv(), 60  
system2, 7  
system2(), 42, 56, 57, 65, 71  
system3, 65  
  
tinify, 66  
tinify(), 60, 61, 66  
tinify\_dir (tinify), 66  
tojson, 67  
tools::file\_ext(), 23  
tools::file\_path\_sans\_ext(), 23  
tools::package\_dependencies(), 54  
tree, 68  
try\_error, 69  
try\_silent, 70  
tryCatch(), 69  
  
upload\_ftp, 70  
upload\_imgur, 71  
upload\_win\_builder (upload\_ftp), 70  
url(), 52  
url\_accessible, 73  
url\_filename, 73  
url\_filename(), 17  
  
valid\_syntax, 74  
  
with\_ext (file\_ext), 23  
write\_utf8 (read\_utf8), 47  
writeLines(), 48  
  
yaml::yaml.load(), 75, 76  
yaml\_body, 75  
yaml\_load, 75