

Package ‘xpectr’

November 17, 2022

Title Generates Expectations for 'testthat' Unit Testing

Version 0.4.3

Description Helps systematize and ease the process of building unit tests with the 'testthat' package by providing tools for generating expectations.

License MIT + file LICENSE

URL <https://github.com/ludvigolsen/xpectr>

BugReports <https://github.com/ludvigolsen/xpectr/issues>

Depends R (>= 3.5.0)

Imports clipr (>= 0.7.0),
checkmate (>= 2.0.0),
dplyr,
fansI (>= 0.4.1),
lifecycle,
plyr,
rlang,
rstudioapi (>= 0.10),
stats,
testthat (>= 2.3.1),
tibble,
utils,
withr (>= 2.0.0)

Suggests data.table,
knitr,
rmarkdown

RdMacros lifecycle

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

VignetteBuilder knitr

R topics documented:

assertCollectionAddin	2
capture_parse_eval_side_effects	3

capture_side_effects	4
dputSelectedAddin	6
element_classes	7
element_lengths	8
element_types	9
gxs_function	10
gxs_selection	13
initializeGXSTFunctionAddin	16
initializeTestthatAddin	17
insertExpectationsAddin	18
navigateTestFileAddin	20
num_total_elements	21
prepare_insertion	22
set_test_seed	23
simplified_formals	23
smpl	24
stop_if	25
strip	26
strip_msg	27
suppress_mw	29
wrapStringAddin	30
xpectr	31

Index	32
--------------	-----------

assertCollectionAddin *Inserts code for a checkmate assert collection*

Description

[Experimental]

RStudio Addin: Inserts code for initializing and reporting a [checkmate assert collection](#).

See ``Details`` for how to set a key command.

Usage

```
assertCollectionAddin(add_comments = TRUE, insert = TRUE, indentation = NULL)
```

Arguments

- | | |
|--------------|---|
| add_comments | Whether to add comments around. (Logical)
This makes it easy for a user to create their own addin without the comments. |
| insert | Whether to insert the code via <code>rstudioapi::insertText()</code> or return it. (Logical)
N.B. Mainly intended for testing the addin programmatically. |
| indentation | Indentation of the code. (Numeric)
N.B. Mainly intended for testing the addin programmatically. |

Details

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Insert checkmate AssertCollection Code" and press its field under Shortcut.

Press desired key command, e.g. Alt+C.

Press Apply.

Press Execute.

Value

Inserts the following (excluding the ----):

```
----  
# Check arguments #####  
assert_collection <- checkmate::makeAssertCollection()  
# checkmate::assert_ , add = assert_collection)  
checkmate::reportAssertions(assert_collection)  
# End of argument checks #####  
----
```

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other addins: [dputSelectedAddin\(\)](#), [initializeGXFunctionAddin\(\)](#), [initializeTestthatAddin\(\)](#), [insertExpectationsAddin\(\)](#), [navigateTestFileAddin\(\)](#), [wrapStringAddin\(\)](#)

capture_parse_eval_side_effects

Capture side effects from parse eval

Description

Wraps string in [capture_side_effects\(\)](#) before parsing and evaluating it. The side effects (error, warnings, messages) are returned in a list.

When capturing an error, no other side effects are captured.

Usage

```
capture_parse_eval_side_effects(  
  string,  
  envir = NULL,  
  copy_env = FALSE,  
  reset_seed = FALSE,  
  disable_crayon = TRUE  
)
```

Arguments

string	String of code that can be parsed and evaluated in <code>envir</code> .
envir	Environment to evaluate in. Defaults to <code>parent.frame()</code> .
copy_env	Whether to use deep copies of the environment when capturing side effects. (Logical) Disabled by default to save memory but is often preferable to enable, e.g. when the function alters non-local variables before throwing its error/warning/message.
reset_seed	Whether to reset the random state on exit. (Logical)
disable_crayon	Whether to disable crayon formatting. This can remove ANSI characters from the messages. (Logical)

Value

named list with the side effects.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other capturers: [capture_side_effects\(\)](#)

Examples

```
# Attach package
library(xpectr)

capture_parse_eval_side_effects("stop('hi!')")
capture_parse_eval_side_effects("warning('hi!')")
capture_parse_eval_side_effects("message('hi!')")
```

capture_side_effects *Capture side effects*

Description

Captures errors, warnings, and messages from an expression.

In case of an error, no other side effects are captured.

Simple wrapper for testthat's [capture_error\(\)](#), [capture_warnings\(\)](#) and [capture_messages\(\)](#).

Note: Evaluates `expr` up to three times.

Usage

```
capture_side_effects(
  expr,
  envir = NULL,
  copy_env = FALSE,
  reset_seed = FALSE,
  disable_crayon = TRUE
)
```

Arguments

expr	Expression.
envir	Environment to evaluate in. Defaults to <code>parent.frame()</code> .
copy_env	Whether to use deep copies of the environment when capturing side effects. (Logical) Disabled by default to save memory but is often preferable to enable, e.g. when the function alters non-local variables before throwing its error/warning/message.
reset_seed	Whether to reset the random state on exit. (Logical)
disable_crayon	Whether to disable crayon formatting. This can remove ANSI characters from the messages. (Logical)

Value

named list with the side effects.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other capturers: [capture_parse_eval_side_effects\(\)](#)

Examples

```
# Attach packages
library(xpectr)

fn <- function(raise = FALSE){
  message("Hi! I'm Kevin, your favorite message!")
  warning("G'Day Mam! I'm a warning to the world!")
  message("Kevin is ma name! Yesss!")
  warning("Hopefully the whole world will see me :o")
  if (isTRUE(raise)){
    stop("Lord Evil Error has arrived! Yeehaaa")
  }
  "the output"
}

capture_side_effects(fn())
capture_side_effects(fn(raise = TRUE))
capture_side_effects(fn(raise = TRUE), copy_env = TRUE)
```

dputSelectedAddin *Replaces selected code with its dput() output*

Description

[Experimental]

RStudio Addin: Runs `dput()` on the selected code and inserts it instead of the selection.

See `Details` for how to set a key command.

Usage

```
dputSelectedAddin(selection = NULL, insert = TRUE, indentation = 0)
```

Arguments

selection	String of code. (Character) E.g. <code>"stop('This gives an expect_error test')"</code> . N.B. Mainly intended for testing the addin programmatically.
insert	Whether to insert the expectations via <code>rstudioapi::insertText()</code> or return them. (Logical) N.B. Mainly intended for testing the addin programmatically.
indentation	Indentation of the selection. (Numeric) N.B. Mainly intended for testing the addin programmatically.

Details

How: Parses and evaluates the selected code string, applies `dput()` and inserts the output instead of the selection.

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "dput() Selected" and press its field under Shortcut.

Press desired key command, e.g. Alt+D.

Press Apply.

Press Execute.

Value

Inserts the output of running `dput()` on the selected code.

Does not return anything.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other addins: `assertCollectionAddin()`, `initializeGXFunctionAddin()`, `initializeTestthatAddin()`, `insertExpectationsAddin()`, `navigateTestFileAddin()`, `wrapStringAddin()`

element_classes	<i>Gets the class of each element</i>
-----------------	---------------------------------------

Description

[Experimental]

Applies `class()` to each element of `x` (without recursion). When `class()` returns multiple strings, the first class string is returned.

Usage

```
element_classes(x, keep_names = FALSE)
```

Arguments

<code>x</code>	List with elements.
<code>keep_names</code>	Whether to keep existing names. (Logical)

Details

Gets first string in `class()` for all elements.

Value

The main class of each element.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other element descriptors: [element_lengths\(\)](#), [element_types\(\)](#), [num_total_elements\(\)](#)

Examples

```
# Attach packages
library(xpectr)

l <- list("a" = c(1,2,3), "b" = "a", "c" = NULL)

element_classes(l)
element_classes(l, keep_names = TRUE)
```

element_lengths	<i>Gets the length of each element</i>
-----------------	--

Description

[Experimental]

Applies `length()` to each element of `x` (without recursion).

Usage

```
element_lengths(x, keep_names = FALSE)
```

Arguments

<code>x</code>	List with elements.
<code>keep_names</code>	Whether to keep existing names. (Logical)

Details

Simple wrapper for `unlist(lapply(x, length))`.

Value

The length of each element.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other element descriptors: `element_classes()`, `element_types()`, `num_total_elements()`

Examples

```
# Attach packages
library(xpectr)

l <- list("a" = c(1,2,3), "b" = 1, "c" = NULL)

element_lengths(l)
element_lengths(l, keep_names = TRUE)
```

element_types	<i>Gets the type of each element</i>
---------------	--------------------------------------

Description

[Experimental]

Applies `typeof()` to each element of `x` (without recursion).

Usage

```
element_types(x, keep_names = FALSE)
```

Arguments

<code>x</code>	List with elements.
<code>keep_names</code>	Whether to keep existing names. (Logical)

Details

Simple wrapper for `unlist(lapply(x, typeof))`.

Value

The type of each element.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other element descriptors: [element_classes\(\)](#), [element_lengths\(\)](#), [num_total_elements\(\)](#)

Examples

```
# Attach packages
library(xpectr)

l <- list("a" = c(1,2,3), "b" = "a", "c" = NULL)

element_types(l)
element_types(l, keep_names = TRUE)
```

gxs_function

*Generate testthat expectations for argument values in a function***Description****[Experimental]**

Based on a set of supplied values for each function argument, a set of testthat expect_* statements are generated.

Included tests: The first value supplied for an argument is considered the *valid baseline* value. For each argument, we create tests for each of the supplied values, where the other arguments have their baseline value.

When testing a function that alters non-local variables, consider enabling `copy_env`.

See supported objects in details.

Usage

```
gxs_function(
  fn,
  args_values,
  extra_combinations = NULL,
  check_nulls = TRUE,
  indentation = 0,
  tolerance = "1e-4",
  round_to_tolerance = TRUE,
  strip = TRUE,
  sample_n = 30,
  envir = NULL,
  copy_env = FALSE,
  assign_output = TRUE,
  seed = 42,
  add_wrapper_comments = TRUE,
  add_test_comments = TRUE,
  start_with_newline = TRUE,
  end_with_newline = TRUE,
  out = "insert",
  parallel = FALSE
)
```

Arguments

fn	Function to create tests for.
args_values	The arguments and the values to create tests for. Should be supplied as a named list of lists, like the following: <pre>args_values = list("x1" = list(1, 2, 3), "x2" = list("a", "b", "c"))</pre> <p>The first value for each argument (referred to as the 'baseline' value) should be valid (not throw an error/message/warning).</p>

N.B. This is not checked but should lead to more meaningful tests.

N.B. Please define the list directly in the function call. This is currently necessary.

extra_combinations	<p>Additional combinations to test. List of lists, where each combination is a named sublist.</p> <p>E.g. the following two combinations:</p> <pre>extra_combinations = list(list("x1" = 4, "x2" = "b"), list("x1" = 7, "x2" = "c"))</pre> <p>N.B. Unspecified arguments gets the baseline value.</p> <p>If you find yourself adding many combinations, an additional <code>gxs_function()</code> call with different baseline values might be preferable.</p>
check_nulls	<p>Whether to try all arguments with NULL. (Logical)</p> <p>When enabled, you don't need to add NULL to your <code>`args_values`</code>, unless it should be the baseline value.</p>
indentation	Indentation of the selection. (Numeric)
tolerance	The tolerance for numeric tests as a string, like "1e-4". (Character)
round_to_tolerance	<p>Whether to round numeric elements to the specified tolerance. (Logical)</p> <p>This is currently applied to numeric columns and vectors (excluding some lists).</p>
strip	<p>Whether to insert <code>strip_msg()</code> and <code>strip()</code> in tests of side effects. (Logical)</p> <p>Sometimes testthat tests have differences in punctuation and newlines on different systems. By stripping both the error message and the expected message of non-alphanumeric symbols, we can avoid such failed tests.</p>
sample_n	<p>The number of elements/rows to sample. Set to NULL to avoid sampling.</p> <p>Inserts <code>smp1()</code> in the generated tests when sampling was used. A seed is set internally, setting <code>sample.kind</code> as "Rounding" to ensure compatibility with R versions < 3.6.0.</p> <p>The order of the elements/rows is kept intact. No replacement is used, why no oversampling will take place.</p> <p>When testing a big <code>data.frame</code>, sampling the rows can help keep the test files somewhat readable.</p>
envir	Environment to evaluate in. Defaults to <code>parent.frame()</code> .
copy_env	<p>Whether each combination should be tested in a deep copy of the environment. (Logical)</p> <p>Side effects will be captured in copies of the copy, why two copies of the environment will exist at the same time.</p> <p>Disabled by default to save memory but is often preferable to enable, e.g. when the function changes non-local variables.</p>
assign_output	<p>Whether to assign the output of a function call or long selection to a variable. This will avoid recalling the function and decrease cluttering. (Logical)</p> <p>Heuristic: when the <code>`selection`</code> isn't of a string and contains a parenthesis, it is considered a function call. A selection with more than 30 characters will be assigned as well.</p> <p>The tests themselves can be more difficult to interpret, as you will have to look at the assignment to see the object that is being tested.</p>

seed	seed to set. (Whole number)
add_wrapper_comments	Whether to add intro and outro comments. (Logical)
add_test_comments	Whether to add comments for each test. (Logical)
start_with_newline, end_with_newline	Whether to have a newline in the beginning/end. (Logical)
out	Either "insert" or "return". "insert" (Default): Inserts the expectations via <code>rstudioapi::insertText()</code> . "return": Returns the expectations in a list. These can be prepared for insertion with <code>prepare_insertion()</code> .
parallel	Whether to parallelize the generation of expectations. (Logical) Requires a registered parallel backend. Like with <code>doParallel::registerDoParallel</code> .

Details

The following "types" are currently supported or intended to be supported in the future. Please suggest more types and tests in a GitHub issue!

Note: A set of fallback tests will be generated for unsupported objects.

Type	Supported	Notes
Side effects	Yes	Errors, warnings, and messages.
Vector	Yes	Lists are treated differently, depending on their structure.
Factor	Yes	
Data Frame	Yes	List columns (like nested tibbles) are currently skipped.
Matrix	Yes	Supported but could be improved.
Formula	Yes	
Function	Yes	
NULL	Yes	
Array	No	
Dates	No	Base and lubridate.
ggplot2	No	This may be a challenge, but would be cool!

Value

Either NULL or the unprepared expectations as a character vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other expectation generators: `gxs_selection()`, `initializeGXFunctionAddin()`, `insertExpectationsAddin()`

Examples

```

# Attach packages
library(xpectr)

## Not run:
fn <- function(x, y, z){
  if (x>3) stop("'x' > 3")
  if (y<0) warning("'y'<0")
  if (z==10) message("'z' was 10!")
  x + y + z
}

# Create expectations
# Note: define the list in the call
gxs_function(fn,
  args_values = list(
    "x" = list(2, 4, NA),
    "y" = list(0, -1),
    "z" = list(5, 10))
)

# Add additional combinations
gxs_function(fn,
  args_values = list(
    "x" = list(2, 4, NA),
    "y" = list(0, -1),
    "z" = list(5, 10)),
  extra_combinations = list(
    list("x" = 4, "z" = 10),
    list("y" = 1, "z" = 10))
)

## End(Not run)

```

gxs_selection

*Generate testthat expectations from selection***Description****[Experimental]**

Based on the selection (string of code), a set of testthat `expect_*` statements are generated.

Example: If the selected code is the name of a data.frame object, it will create an [expect_equal](#) test for each column, along with a test of the column names, types and classes, dimensions, grouping keys, etc.

See supported objects in details.

When testing a function that alters non-local variables, consider enabling ``copy_env``.

Feel free to suggest useful tests etc. in a GitHub issue!

Addin: [insertExpectationsAddin\(\)](#)

Usage

```

gxs_selection(
  selection,
  indentation = 0,
  tolerance = "1e-4",
  round_to_tolerance = TRUE,
  strip = TRUE,
  sample_n = 30,
  envir = NULL,
  copy_env = FALSE,
  assign_output = TRUE,
  seed = 42,
  test_id = NULL,
  add_wrapper_comments = TRUE,
  add_test_comments = TRUE,
  start_with_newline = TRUE,
  end_with_newline = TRUE,
  out = "insert"
)

```

Arguments

selection	String of code. (Character) E.g. "stop('This gives an expect_error test')".
indentation	Indentation of the selection. (Numeric)
tolerance	The tolerance for numeric tests as a string, like "1e-4". (Character)
round_to_tolerance	Whether to round numeric elements to the specified tolerance. (Logical) This is currently applied to numeric columns and vectors (excluding some lists).
strip	Whether to insert <code>strip_msg()</code> and <code>strip()</code> in tests of side effects. (Logical) Sometimes testthat tests have differences in punctuation and newlines on different systems. By stripping both the error message and the expected message of non-alphanumeric symbols, we can avoid such failed tests.
sample_n	The number of elements/rows to sample. Set to NULL to avoid sampling. Inserts <code>smp1()</code> in the generated tests when sampling was used. A seed is set internally, setting <code>sample.kind</code> as "Rounding" to ensure compatibility with R versions < 3.6.0. The order of the elements/rows is kept intact. No replacement is used, why no oversampling will take place. When testing a big <code>data.frame</code> , sampling the rows can help keep the test files somewhat readable.
envir	Environment to evaluate in. Defaults to <code>parent.frame()</code> .
copy_env	Whether to work in a deep copy of the environment. (Logical) Side effects will be captured in copies of the copy, why two copies of the environment will exist at the same time. Disabled by default to save memory but is often preferable to enable, e.g. when the function changes non-local variables.

assign_output	Whether to assign the output of a function call or long selection to a variable. This will avoid recalling the function and decrease cluttering. (Logical) Heuristic: when the `selection` isn't of a string and contains a parenthesis, it is considered a function call. A selection with more than 30 characters will be assigned as well. The tests themselves can be more difficult to interpret, as you will have to look at the assignment to see the object that is being tested.
seed	seed to set. (Whole number)
test_id	Number to append to assignment names. (Whole number) For instance used to create the "output_" name: output_<test_id>.
add_wrapper_comments	Whether to add intro and outro comments. (Logical)
add_test_comments	Whether to add comments for each test. (Logical)
start_with_newline, end_with_newline	Whether to have a newline in the beginning/end. (Logical)
out	Either "insert" or "return". "insert" (Default): Inserts the expectations via <code>rstudioapi::insertText()</code> . "return": Returns the expectations in a list. These can be prepared for insertion with <code>prepare_insertion()</code> .

Details

The following "types" are currently supported or intended to be supported in the future. Please suggest more types and tests in a GitHub issue!

Note: A set of fallback tests will be generated for unsupported objects.

Type	Supported	Notes
Side effects	Yes	Errors, warnings, and messages.
Vector	Yes	Lists are treated differently, depending on their structure.
Factor	Yes	
Data Frame	Yes	List columns (like nested tibbles) are currently skipped.
Matrix	Yes	Supported but could be improved.
Formula	Yes	
Function	Yes	
NULL	Yes	
Array	No	
Dates	No	Base and lubridate.
ggplot2	No	This may be a challenge, but would be cool!

Value

Either NULL or the unprepared expectations as a character vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other expectation generators: [gxs_function\(\)](#), [initializeGXSFunctinAddin\(\)](#), [insertExpectationsAddin\(\)](#)

Examples

```
# Attach packages
library(xpectr)

## Not run:
df <- data.frame('a' = c(1, 2, 3), 'b' = c('t', 'y', 'u'),
                 stringsAsFactors = FALSE)

gxs_selection("stop('This gives an expect_error test!')")
gxs_selection("warning('This gives a set of side effect tests!')")
gxs_selection("message('This also gives a set of side effect tests!')")
gxs_selection("stop('This: tests the -> punctuation!')", strip = FALSE)
gxs_selection("sum(1, 2, 3, 4)")
gxs_selection("df")

tests <- gxs_selection("df", out = "return")
for_insertion <- prepare_insertion(tests)
rstudioapi::insertText(for_insertion)

## End(Not run)
```

```
initializeGXSFunctinAddin
      Initialize gxs_function() call
```

Description**[Experimental]**

Initializes the `gxs_function()` call with the arguments and default values of the selected function. See ``Details`` for how to set a key command.

Usage

```
initializeGXSFunctinAddin(selection = NULL, insert = TRUE, indentation = 0)
```

Arguments

selection	Name of function to test with <code>gxs_function()</code> . (Character) N.B. Mainly intended for testing the addin programmatically.
insert	Whether to insert the code via <code>rstudioapi::insertText()</code> or return them. (Logical) N.B. Mainly intended for testing the addin programmatically.
indentation	Indentation of the selection. (Numeric) N.B. Mainly intended for testing the addin programmatically.

Details

How: Parses and evaluates the selected code string within the parent environment. When the output is a function, it extracts the formals (arguments and default values) and creates the initial `args_values`` for `gxs_function()`. When the output is not a function, it throws an error.

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Initialize `gxs_function()`" and press its field under Shortcut.

Press desired key command, e.g. Alt+F.

Press Apply.

Press Execute.

Value

Inserts `gxs_function()` call for the selected function.

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other expectation generators: `gxs_function()`, `gxs_selection()`, `insertExpectationsAddin()`

Other addins: `assertCollectionAddin()`, `dputSelectedAddin()`, `initializeTestthatAddin()`, `insertExpectationsAddin()`, `navigateTestFileAddin()`, `wrapStringAddin()`

```
initializeTestthatAddin
```

Initializes test_that() call

Description**[Experimental]**

Inserts code for calling `testthat::test_that()`.

See `Details`` for how to set a key command.

Usage

```
initializeTestthatAddin(insert = TRUE, indentation = NULL)
```

Arguments

`insert` Whether to insert the code via `rstudioapi::insertText()` or return it. (Logical)

N.B. Mainly intended for testing the addin programmatically.

`indentation` Indentation of the code. (Numeric)

N.B. Mainly intended for testing the addin programmatically.

Details**How to set up a key command in RStudio:**

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Initialize test_that()" and press its field under Shortcut.

Press desired key command, e.g. Alt+T.

Press Apply.

Press Execute.

Value

Inserts code for calling `testthat::test_that()`.

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other addins: [assertCollectionAddin\(\)](#), [dputSelectedAddin\(\)](#), [initializeGXFunctionAddin\(\)](#), [insertExpectationsAddin\(\)](#), [navigateTestFileAddin\(\)](#), [wrapStringAddin\(\)](#)

insertExpectationsAddin

Creates testthat tests for selected code

Description**[Experimental]**

Inserts relevant `expect_*` tests based on the evaluation of the selected code.

Example: If the selected code is the name of a `data.frame` object, it will create an `expect_equal` test for each column, along with a test of the column names.

Currently supports side effects (error, warnings, messages), `data.frames`, and vectors.

List columns in `data.frames` (like nested tibbles) are currently skipped.

See ``Details`` for how to set a key command.

Usage

```
insertExpectationsAddin(
  selection = NULL,
  insert = TRUE,
  indentation = 0,
  copy_env = FALSE
)
```

```
insertExpectationsCopyEnvAddin(
  selection = NULL,
```

```

insert = TRUE,
indentation = 0,
copy_env = TRUE
)

```

Arguments

selection	String of code. (Character) E.g. "stop('This gives an expect_error test')". N.B. Mainly intended for testing the addin programmatically.
insert	Whether to insert the expectations via <code>rstudioapi::insertText()</code> or return them. (Logical) N.B. Mainly intended for testing the addin programmatically.
indentation	Indentation of the selection. (Numeric) N.B. Mainly intended for testing the addin programmatically.
copy_env	Whether to work in a deep copy of the environment. (Logical) Side effects will be captured in copies of the copy, why two copies of the environment will exist at the same time. Disabled by default to save memory but is often preferable to enable, e.g. when the function changes non-local variables.

Details

How: Parses and evaluates the selected code string within the parent environment (or a deep copy thereof). Depending on the output, it creates a set of unit tests (like `expect_equal(data[["column"]], c(1, 2, 3))`), and inserts them instead of the selection.

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Insert Expectations" and press its field under Shortcut.

Press desired key command, e.g. Alt+E.

Press Apply.

Press Execute.

Value

Inserts `testthat::expect_*` unit tests for the selected code.

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other expectation generators: `gxs_function()`, `gxs_selection()`, `initializeGXFunctionAddin()`

Other addins: `assertCollectionAddin()`, `dputSelectedAddin()`, `initializeGXFunctionAddin()`, `initializeTestthatAddin()`, `navigateTestFileAddin()`, `wrapStringAddin()`

navigateTestFileAddin *Navigates to test file*

Description

[Experimental]

RStudio Addin: Extracts file name and (possibly) line number of a test file from a selection or from clipboard content. Navigates to the file and places the cursor at the line number.

Supported types of strings: "test_x.R:3", "test_x.R#3", "test_x.R".

The string must start with "test_" and contain ".R". It is split at either ":" or "#", with the second element (here "3") being interpreted as the line number.

See ``Details`` for how to set a key command.

Usage

```
navigateTestFileAddin(selection = NULL, navigate = TRUE, abs_path = TRUE)
```

Arguments

selection	String with file name and line number. (Character) E.g. "test_x.R:3:", which navigates to the third line of "/tests/testthat/test_x.R". N.B. Mainly intended for testing the addin programmatically.
navigate	Whether to navigate to the file or return the extracted file name and line number. (Logical) N.B. Mainly intended for testing the addin programmatically.
abs_path	Whether to return the full path or only the file name when <code>`navigate`</code> is FALSE. N.B. Mainly intended for testing the addin programmatically.

Details

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Go To Test File" and press its field under Shortcut.

Press desired key command, e.g. Alt+N.

Press Apply.

Press Execute.

Value

Navigates to file and line number.

Does not return anything.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other addins: [assertCollectionAddin\(\)](#), [dputSelectedAddin\(\)](#), [initializeGXFunctionAddin\(\)](#), [initializeTestthatAddin\(\)](#), [insertExpectationsAddin\(\)](#), [wrapStringAddin\(\)](#)

num_total_elements	<i>Total number of elements</i>
--------------------	---------------------------------

Description**[Experimental]**

Unlists `x` recursively and finds the total number of elements.

Usage

```
num_total_elements(x, deduplicated = FALSE)
```

Arguments

`x` List with elements.
`deduplicated` Whether to only count the unique elements. (Logical)

Details

Simple wrapper for `length(unlist(x, recursive = TRUE, use.names = FALSE))`.

Value

The total number of elements in `x`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other element descriptors: [element_classes\(\)](#), [element_lengths\(\)](#), [element_types\(\)](#)

Examples

```
# Attach packages
library(xpectr)

l <- list(list(list(1, 2, 3), list(2, list(3, 2))),
          list(1, list(list(2, 4), list(7, 1, list(3, 8)))),
          list(list(2, 7, 8), list(10, 2, list(18, 1, 4))))

num_total_elements(l)
num_total_elements(l, deduplicated = TRUE)
```

prepare_insertion *Prepare expectations for insertion*

Description

[Experimental]

Collapses a list/vector of expectation strings and adds the specified indentation.

Usage

```
prepare_insertion(  
  strings,  
  indentation = 0,  
  trim_left = FALSE,  
  trim_right = FALSE  
)
```

Arguments

strings	Expectation strings. (List or Character) As returned with <code>gxs_*</code> functions with <code>out = "return"</code> .
indentation	Indentation to add. (Numeric)
trim_left	Whether to trim whitespaces from the beginning of the collapsed string. (Logical)
trim_right	Whether to trim whitespaces from the end of the collapsed string. (Logical)

Value

A string for insertion with `rstudioapi::insertText()`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages  
library(xpectr)  
  
## Not run:  
df <- data.frame('a' = c(1, 2, 3), 'b' = c('t', 'y', 'u'),  
                stringsAsFactors = FALSE)  
  
tests <- gxs_selection("df", out = "return")  
for_insertion <- prepare_insertion(tests)  
for_insertion  
rstudioapi::insertText(for_insertion)  
  
## End(Not run)
```

set_test_seed	<i>Set random seed for unit tests</i>
---------------	---------------------------------------

Description**[Experimental]**

In order for tests to be compatible with R versions < 3.6.0, we set the `sample.kind` argument in `set.seed()` to "Rounding" when using R versions >= 3.6.0.

Usage

```
set_test_seed(seed = 42, ...)
```

Arguments

seed	Random seed.
...	Named arguments to <code>set.seed()</code> .

Details

Initially contributed by R. Mark Sharp (github: @rmsharp).

Value

NULL.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>
R. Mark Sharp

simplified_formals	<i>Extract and simplify a function's formal arguments</i>
--------------------	---

Description**[Experimental]**

Extracts `formals` and formats them as an easily testable character vector.

Usage

```
simplified_formals(fn)
```

Arguments

fn	Function.
----	-----------

Value

A character vector with the simplified formals.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages
library(xpectr)

fn1 <- function(a = "x", b = NULL, c = NA, d){
  paste0(a, b, c, d)
}

simplified_formals(fn1)
```

smpI

Random sampling

Description**[Experimental]**

Samples a vector, factor or data.frame. Useful to reduce size of testthat expect_* tests. Not intended for other purposes.

Wraps `sample.int()`. data.frames are sampled row-wise.

The seed is set within the function with `sample.kind` as "Rounding" for compatibility with R versions < 3.6.0. On exit, the random state is restored.

Usage

```
smpI(data, n, keep_order = TRUE, seed = 42)
```

Arguments

data	vector or data.frame. (Logical)
n	Number of elements/rows to sample. N.B. No replacement is used, why n > the number of elements/rows in <code>`data`</code> won't perform oversampling.
keep_order	Whether to keep the order of the elements. (Logical)
seed	seed to use. The seed is set with <code>sample.kind = "Rounding"</code> for compatibility with R versions < 3.6.0.

Value

When ``data`` has $\leq n$ elements, ``data`` is returned. Otherwise, ``data`` is sampled and returned.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages
library(xpectr)

smp1(c(1,2,3,4,5), n = 3)
smp1(data.frame("a" = c(1,2,3,4,5), "b" = c(2,3,4,5,6), stringsAsFactors = FALSE), n = 3)
```

stop_if

Simple side effect functions

Description

[Experimental]

If the `condition` is TRUE, generate error/warning/message with the supplied message.

Usage

```
stop_if(condition, message = NULL, sys.parent.n = 0L)
```

```
warn_if(condition, message = NULL, sys.parent.n = 0L)
```

```
message_if(condition, message = NULL, sys.parent.n = 0L)
```

Arguments

`condition` The condition to check. (Logical)

`message` Message. (Character)

Note: If NULL, the `condition` will be used as message.

`sys.parent.n` The number of generations to go back when calling the message function.

Details

When `condition` is FALSE, they return NULL invisibly.

When `condition` is TRUE:

stop_if(): Throws error with the supplied message.

warn_if(): Throws warning with the supplied message.

message_if(): Generates message with the supplied message.

Value

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages
library(xpectr)
## Not run:
a <- 0
stop_if(a == 0, "'a' cannot be 0.")
warn_if(a == 0, "'a' was 0.")
message_if(a == 0, "'a' was so kind to be 0.")

## End(Not run)
```

strip

Strip strings of non-alphanumeric characters

Description**[Experimental]**

1. Removes any character that is not alphanumeric or a space.
2. (Disabled by default): Remove numbers.
3. Reduces multiple consecutive whitespaces to a single whitespace and trims ends.

Can for instance be used to simplify error messages before checking them.

Usage

```
strip(
  strings,
  replacement = "",
  remove_spaces = FALSE,
  remove_numbers = FALSE,
  remove_ansi = TRUE,
  lowercase = FALSE,
  allow_na = TRUE
)
```

Arguments

strings	vector of strings. (Character)
replacement	What to replace blocks of punctuation with. (Character)
remove_spaces	Whether to remove all whitespaces. (Logical)
remove_numbers	Whether to remove all numbers. (Logical)
remove_ansi	Whether to remove ANSI control sequences. (Logical)
lowercase	Whether to make the strings lowercase. (Logical)
allow_na	Whether to allow strings to contain NAs. (Logical)

Details

1. ANSI control sequences are removed with `fansi::strip_ctl()`.
2. `gsub("[^[:alnum:][:blank:]]", replacement, strings)`
3. `gsub('[0-9]+', '', strings)` (Note: only if specified!)
4. `trimws(gsub("[[:blank:]]+", " ", strings))` (Or "" if `remove_spaces` is TRUE)

Value

The stripped strings.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other strippers: `strip_msg()`

Examples

```
# Attach packages
library(xpectr)

strings <- c(
  "Hello! I am George. \n\rDon't call me Frank! 123",
  " \tAs that, is, not, my, name!"
)

strip(strings)
strip(strings, remove_spaces = TRUE)
strip(strings, remove_numbers = TRUE)
```

strip_msg

Strip side-effect messages of non-alphanumeric characters and rethrow them

Description**[Experimental]**

Catches side effects (error, warnings, messages), strips the message strings of non-alphanumeric characters with `strip()` and regenerates them.

When numbers in error messages vary slightly between systems (and this variation isn't important to catch), we can strip the numbers as well.

Use case: Sometimes `testthat` tests have differences in punctuation and newlines on different systems. By stripping both the error message and the expected message (with `strip()`), we can avoid such failed tests.

Usage

```
strip_msg(  
  x,  
  remove_spaces = FALSE,  
  remove_numbers = FALSE,  
  remove_ansi = TRUE,  
  lowercase = FALSE  
)
```

Arguments

x	Code that potentially throws warnings, messages, or an error.
remove_spaces	Whether to remove all whitespaces. (Logical)
remove_numbers	Whether to remove all numbers. (Logical)
remove_ansi	Whether to remove ANSI control sequences. (Logical)
lowercase	Whether to make the strings lowercase. (Logical)

Value

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other strippers: [strip\(\)](#)

Examples

```
# Attach packages  
library(xpectr)  
library(testthat)  
  
## Not run:  
strip_msg(stop("this 'dot' .\n is removed! 123"))  
strip_msg(warning("this 'dot' .\n is removed! 123"))  
strip_msg(message("this 'dot' .\n is removed! 123"))  
strip_msg(message("this 'dot' .\n is removed! 123"), remove_numbers = TRUE)  
error_fn <- function(){stop("this 'dot' .\n is removed! 123")}  
strip_msg(error_fn())  
  
# With testthat tests  
expect_error(strip_msg(error_fn()),  
             strip("this 'dot' .\n is removed! 123"))  
expect_error(strip_msg(error_fn(), remove_numbers = TRUE),  
             strip("this 'dot' .\n is removed! 123", remove_numbers = TRUE))  
  
## End(Not run)
```

suppress_mw	<i>Suppress warnings and messages</i>
-------------	---------------------------------------

Description

[Experimental]

Run expression wrapped in both `suppressMessages()` and `suppressWarnings()`.

Usage

```
suppress_mw(expr)
```

Arguments

`expr` Any expression to run within `suppressMessages()` and `suppressWarnings()`.

Details

```
suppressWarnings(suppressMessages(expr))
```

Value

The output of `expr`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages
library(xpectr)

fn <- function(a, b){
  warning("a warning")
  message("a message")
  a + b
}

suppress_mw(fn(1, 5))
```

wrapStringAddin	<i>Wraps the selection with paste0</i>
-----------------	--

Description

[Experimental]

Splits the selection every `n` characters and inserts it in a `paste0()` call.

See `Details` for how to set a key command.

Usage

```
wrapStringAddin(
  selection = NULL,
  indentation = 0,
  every_n = NULL,
  tolerance = 10,
  insert = TRUE
)
```

Arguments

<code>selection</code>	String of code. (Character) N.B. Mainly intended for testing the addin programmatically.
<code>indentation</code>	Indentation of the selection. (Numeric) N.B. Mainly intended for testing the addin programmatically.
<code>every_n</code>	Number of characters per split. If NULL, the following is used to calculate the string width: <code>max(min(80 - indentation, 70), 50)</code> N.B. Strings shorter than <code>every_n + tolerance</code> will not be wrapped.
<code>tolerance</code>	Tolerance. Number of characters. We may prefer not to split a string that's only a few characters too long. Strings shorter than <code>every_n + tolerance</code> will not be wrapped.
<code>insert</code>	Whether to insert the wrapped text via <code>rstudioapi::insertText()</code> or return it. (Logical) N.B. Mainly intended for testing the addin programmatically.

Details

How to set up a key command in RStudio:

After installing the package. Go to:

Tools >> Addins >> Browse Addins >> Keyboard Shortcuts.

Find "Wrap String with paste0" and press its field under Shortcut.

Press desired key command, e.g. Alt+P.

Press Apply.

Press Execute.

Value

Inserts the following (with newlines and correct indentation):

```
paste0("first n chars", "next n chars")
```

Returns NULL invisibly.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other addins: [assertCollectionAddin\(\)](#), [dputSelectedAddin\(\)](#), [initializeGXFunctionAddin\(\)](#), [initializeTestthatAddin\(\)](#), [insertExpectationsAddin\(\)](#), [navigateTestFileAddin\(\)](#)

xpectr

xpectr: A package for generating tests for testthat unit testing

Description

A set of utilities and RStudio addins for generating tests.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Index

- * **addins**
 - assertCollectionAddin, 2
 - dputSelectedAddin, 6
 - initializeGXFunctionAddin, 16
 - initializeTestthatAddin, 17
 - insertExpectationsAddin, 18
 - navigateTestFileAddin, 20
 - wrapStringAddin, 30
- * **capturers**
 - capture_parse_eval_side_effects, 3
 - capture_side_effects, 4
- * **element descriptors**
 - element_classes, 7
 - element_lengths, 8
 - element_types, 9
 - num_total_elements, 21
- * **expectation generators**
 - gxs_function, 10
 - gxs_selection, 13
 - initializeGXFunctionAddin, 16
 - insertExpectationsAddin, 18
- * **inserters**
 - prepare_insertion, 22
- * **strippers**
 - strip, 26
 - strip_msg, 27
- assertCollectionAddin, 2, 6, 17–19, 21, 31
- capture_error(), 4
- capture_messages(), 4
- capture_parse_eval_side_effects, 3, 5
- capture_side_effects, 4, 4
- capture_side_effects(), 3
- capture_warnings(), 4
- class(), 7
- dput(), 6
- dputSelectedAddin, 3, 6, 17–19, 21, 31
- element_classes, 7, 8, 9, 21
- element_lengths, 7, 8, 9, 21
- element_types, 7, 8, 9, 21
- expect_equal, 13, 18
- fansi::strip_ctl(), 27
- formals, 23
- gxs_function, 10, 16, 17, 19
- gxs_function(), 17
- gxs_selection, 12, 13, 17, 19
- initializeGXFunctionAddin, 3, 6, 12, 16, 16, 18, 19, 21, 31
- initializeTestthatAddin, 3, 6, 17, 17, 19, 21, 31
- insertExpectationsAddin, 3, 6, 12, 16–18, 18, 21, 31
- insertExpectationsAddin(), 13
- insertExpectationsCopyEnvAddin (insertExpectationsAddin), 18
- length(), 8
- message_if (stop_if), 25
- navigateTestFileAddin, 3, 6, 17–19, 20, 31
- num_total_elements, 7–9, 21
- parent.frame(), 4, 5, 11, 14
- paste0(), 30
- prepare_insertion, 22
- prepare_insertion(), 12, 15
- rstudioapi::insertText(), 2, 6, 12, 15–17, 19, 22, 30
- sample.int(), 24
- set.seed(), 23
- set_test_seed, 23
- simplified_formals, 23
- smpl, 24
- smpl(), 11, 14
- stop_if, 25
- strip, 26, 28
- strip(), 11, 14, 27
- strip_msg, 27, 27
- strip_msg(), 11, 14
- suppress_mw, 29
- suppressMessages(), 29

`suppressWarnings()`, [29](#)

`testthat::expect_*`, [19](#)

`testthat::test_that()`, [17](#), [18](#)

`typeof()`, [9](#)

`warn_if(stop_if)`, [25](#)

`wrapStringAddin`, [3](#), [6](#), [17–19](#), [21](#), [30](#)

`xpectr`, [31](#)