

Package ‘tynding’

March 31, 2026

Title 'Typst' Bindings

Version 0.1.2

Description Provides bindings to the 'Typst' typesetting system, enabling users to compile 'Typst' documents directly from R. The package interfaces with the 'Typst' 'Rust' library to render documents, making it possible to integrate 'Typst'-based workflows into R scripts, reports, and reproducible research pipelines. It supports programmatic document generation, compilation, and output handling, facilitating seamless use of 'Typst' alongside tools such as knitr and Quarto.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

URL <https://github.com/y-sunflower/tynding>

BugReports <https://github.com/y-sunflower/tynding/issues>

Depends R (>= 4.2)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Config/rextendr/version 0.4.2

SystemRequirements Cargo (Rust's package manager), rustc >= 1.89.0, xz

Imports jsonlite

NeedsCompilation yes

Author Joseph Barbier [aut, cre]

Maintainer Joseph Barbier <joseph@ysunflower.com>

Repository CRAN

Date/Publication 2026-03-31 09:40:02 UTC

Contents

is_valid_typst	2
typst_compile	2
typst_write	3

Index	5
--------------	----------

is_valid_typst	<i>Is valid Typst?</i>
----------------	------------------------

Description

Check that a character vector is valid Typst markup by compiling it. If no error, it assumes the code is valid.

Usage

```
is_valid_typst(x, error_on_failure = FALSE)
```

Arguments

x	A character vector
error_on_failure	Whether to raise an error if the code is invalid. Default to FALSE.

Value

Indicates whether the output PDF file exists (for example, if TRUE, then Typst has been compiled successfully).

Examples

```
typst_code <- c("= Hello World", "This is a Typst document.")
is_valid_typst(typst_code) # TRUE

typst_code <- c("= Hello World", "#This is a Typst document.")
is_valid_typst(typst_code) # FALSE

## Not run:
typst_code <- c("= Hello World", "#This is a Typst document.")
is_valid_typst(typst_code, error_on_failure = TRUE) # ERROR

## End(Not run)
```

typst_compile	<i>Compile a .typ file and return the output path.</i>
---------------	--

Description

This function uses the Typst Rust library to compile a .typ file to a supported output format and return the output path.

Usage

```

typst_compile(
  file,
  output = NULL,
  font_path = NULL,
  pdf_standard = NULL,
  output_format = NULL,
  ...
)

```

Arguments

file	Path to an existing .typ file.
output	Optional output path. Defaults to the input path with the extension implied by the output format.
font_path	Optional path to font files.
pdf_standard	Optional PDF standard specification. Options are: : 1.4, 1.5, 1.6, 1.7, 2.0, a-1b, a-1a, a-2b, a-2u, a-2a, a-3b, a-3u, a-3a, a-4, a-4f, a-4e, ua-1. Only used for PDF output.
output_format	Optional output format. Supported values are pdf, html, png, and svg. Defaults to NULL, which means "infer from output when possible, otherwise use pdf". Multi-page png and svg outputs are merged into a single image.
...	Named inputs passed to the Typst document via <code>sys.inputs</code> . Each argument must be named. Scalar values are passed as-is; other values are JSON-encoded.

Value

Output path, invisibly.

typst_write	<i>Write a Typst file from a character vector</i>
-------------	---

Description

Create a Typst file (.typ) from a character vector.

Usage

```
typst_write(x, output = NULL)
```

Arguments

x	A character vector representing Typst code.
output	Optional output file path (must end with ".typ"). If NULL, a temporary file is created.

Value

The path to the written .typ file, invisibly.

Examples

```
## Not run:  
code <- c("= Hello World", "This is a Typst document.")  
typst_write(code, output = "hello.typ")  
  
## End(Not run)
```

Index

`is_valid_typst`, 2

`typst_compile`, 2

`typst_write`, 3