

Package ‘bmlm’

September 25, 2023

Title Bayesian Multilevel Mediation

Version 1.3.15

Date 2023-09-25

Description Easy estimation of Bayesian multilevel mediation models with Stan.

URL <https://github.com/mvuorre/bmlm/>

BugReports <https://github.com/mvuorre/bmlm/issues/>

License GPL (>= 3)

LazyData true

NeedsCompilation yes

Depends R (>= 3.4.0), Rcpp (>= 0.12.0)

Imports ggplot2 (>= 2.0.0), methods, RcppParallel (>= 5.0.1), rstan (>= 2.26.0), rstantools (>= 2.3.1.1)

Suggests qgraph, knitr, rmarkdown, reshape2, dplyr

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0), RcppParallel (>= 5.0.1), rstan (>= 2.26.0), StanHeaders (>= 2.26.0)

RoxygenNote 7.1.2

Encoding UTF-8

SystemRequirements GNU make

Biarch true

Author Matti Vuorre [aut, cre] (<<https://orcid.org/0000-0001-5052-066X>>)

Maintainer Matti Vuorre <m.j.vuorre@tilburguniversity.edu>

Repository CRAN

Date/Publication 2023-09-25 14:22:24 UTC

R topics documented:

bmlm-package	2
BLch9	2
isolate	3
MEC2010	4
mlm	4
mlm_pars_plot	6
mlm_path_plot	7
mlm_spaghetti_plot	8
mlm_summary	9

Index	12
--------------	-----------

bmlm-package	<i>bmlm: Easy estimation of Bayesian multilevel mediation models with Stan.</i>
--------------	---

Description

See <https://mvuorre.github.io/bmlm/> for a short tutorial.

BLch9	<i>Relationship between work stressors, work dissatisfaction, and relationship dissatisfaction.</i>
-------	---

Description

Simulated data from Intensive Longitudinal Methods: An Introduction to Diary and Experience Sampling Research. (Bolger, & Laurenceau, 2013, chapter 9; <http://www.intensivelongitudinal.com/index.html>).

Usage

```
data(BLch9)
```

Format

A data frame with 2100 rows and 8 variables:

- id** ID of study participant
- time** Time
- fwkstrs** Number of work stressors
- fwkdis** Work dissatisfaction rating
- frelidis** Relationship dissatisfaction
- x** Subject-mean deviated number of work stressors
- m** Subject-mean deviated work dissatisfaction rating
- y** Subject-mean deviated relationship dissatisfaction

Source

<http://www.intensivelongitudinal.com/datasets.html>

isolate

Create isolated within- (and optionally between-) person variables.

Description

Creates variables that represent pure within- and between-person predictors.

Usage

```
isolate(d = NULL, by = NULL, value = NULL, z = FALSE, which = "within")
```

Arguments

d	A <code>data.frame</code> .
by	A vector of values in d by which the data is clustered. i.e. a vector of unique participant IDs.
value	Names of columns in d to isolate. Multiple values can be given by <code>value = c("var1", "var2", "var3")</code>
z	Should the created values be standardized (defaults to FALSE).
which	Which component to return. "within" (default) returns within-person deviations only; "between" returns between-person means only; "both" returns both.

Value

A `data.frame` with additional columns for the within- and between-person variables. The new columns are labelled `_cw` for centered-within and `_cb` for centered-between.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
# Create within-person deviations of work stressors in BLch9.  
data(BLch9)  
BLch9 <- isolate(BLch9, by = "id", value = "fwkstrs")  
head(BLch9) # Now has new column for within-person work stressors.
```

MEC2010

*Judgments of performance in a video game***Description**

Data from an experiment where participants rated their performance in a video game in two conditions. (Experiment 1 in Metcalfe, Eich, & Castel, 2010; <https://www.sciencedirect.com/science/article/pii/S0010027710001113>).

Usage

```
data(MEC2010)
```

Format

A data frame with 344 rows and 4 variables:

subj Subject id number.
lag Lag condition (0 = no lag, 1 = 250ms lag).
hr Hit rate.
jop Judgment of Performance.

Source

Metcalfe, J., Eich, T. S., & Castel, A. D. (2010). Metacognition of agency across the lifespan. *Cognition*, 116(2), 267-282. doi:[10.1016/j.cognition.2010.05.009](https://doi.org/10.1016/j.cognition.2010.05.009)

*mlm**Estimate a multilevel mediation model***Description**

Estimates a Bayesian multilevel mediation model using Stan.

Usage

```
mlm(  
  d = NULL,  
  id = "id",  
  x = "x",  
  m = "m",  
  y = "y",  
  priors = NULL,  
  binary_y = FALSE,  
  ...  
)
```

Arguments

d	A <code>data.frame</code> or a <code>data_frame</code> .
id	Column of participant IDs in data.
x	Column of X values in data.
m	Column of M values in data.
y	Column of Y values in data.
priors	A list of named values to be used as the prior scale parameters. See details.
binary_y	Set to TRUE if y is binary and should be modelled with logistic regression. Defaults to FALSE (y treated as continuous.) This feature is experimental.
...	Other optional parameters passed to <code>rstan::stan()</code> .

Details

Draw samples from the joint posterior distribution of a multilevel mediation model using Stan.

Priors:

Users may pass a list of named values for the `priors` argument. The values will be used to define the scale parameter of the respective prior distributions. This list may specify some or all of the following parameters:

dy, dm Regression intercepts (for Y and M as outcomes, respectively.)

a, b, cp Regression slopes.

tau_x Varying effects SDs for above parameters (e.g replace x with a.)

lkj_shape Shape parameter for the LKJ prior.

See examples for specifying the following: Gaussian distributions with SD = 10 as priors for the intercepts, Gaussians with SD = 2 for the slopes, Half-Cauchy distributions with scale parameters 1 for the varying effects SDs, and an LKJ prior of 2.

Value

An object of S4 class `stanfit`, with all its available methods.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
## Not run:
## Run example from Bolger and Laurenceau (2013)
data(BLch9)
fit <- mlm(BLch9)
mlm_summary(fit)

### With priors
Priors <- list(dy = 10, dm = 10, a = 2, b = 2, cp = 2,
  tau_dy = 1, tau_dm = 1, tau_a = 1, tau_b = 1, tau_cp = 1,
```

```

lkj_shape = 2)
fit <- mlm(BLch9, priors = Priors)

## End(Not run)

```

mlm_pars_plot*Plot estimated parameters of multilevel mediation model***Description**

Plot the model's estimated parameters as histograms or a coefficient plot.

Usage

```

mlm_pars_plot(
  mod = NULL,
  type = "hist",
  color = "black",
  p_shape = 15,
  p_size = 1.2,
  level = 0.95,
  nrow = 3,
  pars = c("a", "b", "cp", "covab", "me", "c", "pme")
)

```

Arguments

<code>mod</code>	A Stanfit model estimated with <code>mlm()</code> .
<code>type</code>	Type of the plot, <code>hist</code> , <code>coef</code> , or <code>violin</code> .
<code>color</code>	Color (and fill) for plots.
<code>p_shape</code>	Shape of points for <code>coefplot</code> .
<code>p_size</code>	Size of points for <code>coefplot</code> .
<code>level</code>	X level for Credible Intervals. (Defaults to .95.)
<code>nrow</code>	Number of rows for multiple histograms.
<code>pars</code>	Which parameters to plot.

Details

The point estimate for the coefficient plot is the posterior mean.

Value

A `ggplot2` object.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

`mlm_path_plot` *Plot bmlm's mediation model as a path diagram*

Description

Plots a path diagram for an estimated multilevel mediation model.

Usage

```
mlm_path_plot(  
  mod = NULL,  
  xlab = "X",  
  ylab = "Y",  
  mlab = "M",  
  level = 0.95,  
  random = TRUE,  
  text = FALSE,  
  id = NULL,  
  digits = 2,  
  ...  
)
```

Arguments

<code>mod</code>	A Stanfit model estimated with <code>mlm()</code> .
<code>xlab</code>	Label for X
<code>ylab</code>	Label for Y
<code>mlab</code>	Label for M
<code>level</code>	"Confidence" level for credible intervals. (Defaults to .95.)
<code>random</code>	Should the "random" effects SDs be displayed? (Default = TRUE)
<code>text</code>	Should additional parameter values be displayed? (Defaults to FALSE.)
<code>id</code>	Plot an individual-level path diagram by specifying ID number.
<code>digits</code>	Number of significant digits to show on graph. (Default = 2.)
...	Other arguments passed on to <code>qgraph::qgraph()</code> .

Details

Plots a path diagram of the mediation model, with estimated parameter values and credible intervals. Can also be used to draw a template diagram of the mediation model by not specifying input to the `mod` argument.

To modify various settings of the underlying `qgraph` object, see [qgraph](#).

Value

A `qgraph` object.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
# Draw a template path diagram of the mediation model
mlm_path()
```

mlm_spaghetti_plot *Plot fitted values of M and Y from multilevel mediation model*

Description

Plot population-level fitted values and X values, for M and Y.

Usage

```
mlm_spaghetti_plot(
  mod = NULL,
  d = NULL,
  id = "id",
  x = "x",
  m = "m",
  y = "y",
  level = 0.95,
  n = 12,
  binary_y = FALSE,
  mx = "fitted",
  fixed = TRUE,
  random = TRUE,
  h_jitter = 0,
  v_jitter = 0,
  bar_width = 0.2,
  bar_size = 0.75,
  n_samples = NA
)
```

Arguments

<code>mod</code>	A multilevel mediation model estimated with <code>mlm()</code> .
<code>d</code>	A <code>data.frame</code> or a <code>data_frame</code> used in fitting model.
<code>id</code>	Name of id variable (identifying subjects) in data (d).
<code>x</code>	Name of X variable in data.
<code>m</code>	Name of M variable in data.
<code>y</code>	Name of Y variable in data.

level	X level for Credible Intervals. (Defaults to .95.)
n	Number of points along X to evaluate fitted values on. See details.
binary_y	Set to TRUE if the outcome variable (Y) is 0/1.
mx	Should the X axis of the M-Y figure be "fitted" values, or "data" values. Defaults to "fitted".
fixed	Should the population-level ("fixed") fitted values be shown?
random	Should the subject-level ("random") fitted values be shown?
h_jitter	Horizontal jitter of points. Defaults to 0.
v_jitter	Vertical jitter of points. Defaults to 0.
bar_width	Width of the error bars. Defaults to 0.2.
bar_size	Thickness of the error bars. Defaults to 0.75.
n_samples	Number of MCMC samples to use in calculating fitted values. See details.

Details

If n = 2, the fitted values will be represented as points with X line with a Confidence Ribbon instead. If a very large model is fitted with a large number of MCMC iterations, the function might take a long time to run. In these cases, users can set n_samples to a smaller value (e.g. 1000), in which case the fitted values (and the CIs) will be based on a random subset of n_samples MCMC samples. The default value is NA, meaning that all MCMC samples are used.

Value

A list of two ggplot2 objects.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

mlm_summary

Print a summary of the estimated multilevel mediation model

Description

Prints the estimated parameters (numerical summaries of the marginal posterior distributions).

Usage

```
mlm_summary(
  mod = NULL,
  level = 0.95,
  pars = c("a", "b", "cp", "me", "c", "pme"),
  digits = 2
)
```

Arguments

mod	A <code>stanfit</code> object obtained from <code>mlm()</code>
level	"Confidence" level; Defines the limits of the credible intervals. Defaults to .95 (i.e. displays 95% CIs.)
pars	Parameters to summarize. Defaults to main average-level parameters. See Details for more information.
digits	How many decimal points to display in the output. Defaults to 2.

Details

After estimating a model (drawing samples from the joint posterior probability distribution) with `mlm()`, show the estimated results by using `mlm_summary(fit)`, where `fit` is an object containing the fitted model.

The function shows, for each parameter specified with `pars`, the posterior mean, and limits of the Credible Interval as specified by `level`. For example, `level = .91` shows a 91% Credible Interval, which summarizes the central 91% mass of the marginal posterior distribution.

Parameters: By default, `mlm()` estimates and returns a large number of parameters, including the varying effects, and their associated standard deviations. However, `mlm_summary()` by default only displays a subset of the estimated parameters:

- a** Regression slope of the X -> M relationship.
- b** Regression slope of the M -> Y relationship.
- cp** Regression slope of the X -> Y relationship. (Direct effect.)
- me** Mediated effect ($a * b + \sigma_{a_j} b_j$).
- c** Total effect of X on Y. ($cp + me$)
- pme** Percent mediated effect.

The user may specify `pars = NULL` to display all estimated parameters. Other options include e.g. `pars = "tau"` to display the varying effects' standard deviations. To display all the group-level parameters (also known as random effects) only, specify `pars = "random"`. With this argument, `mlm_summary()` prints the following parameters:

- tau_a** Standard deviation of subject-level a_{-js} .
- tau_b** Standard deviation of subject-level b_{-js} .
- tau_cp** Standard deviation of subject-level $c\backslash'_{-js}$.
- covab** Estimated covariance of a_{-j} and b_{-js} .
- corrab** Estimated correlation of a_{-j} and b_{-js} .

To learn more about the additional parameters, refer to the Stan code (`cat(get_stancode(fit))`).

Value

A `data.frame` summarizing the estimated multilevel mediation model:

Parameter Name of parameter

Mean Mean of parameter's posterior distribution.

Median Median of parameter's posterior distribution.

SE Standard deviation of parameter's posterior distribution.

ci_lwr The lower limit of Credible Intervals.

ci_upr The upper limit of Credible Intervals.

n_eff Number of efficient samples.

Rhat Should be 1.00.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Index

* datasets

BLch9, [2](#)

MEC2010, [4](#)

BLch9, [2](#)

bmlm (bmlm-package), [2](#)

bmlm-package, [2](#)

isolate, [3](#)

MEC2010, [4](#)

mlm, [4](#)

mlm_pars_plot, [6](#)

mlm_path_plot, [7](#)

mlm_spaghetti_plot, [8](#)

mlm_summary, [9](#)

qgraph, [7](#)