

Package ‘nycOpenData’

January 26, 2026

Type Package

Title Convenient Access to NYC Open Data API Endpoints

Version 0.1.5

Description Provides a unified set of helper functions to access datasets from the NYC Open Data platform <<https://opendata.cityofnewyork.us/>>. Functions return results as tidy tibbles and support optional filtering, sorting, and row limits via the Socrata API. The package includes endpoints for 311 service requests, DOB job applications, juvenile justice metrics, school safety, environmental data, event permitting, and additional citywide datasets. The package is utilized as a primary pedagogical tool for teaching data acquisition in 'Reproducible Research Using R'.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Imports httr, jsonlite, tibble, curl

Suggests ggplot2, knitr, rmarkdown, testthat (>= 3.0.0), vcr (>= 0.6.0), webmockr

URL <https://martinezc1.github.io/nycOpenData/>,
<https://github.com/martinezc1/nycOpenData>

BugReports <https://github.com/martinezc1/nycOpenData/issues>

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Christian Martinez [aut, cre]

Maintainer Christian Martinez <c.martinez0@outlook.com>

Repository CRAN

Date/Publication 2026-01-25 23:00:02 UTC

Contents

nyc_311	3
nyc_311_2010_2019	4
nyc_any_dataset	5
nyc_borough_community_report	5
nyc_cause_of_death	6
nyc_city_record	7
nyc_civil_service_list	8
nyc_daily_attendance_2018_2019	9
nyc_detention_admissions	10
nyc_dhs_daily_report	11
nyc_dob_job_applications	12
nyc_dob_permit_issuance	13
nyc_domestic_violence_annual_report	14
nyc_dop_Juvenile_cases	15
nyc_dop_juvenile_rearrest_rate	16
nyc_film_permits	17
nyc_for_hire_vehicles	18
nyc_homeless_drop_in_centers	19
nyc_homeless_population_by_year	20
nyc_medallion_drivers_active	21
nyc_medallion_drivers_authorized	22
nyc_motor_vehicle_collisions_crashes	23
nyc_museum_locations	24
nyc_nYPD_hate_crimes	25
nyc_open_parking_camera_violations	26
nyc_period_attendance_reporting	27
nyc_permit_events_historic	28
nyc_pets_in_shelters	29
nyc_restaurant_inspection_results	30
nyc_runaway_and_homeless_youth_daily_census	31
nyc_school_discharge	33
nyc_school_discharge_report_2013_2015	34
nyc_school_discharge_report_2015_2018	35
nyc_street_hail_livery_active	36
nyc_tlc_new_driver_app_status	37
nyc_tree_census_2015	38
nyc_urban_park_animal_condition	39
nyc_violent_disruptive_school_incidents	40

Index

42

nyc_311NYC 311 Service Requests

Description

Downloads NYC 311 Service Request data from NYC Open Data.

Usage

```
nyc_311(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset contains all service requests made to NYC 311 since 2012. Data is updated daily and includes agency, complaint type, location, and resolution.

Value

A tibble containing 311 Service Request data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/311-Service-Requests-from-2020-to-Present/erm2-nwe9/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_311(limit = 2)
  small_sample

  nyc_311(filters = list(agency = "NYPD", city = "BROOKLYN"))
}
```

nyc_311_2010_2019	<i>NYC 311 Service Requests</i>
-------------------	---------------------------------

Description

Downloads NYC 311 Service Request from 2010 to 2019 data from NYC Open Data.

Usage

```
nyc_311_2010_2019(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset contains all service requests made to NYC 311 from 2010 to 2019. Data is updated daily and includes agency, complaint type, location, and resolution.

Value

A tibble containing 311 Service Request data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/311-Service-Requests-from-2010-to-2019/76ig-c548/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_311_2010_2019(limit = 2)
  small_sample

  nyc_311_2010_2019(filters = list(agency = "NYPD", city = "BROOKLYN"))
}
```

nyc_any_dataset	<i>Load Any NYC Open Data Dataset</i>
-----------------	---------------------------------------

Description

Downloads any NYC Open Data dataset given its Socrata JSON endpoint.

Usage

```
nyc_any_dataset(json_link, limit = 10000, timeout_sec = 30)
```

Arguments

json_link	A Socrata dataset JSON endpoint URL (e.g., "https://data.cityofnewyork.us/resource/abcd-1234.json").
limit	Number of rows to retrieve (default = 10,000).
timeout_sec	Request timeout in seconds (default = 30).

Value

A tibble containing the requested dataset.

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.
```

```
if (curl::has_internet()) {
  endpoint <- "https://data.cityofnewyork.us/resource/erm2-nwe9.json"
  out <- try(nyc_any_dataset(endpoint, limit = 3), silent = TRUE)
  if (!inherits(out, "try-error")) {
    head(out)
  }
}
```

nyc_borough_community_report	<i>NYC Borough/Community District Report</i>
------------------------------	--

Description

Downloads Borough/Community District Report data from NYC Open Data.

Usage

```
nyc_borough_community_report(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.
<code>timeout_sec</code>	Request timeout in seconds (default = 30).

Details

This dataset provides monthly reports by borough and community district, covering metrics such as service requests, inspections, and community outreach. It's published by NYC Department of Social Services for transparency and analysis.

Value

A tibble containing Borough/Community District Report data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/5awp-wfkt>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_borough_community_report(limit = 2)
  head(small_sample)

  nyc_borough_community_report(filters = list(borough = "Bronx"))
}
```

<code>nyc_cause_of_death</code>	<i>New York City Leading Causes of Death</i>
---------------------------------	--

Description

Downloads New York City Leading Causes of Death data from NYC Open Data.

Usage

```
nyc_cause_of_death(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.
<code>timeout_sec</code>	Request timeout in seconds (default = 30).

Details

The leading causes of death by sex and ethnicity in New York City in since 2007. Cause of death is derived from the NYC death certificate which is issued for every death that occurs in New York City.

Value

A tibble containing New York City Leading Causes of Death data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Health/New-York-City-Leading-Causes-of-Death/jb7j-dtam/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_cause_of_death(limit = 2)
  small_sample

  nyc_cause_of_death(filters = list(sex = "M"))
}
```

nyc_city_record	<i>City Record Online</i>
-----------------	---------------------------

Description

Downloads City Record Online data from NYC Open Data.

Usage

```
nyc_city_record(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The City Record Online (CROL) is a fully searchable database of notices published in the City Record newspaper, including, but not limited to: public hearings and meetings, public auctions and sales, solicitations and awards and official rules proposed and adopted by city agencies.

Value

A tibble containing City Record Online data.

Source

NYC Open Data: <https://data.cityofnewyork.us/City-Government/City-Record-Online/dg92-zbpx/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_city_record(limit = 2)
  small_sample

  nyc_city_record(filters = list(short_title = "APPOINTED"))
}
```

nyc_civil_service_list

NYC Civil Service List (Active)

Description

Downloads Civil Service List (Active) data from NYC Open Data.

Usage

```
nyc_civil_service_list(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset provides information about active Civil Service lists, including eligible candidates, examination numbers, and certification status. Published by the NYC Department of Citywide Administrative Services (DCAS).

Value

A tibble containing Civil Service List (Active) data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/vx8i-nprf>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.
```

```
if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_civil_service_list(limit = 2)
  small_sample

  nyc_civil_service_list(filters = list(last_name = "Martinez"))
}
```

nyc_daily_attendance_2018_2019
2018-2019 Daily Attendance

Description

Downloads 2018-2019 Daily Student Attendance from NYC Open Data.

Usage

```
nyc_daily_attendance_2018_2019(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Daily listing (counts) of students registered, present, absent and released by School DBN.

Value

A tibble containing 2018–2019 NYC Daily Student Attendance data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Education/2018-2019-Daily-Attendance/x3bb-kg5j/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_daily_attendance_2018_2019(limit = 2)
  small_sample

  nyc_daily_attendance_2018_2019(filters = list(school_dbn = "01M015"))
}
```

nyc_detention_admissions

NYC Detention Admissions by Community District

Description

Downloads Detention Admissions by Community District data from NYC Open Data.

Usage

```
nyc_detention_admissions(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset reports annual counts of detention admissions across NYC community districts, disaggregated by borough and calendar year. Provided by the NYC Department of Correction and Department of Youth and Community Development.

Value

A tibble containing NYC Detention Admissions by Community District data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/2hrw-qfsu>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_detention_admissions(limit = 2)
  small_sample

  nyc_detention_admissions(filters = list(borough = "Bronx"))
}
```

nyc_dhs_daily_report *NYC Department of Homeless Services (DHS) Daily Report*

Description

Department of Homeless Services (DHS) Daily Report

Usage

```
nyc_dhs_daily_report(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset includes the daily number of families and individuals residing in the Department of Homeless Services (DHS) shelter system and the daily number of families applying to the DHS shelter system.

Value

A tibble containing Department of Homeless Services (DHS) Daily Report data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/DHS-Daily-Report/k46n-sa2m/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_dhs_daily_report(limit = 2)
  small_sample

  nyc_dhs_daily_report(filters = list(total_adults_in_shelter = 55694))
}
```

nyc_dob_job_applications

NYC DOB Job Application Filings

Description

Downloads DOB Job Application Filings data from NYC Open Data.

Usage

```
nyc_dob_job_applications(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset includes job application filings submitted to the NYC Department of Buildings (DOB). Each record represents a construction or alteration project application, including location, work type, and approval status.

Value

A tibble containing DOB Job Application Filings data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/ic3t-wcy2>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_dob_job_applications(limit = 2)
  small_sample

  nyc_dob_job_applications(filters = list(borough = "BROOKLYN"))
}
```

nyc_dob_permit_issuance

DOB Permit Issuance

Description

Downloads DOB Permit Issuance data from NYC Open Data.

Usage

```
nyc_dob_permit_issuance(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The Department of Buildings (DOB) issues permits for construction and demolition activities in the City of New York. The construction industry must submit an application to DOB with details of the construction job they would like to complete. The primary types of application, aka job type, are: New Building, Demolition, and Alterations Type 1, 2, and 3. Each job type can have multiple work types, such as general construction, boiler, elevator, and plumbing. Each work type will receive a separate permit. (See the DOB Job Application Filings dataset for information about each job application.) Each row/record in this dataset represents the life cycle of one permit for one work type. The dataset is updated daily with new records, and each existing record will be updated as the permit application moves through the approval process to reflect the latest status of the application.

Value

A tibble containing DOB Permit Issuance data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Housing-Development/DOB-Permit-Issuance/ipu4-2q9a/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_dob_permit_issuance(limit = 2)
  small_sample

  nyc_dob_permit_issuance(filters = list(borough = "BROOKLYN"))
}
```

nyc_domestic_violence_annual_report

Annual Report on Domestic Violence Initiatives, Indicators and Factors

Description

Downloads Annual Report on Domestic Violence Initiatives, Indicators and Factors data from NYC Open Data.

Usage

```
nyc_domestic_violence_annual_report(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The information in the report is required under Local Law 38 of 2019.

Value

A tibble containing Annual Report on Domestic Violence Initiatives, Indicators and Factors data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/Annual-Report-on-Domestic-Violence-Initiatives-Ind/7t9i-jsfp/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_domestic_violence_annual_report(limit = 2)
  small_sample

  nyc_domestic_violence_annual_report(filters = list(category = "FJC_Client_Visits"))
}
```

nyc_dop_Juvenile_cases

NYC DOP Juvenile Case Count By Type

Description

Downloads DOP Juvenile Case Count By Type data from NYC Open Data.

Usage

```
nyc_dop_Juvenile_cases(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset tracks the number of juvenile cases handled by the NYC Department of Probation (DOP), broken down by case type and region. It provides insight into trends in youth justice and probation supervision citywide.

Value

A tibble containing DOP Juvenile Case Count By Type data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/c49b-3kmd>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.
```

```
if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_dop_Juvenile_cases(limit = 2)
  small_sample

  nyc_dop_Juvenile_cases(filters = list(borough = "Citywide"))
}
```

nyc_dop_juvenile_rearrest_rate

NYC DOP Juvenile Rearrest Rate (Monthly Average)

Description

Downloads DOP Juvenile Rearrest Rate (Monthly Average) data from NYC Open Data.

Usage

```
nyc_dop_juvenile_rearrest_rate(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset provides the average monthly rate of juvenile rearrests reported by the NYC Department of Probation (DOP). Data includes region, year, and monthly averages, allowing for trend analysis across boroughs.

Value

A tibble containing NYC DOP Juvenile Rearrest Rate (Monthly Average) data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/c87b-2j3i>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_dop_juvenile_rearrest_rate(limit = 2)
  small_sample

  nyc_dop_juvenile_rearrest_rate(filters = list(borough = "Citywide"))
}
```

nyc_film_permits	<i>Film Permits</i>
------------------	---------------------

Description

Downloads Film Permits data from NYC Open Data.

Usage

```
nyc_film_permits(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Permits are generally required when asserting the exclusive use of city property, like a sidewalk, a street, or a park. See <http://www1.nyc.gov/site/mome/permits/when-permit-required.page>

Value

A tibble containing Film Permits data.

Source

NYC Open Data: <https://data.cityofnewyork.us/City-Government/Film-Permits/tg4x-b46p/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_film_permits(limit = 2)
  small_sample

  nyc_film_permits(filters = list(eventtype = "Shooting Permit"))
}
```

nyc_for_hire_vehicles *NYC For-Hire Vehicles (FHV) - Active*

Description

Downloads For-Hire Vehicles (FHV) - Active data from NYC Open Data.

Usage

```
nyc_for_hire_vehicles(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset includes all active For-Hire Vehicle (FHV) licenses in NYC, such as taxis, limousines, and app-based services (e.g., Uber, Lyft). Maintained by the NYC Taxi and Limousine Commission (TLC).

Value

A tibble containing For-Hire Vehicles (FHV) - Active data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/8wbx-tschr>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_for_hire_vehicles(limit = 2)
  small_sample

  nyc_for_hire_vehicles(filters = list(active = "YES"))
}
```

nyc_homeless_drop_in_centers

NYC Homeless Drop- In Centers

Description

Directory Of Homeless Drop- In Centers

Usage

```
nyc_homeless_drop_in_centers(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

List of centers where homeless people are provided with hot meals, showers, medical help and a place to sleep

Value

A tibble containing Directory Of Homeless Drop- In Centers data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/Directory-Of-Homeless-Drop-In-Centers/bmxf-3rd4/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_homeless_drop_in_centers(limit = 2)
  small_sample

  nyc_homeless_drop_in_centers(filters = list(borough = "Bronx"))
}
```

nyc_homeless_population_by_year

NYC Homeless Population By Year

Description

Directory Of Homeless Population By Year

Usage

```
nyc_homeless_population_by_year(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Table of homeless population by Year (for years 2009 through 2012)

Value

A tibble containing Directory Of Homeless Population By Year data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/Directory-Of-Homeless-Population-By-Year/5t4n-d72c/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_homeless_population_by_year(limit = 2)
  small_sample

  nyc_homeless_population_by_year(filters = list(area = "Subways"))
}
```

```
nyc_medallion_drivers_active
      Medallion Drivers - Active
```

Description

Downloads Medallion Drivers - Active data from NYC Open Data.

Usage

```
nyc_medallion_drivers_active(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This is a list of drivers with a current TLC Driver License, which authorizes drivers to operate NYC TLC licensed yellow and green taxicabs and for-hire vehicles (FHV's). This list is accurate as of the date and time shown in the Last Date Updated and Last Time Updated fields.

Value

A tibble containing Medallion Drivers - Active data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Transportation/Medallion-Drivers-Active/jb3k-j3gp/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_medallion_drivers_active(limit = 2)
  small_sample

  nyc_medallion_drivers_active(filters = list(type = "MEDALLION TAXI DRIVER"))
}
```

```
nyc_medallion_drivers_authorized
      Medallion Vehicles - Authorized
```

Description

Downloads Medallion Vehicles - Authorized data from NYC Open Data.

Usage

```
nyc_medallion_drivers_authorized(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset, which includes all TLC licensed medallion vehicles which are in good standing and able to drive, is updated every day in the evening between 4–7pm. Please check the 'Last Update Date' field to make sure the list has updated successfully. 'Last Update Date' should show either today or yesterday's date, depending on the time of day.

Value

A tibble containing Medallion Vehicles - Authorized data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Transportation/Medallion-Vehicles-Authorized/rhe8-mgbb/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_medallion_drivers_authorized(limit = 2)
  small_sample

  nyc_medallion_drivers_authorized(filters = list(current_status = "CUR"))
}
```

nyc_motor_vehicle_collisions_crashes

Motor Vehicle Collisions - Crashes

Description

Downloads Motor Vehicle Collisions - Crashes data from NYC Open Data.

Usage

```
nyc_motor_vehicle_collisions_crashes(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The Motor Vehicle Collisions crash table contains details on the crash event. Each row represents a crash event. The Motor Vehicle Collisions data tables contain information from all police reported motor vehicle collisions in NYC. The police report (MV104-AN) is required to be filled out for collisions where someone is injured or killed, or where there is at least \$1000 worth of damage (https://www.nhtsa.gov/sites/nhtsa.dot.gov/files/documents/ny_overlay_mv-104an_rev05_2004.pdf).

Value

A tibble containing Motor Vehicle Collisions - Crashes data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Public-Safety/Motor-Vehicle-Collisions-Crashes/h9gi-nx95/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_motor_vehicle_collisions_crashes(limit = 2)
  small_sample

  nyc_motor_vehicle_collisions_crashes(filters = list(borough = "BROOKLYN"))
}
```

nyc_museum_locations	<i>MUSEUM</i>
----------------------	---------------

Description

Downloads Locations of New York City Museums from NYC Open Data.

Usage

```
nyc_museum_locations(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Locations of New York City Museums

Value

A tibble containing Locations of New York City Museums data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Recreation/MUSEUM/fn6f-htvy/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_museum_locations(limit = 2)
  small_sample

  nyc_museum_locations(filters = list(city = "New York"))
}
```

nyc_nypd_hate_crimes	<i>NYC NYPD Hate Crimes</i>
----------------------	-----------------------------

Description

Downloads NYPD Hate Crimes data from NYC Open Data.

Usage

```
nyc_nypd_hate_crimes(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset contains records of hate crime incidents reported by the NYPD. Each entry includes the bias motivation, offense category, and borough, providing insight into hate crime trends across New York City.

Value

A tibble containing NYC NYPD Hate Crimes data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/bqiq-cu78>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_nypd_hate_crimes(limit = 2)
  small_sample

  nyc_nypd_hate_crimes(filters = list(county = "KINGS"))
}
```

nyc_open_parking_camera_violations

Open Parking and Camera Violations

Description

Downloads Open Parking and Camera Violations data from NYC Open Data.

Usage

```
nyc_open_parking_camera_violations(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The Open Parking and Camera Violations dataset was initially loaded with all violations contained in the mainframe database as of May 2016.

Value

A tibble containing Open Parking and Camera Violations data.

Source

NYC Open Data: <https://data.cityofnewyork.us/City-Government/Open-Parking-and-Camera-Violations/nc67-uf89/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_open_parking_camera_violations(limit = 2)
  small_sample

  nyc_open_parking_camera_violations(filters = list(state = "NJ"))
}
```

nyc_period_attendance_reporting

Statistical Summary Period Attendance Reporting (PAR)

Description

Downloads Statistical Summary Period Attendance Reporting (PAR) from NYC Open Data.

Usage

```
nyc_period_attendance_reporting(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Statistical report on attendance by borough, grade. Alternate views of same data by grade level and enrollment (register). All students including YABC, adults, LYFE babies and charters, home instruction, home/hospital, CBO UPK.

Value

A tibble containing Period Attendance data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Education/Statistical-Summary-Period-Attendance-Reporting-PA/hrs-u-3w2q/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_period_attendance_reporting(limit = 2)
  small_sample

  nyc_period_attendance_reporting(filters = list(boro = "X"))
}
```

nyc_permit_events_historic

NYC Permitted Event Information - Historical

Description

Downloads historical permitted event data from NYC Open Data.

Usage

```
nyc_permit_events_historic(limit = 10000, filters = list(), timeout_sec = 60)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 60).

Details

This dataset includes historical information about events permitted through the Office of Citywide Event Coordination and Management (CECM), including parades, festivals, street fairs, and other public gatherings.

Value

A tibble containing NYC Permitted Event Information - Historical data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/bkfu-528j>>

Examples

```
if (curl::has_internet()) {
  small_sample <- try(
    nyc_permit_events_historic(limit = 2, timeout_sec = 10),
    silent = TRUE
  )
  if (!inherits(small_sample, "try-error")) print(small_sample)

  filtered <- try(
    nyc_permit_events_historic(
      limit = 2,
      filters = list(event_type = "Construction"),
      timeout_sec = 10
    ),
    silent = TRUE
  )
  if (!inherits(filtered, "try-error")) print(filtered)
}
```

nyc_pets_in_shelters	<i>NYC Pets in Shelter Report</i>
----------------------	-----------------------------------

Description

Local Law 97 of 2021 - Pets in Shelter Report from NYC Open Data.

Usage

```
nyc_pets_in_shelters(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This quarterly report provides survey response data about the types of pets whose owners enter homeless shelters. Data is aggregated at the quarterly level (ie: 2024 Q3). The unit of analysis is a fiscal year quarter: Quarter 1 (Q1): July - September; Quarter 2 (Q2): October - December; Quarter 3 (Q3): January - March; Quarter 4 (Q4): April - June.

Value

A tibble containing Local Law 97 of 2021 - Pets in Shelter Report data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/Local-Law-97-of-2021-Pets-in-Shelter-Report/5nux-zfmw/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_pets_in_shelters(limit = 2)
  small_sample

  nyc_pets_in_shelters(filters = list(date_quarter = "Qtr 1"))
}
```

nyc_restaurant_inspection_results

DOHMH New York City Restaurant Inspection Results

Description

Downloads DOHMH New York City Restaurant Inspection Results from NYC Open Data.

Usage

```
nyc_restaurant_inspection_results(
  limit = 10000,
  filters = list(),
  timeout_sec = 30
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

The dataset contains every sustained or not yet adjudicated violation citation from every full or special program inspection conducted up to three years prior to the most recent inspection for restaurants and college cafeterias in an active status on the RECORD DATE (date of the data pull). When an inspection results in more than one violation, values for associated fields are repeated for each additional violation record. Establishments are uniquely identified by their CAMIS (record ID)

number. Keep in mind that thousands of restaurants start business and go out of business every year; only restaurants in an active status are included in the dataset. Records are also included for each restaurant that has applied for a permit but has not yet been inspected and for inspections resulting in no violations. Establishments with inspection date of 1/1/1900 are new establishments that have not yet received an inspection. Restaurants that received no violations are represented by a single row and coded as having no violations using the ACTION field. Because this dataset is compiled from several large administrative data systems, it contains some illogical values that could be a result of data entry or transfer errors. Data may also be missing. This dataset and the information on the Health Department's Restaurant Grading website come from the same data source. The Health Department's Restaurant Grading website is here: <http://www1.nyc.gov/site/doh/services/restaurant-grades.page> See the data dictionary file in the Attachments section of the OpenData website for a summary of data fields and allowable values.

Value

A tibble containing DOHMH New York City Restaurant Inspection Results data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Health/DOHMH-New-York-City-Restaurant-Inspection-Results/43nn-pn8j/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_restaurant_inspection_results(limit = 2)
  small_sample

  nyc_restaurant_inspection_results(filters = list(boro = "Queens"))
}
```

nyc_runaway_and_homeless_youth_daily_census

NYC Runaway and Homeless Youth (RHY) Daily Census

Description

Runaway and Homeless Youth (RHY) Daily Census

Usage

```
nyc_runaway_and_homeless_youth_daily_census(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This data tracks the number of beds available for runaway and homeless youth and young adults as well as the number and percent vacant. Data include Crisis Shelters, Crisis Shelters HYA (Homeless Young Adults), Transitional Independent Living, and Transitional Independent Living HYA.

Value

A tibble containing Runaway and Homeless Youth (RHY) Daily Census data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Social-Services/Runaway-and-Homeless-Youth-RHY-Daily-Census/5rw7-99k7/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_runaway_and_homeless_youth_daily_census(limit = 2)  
  small_sample  
  
  nyc_runaway_and_homeless_youth_daily_census(filters = list(program_type = "Crisis Shelters"))  
}
```

nyc_school_discharge *NYC School Discharge Reporting (Local Law 42)*

Description

Downloads School Discharge Reporting (Local Law 42) data from NYC Open Data.

Usage

```
nyc_school_discharge(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset reports student discharges from NYC public schools, as required under Local Law 42. It includes counts and percentages of students discharged by category, such as transfer, dropout, or other reasons. Data are aggregated by school and year, supporting analysis of student outcomes across the city.

Value

A tibble containing School Discharge Reporting (Local Law 42) data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/a2gn-nyzs>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_school_discharge(limit = 2)
  small_sample

  nyc_school_discharge(filters = list(school_level = "High School"))
}
```

nyc_school_discharge_report_2013_2015
2013-2015 School Closure Discharge Reporting

Description

Downloads 2013-2015 School Closure Discharge Reporting data from NYC Open Data.

Usage

```
nyc_school_discharge_report_2013_2015(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This report provides data regarding students enrolled in the closed schools according to the guidelines set by Local Law 43 of 2011.

Value

A tibble containing School Closure Discharge data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Education/2013-2015-School-Closure-Discharge-Reporting/r773-ytwa/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_school_discharge_report_2013_2015(limit = 2)  
  small_sample  
  
  nyc_school_discharge_report_2013_2015(filters = list(geography = "Citywide"))  
}
```

`nyc_school_discharge_report_2015_2018`*2015-2018 School Closure Discharge Reporting*

Description

Downloads 2015-2018 School Closure Discharge Reporting data from NYC Open Data.

Usage

```
nyc_school_discharge_report_2015_2018(limit = 10000, filters = list())
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.

Details

This dataset provides data regarding students enrolled in the closed schools according to the guidelines set by Local Law 43 of 2011.

Value

A tibble containing School Closure Discharge Report data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Education/2015-2018-School-Closure-Discharge-Reporting/abh8-frsx/about_data>

Examples

```
# Quick example (fetch 2 rows)
small_sample <- nyc_school_discharge_report_2015_2018(limit = 2)
small_sample
```

```
nyc_school_discharge_report_2015_2018(filters = list(geography = "Borough"))
```

`nyc_street_hail_livery_active`*Street Hail Livery (SHL) Drivers - Active*

Description

Downloads Street Hail Livery (SHL) Drivers - Active data from NYC Open Data.

Usage

```
nyc_street_hail_livery_active(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.
<code>timeout_sec</code>	Request timeout in seconds (default = 30).

Details

NYC TLC licensed drivers that are currently active, in good standing and authorized to operate Street Hail Livery (SHL) vehicles. This list is accurate to the date and time represented in the Last Date Updated and Last Time Updated fields.

Value

A tibble containing Street Hail Livery (SHL) Drivers - Active data.

Source

NYC Open Data: <https://data.cityofnewyork.us/Transportation/Street-Hail-Livery-SHL-Drivers-Active/5tub-eh45/about_data>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_street_hail_livery_active(limit = 2)  
  small_sample  
  
  nyc_street_hail_livery_active(filters = list(status_description = "SHL UNRESTRICTED"))
```

```
}
```

```
nyc_tlc_new_driver_app_status
```

```
NYC TLC New Driver Application Status
```

Description

Downloads TLC New Driver Application Status data from NYC Open Data.

Usage

```
nyc_tlc_new_driver_app_status(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.
<code>timeout_sec</code>	Request timeout in seconds (default = 30).

Details

This dataset provides the application status for individuals applying for a New York City Taxi and Limousine Commission (TLC) driver's license. It includes details such as application date, drug test status, defensive driving completion, and final approval outcome.

Value

A tibble containing TLC New Driver Application Status data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/dpec-ucu7>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_tlc_new_driver_app_status(limit = 2)  
  small_sample
```

```
nyc_tlc_new_driver_app_status(filters = list(drug_test = "NEEDED"))
}
```

nyc_tree_census_2015 *NYC 2015 Street Tree Census - Tree Data*

Description

Downloads 2015 Street Tree Census - Tree Data from NYC Open Data.

Usage

```
nyc_tree_census_2015(limit = 10000, filters = list(), timeout_sec = 30)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

This dataset contains records from the 2015 Street Tree Census, including species, health, and location information for each recorded tree. Data collected by NYC Parks and volunteers.

Value

A tibble containing 2015 Street Tree Census - Tree Data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/uvpi-gqnh>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks
# do not fail when the network is unavailable or slow.

if (curl::has_internet()) {
  # Quick example (fetch 2 rows)
  small_sample <- nyc_tree_census_2015(limit = 2)
  head(small_sample)

  nyc_tree_census_2015(filters = list(curbs_loc = "OnCurb"))
}
```

`nyc_urban_park_animal_condition`*NYC Urban Park Ranger Animal Condition Response*

Description

Downloads Urban Park Ranger Animal Condition Response data from NYC Open Data.

Usage

```
nyc_urban_park_animal_condition(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

<code>limit</code>	Number of rows to retrieve (default = 10,000).
<code>filters</code>	Optional list of field-value pairs to filter results.
<code>timeout_sec</code>	Request timeout in seconds (default = 30).

Details

This dataset records responses by NYC Urban Park Rangers to animal-related incidents across the five boroughs. It includes information on species, condition, location, and outcome, helping to monitor urban wildlife trends and public safety interactions.

Value

A tibble containing Urban Park Ranger Animal Condition Response data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/fuhs-xmg2>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_urban_park_animal_condition(limit = 2)  
  small_sample  
  
  nyc_urban_park_animal_condition(filters = list(age = "Infant"))  
}
```

nyc_violent_disruptive_school_incidents
NYC Violent and Disruptive Incidents

Description

Downloads Violent and Disruptive Incidents data from NYC Open Data.

Usage

```
nyc_violent_disruptive_school_incidents(  
  limit = 10000,  
  filters = list(),  
  timeout_sec = 30  
)
```

Arguments

limit	Number of rows to retrieve (default = 10,000).
filters	Optional list of field-value pairs to filter results.
timeout_sec	Request timeout in seconds (default = 30).

Details

Incident counts and rates reported by NYC schools, broken out by incident category, school, and school year. Useful for safety trend analyses and comparisons across school types.

Value

A tibble containing Violent and Disruptive Incidents data.

Source

NYC Open Data: <<https://data.cityofnewyork.us/resource/fpci-ws56>>

Examples

```
# Examples that hit the live NYC Open Data API are wrapped so CRAN checks  
# do not fail when the network is unavailable or slow.  
  
if (curl::has_internet()) {  
  # Quick example (fetch 2 rows)  
  small_sample <- nyc_violent_disruptive_school_incidents(limit = 2)  
  small_sample
```



```
nyc_violent_disruptive_school_incidents(filters = list(school_type = "Public"))  
}
```

Index

nyc_311, [3](#)
nyc_311_2010_2019, [4](#)
nyc_any_dataset, [5](#)
nyc_borough_community_report, [5](#)
nyc_cause_of_death, [6](#)
nyc_city_record, [7](#)
nyc_civil_service_list, [8](#)
nyc_daily_attendance_2018_2019, [9](#)
nyc_detention_admissions, [10](#)
nyc_dhs_daily_report, [11](#)
nyc_dob_job_applications, [12](#)
nyc_dob_permit_issuance, [13](#)
nyc_domestic_violence_annual_report,
[14](#)
nyc_dop_juvenile_cases, [15](#)
nyc_dop_juvenile_rearrest_rate, [16](#)
nyc_film_permits, [17](#)
nyc_for_hire_vehicles, [18](#)
nyc_homeless_drop_in_centers, [19](#)
nyc_homeless_population_by_year, [20](#)
nyc_medallion_drivers_active, [21](#)
nyc_medallion_drivers_authorized, [22](#)
nyc_motor_vehicle_collisions_crashes,
[23](#)
nyc_museum_locations, [24](#)
nyc_nypd_hate_crimes, [25](#)
nyc_open_parking_camera_violations, [26](#)
nyc_period_attendance_reporting, [27](#)
nyc_permit_events_historic, [28](#)
nyc_pets_in_shelters, [29](#)
nyc_restaurant_inspection_results, [30](#)
nyc_runaway_and_homeless_youth_daily_census,
[31](#)
nyc_school_discharge, [33](#)
nyc_school_discharge_report_2013_2015,
[34](#)
nyc_school_discharge_report_2015_2018,
[35](#)
nyc_street_hail_livery_active, [36](#)
nyc_tlc_new_driver_app_status, [37](#)
nyc_tree_census_2015, [38](#)
nyc_urban_park_animal_condition, [39](#)
nyc_violent_disruptive_school_incidents,
[40](#)