

Package ‘officer’

May 21, 2025

Type Package

Title Manipulation of Microsoft Word and PowerPoint Documents

Version 0.6.9

Description Access and manipulate 'Microsoft Word', 'RTF' and 'Microsoft PowerPoint' documents from R. The package focuses on tabular and graphical reporting from R; it also provides two functions that let users get document content into data objects. A set of functions lets add and remove images, tables and paragraphs of text in new or existing documents. The package does not require any installation of Microsoft products to be able to write Microsoft files.

License MIT + file LICENSE

URL <https://ardata-fr.github.io/officeverse/>,
<https://davidgohel.github.io/officer/>

BugReports <https://github.com/davidgohel/officer/issues>

Imports cli, graphics, grDevices, openssl, R6, ragg, stats, utils,
uuid, xml2 (>= 1.1.0), zip (>= 2.1.0)

Suggests devEMF, doconv (>= 0.3.0), gdtools, ggplot2, knitr, magick,
rmarkdown, rsvg, testthat, withr

Encoding UTF-8

RoxygenNote 7.3.2

Collate 'core_properties.R' 'custom_properties.R' 'defunct.R'
'dev-utils.R' 'docx_add.R' 'docx_comments.R' 'docx_cursor.R'
'docx_part.R' 'docx_replace.R' 'docx_section.R'
'docx_settings.R' 'empty_content.R' 'formatting_properties.R'
'fortify_docx.R' 'fortify_pptx.R' 'knitr_utils.R' 'officer.R'
'ooxml.R' 'ooxml_block_objects.R' 'ooxml_run_objects.R'
'openxml_content_type.R' 'openxml_document.R' 'pack_folder.R'
'ph_location.R' 'post-proc.R' 'ppt_class_dir_collection.R'
'ppt_classes.R' 'ppt_notes.R' 'ppt_ph_dedupe_layout.R'
'ppt_ph_manipulate.R' 'ppt_ph_rename_layout.R'
'ppt_ph_with_methods.R' 'pptx_informations.R'
'pptx_layout_helper.R' 'pptx_matrix.R' 'utils.R'

'pptx_slide_manip.R' 'read_docx.R' 'read_docx_styles.R'
 'read_pptx.R' 'read_xlsx.R' 'relationship.R' 'rtf.R'
 'shape_properties.R' 'shortcuts.R' 'docx_append_context.R'
 'utils-xml.R' 'deprecated.R'

NeedsCompilation no

Author David Gohel [aut, cre],
 Stefan Moog [aut],
 Mark Heckmann [aut] (ORCID: <<https://orcid.org/0000-0002-0736-7417>>),
 ArData [cph],
 Frank Hangler [ctb] (function body_replace_all_text),
 Liz Sander [ctb] (several documentation fixes),
 Anton Victorson [ctb] (fixes xml structures),
 Jon Calder [ctb] (update vignettes),
 John Harrold [ctb] (function annotate_base),
 John Muschelli [ctb] (google doc compatibility),
 Bill Denney [ctb] (ORCID: <<https://orcid.org/0000-0002-5759-428X>>),
 function as.matrix.rpptx),
 Nikolai Beck [ctb] (set speaker notes for .pptx documents),
 Greg Leleu [ctb] (fields functionality in ppt),
 Majid Eismann [ctb],
 Hongyuan Jia [ctb] (ORCID: <<https://orcid.org/0000-0002-0075-8183>>),
 Michael Stackhouse [ctb]

Maintainer David Gohel <david.gohel@ardata.fr>

Repository CRAN

Date/Publication 2025-05-21 17:10:02 UTC

Contents

add_sheet	5
add_slide	6
annotate_base	7
as.matrix.rpptx	8
block_caption	9
block_gg	10
block_list	11
block_pour_docx	12
block_section	13
block_table	14
block_toc	15
body_add_blocks	15
body_add_break	16
body_add_caption	17
body_add_docx	18
body_add_fpar	19
body_add_gg	20
body_add_img	21

body_add_par	22
body_add_plot	23
body_add_table	24
body_add_toc	26
body_append_start_context	27
body_bookmark	28
body_comment	29
body_end_block_section	30
body_end_section_columns	31
body_end_section_columns_landscape	32
body_end_section_continuous	33
body_end_section_landscape	34
body_end_section_portrait	34
body_remove	35
body_replace_all_text	36
body_replace_gg_at_bkm	38
body_replace_text_at_bkm	40
body_set_default_section	41
change_styles	42
color_scheme	42
cursor_begin	43
docx_bookmarks	45
docx_comments	46
docx_dim	47
docx_set_character_style	48
docx_set_paragraph_style	49
docx_show_chunk	50
docx_summary	51
doc_properties	52
empty_content	52
external_img	53
fpar	54
fp_border	56
fp_cell	58
fp_par	60
fp_tab	62
fp_tabs	63
fp_text	63
ftext	66
hyperlink_ftext	67
layout_dedupe_ph_labels	68
layout_default	69
layout_properties	70
layout_rename_ph_labels	71
layout_summary	73
length.rdocx	73
length.rpptx	74
media_extract	75

move_slide	75
notes_location_label	76
notes_location_type	76
officer	77
officer-defunct	78
on_slide	79
page_mar	80
page_size	81
phs_with	81
ph_hyperlink	83
ph_location	84
ph_location_fullsize	85
ph_location_id	86
ph_location_label	87
ph_location_left	88
ph_location_right	89
ph_location_template	90
ph_location_type	91
ph_remove	93
ph_slidelink	94
ph_with	95
plot_instr	101
plot_layout_properties	102
pptx_summary	104
print.rpptx	104
print.rtf	105
prop_section	106
prop_table	108
read_docx	109
read_pptx	111
read_xlsx	112
remove_slide	112
rtf_add	113
rtf_doc	116
run_autonum	117
run_bookmark	118
run_columnbreak	119
run_comment	119
run_footnote	121
run_footnoteref	122
run_linebreak	122
run_pagebreak	123
run_reference	124
run_tab	125
run_wordtext	126
run_word_field	126
section_columns	127
set_autonum_bookmark	128

set_doc_properties	129
set_notes	130
sheet_select	131
shortcuts	132
slide_size	132
slide_summary	133
slide_visible<-	134
sp_line	135
sp_lineend	136
styles_info	137
table_colwidths	138
table_conditional_formatting	139
table_layout	140
table_stylenames	140
table_width	141
unordered_list	142
Index	143

add_sheet	<i>Add a sheet</i>
-----------	--------------------

Description

Add a sheet into an xlsx worksheet.

Usage

```
add_sheet(x, label)
```

Arguments

x	rxlsx object
label	sheet label

Examples

```
my_ws <- read_xlsx()  
my_pres <- add_sheet(my_ws, label = "new sheet")
```

add_slide

Add a slide

Description

Add a slide into a pptx presentation.

Usage

```
add_slide(x, layout = NULL, master = NULL, ..., .dots = NULL)
```

Arguments

x	an rpptx object.
layout	slide layout name to use. Can be omitted if a default layout is set via layout_default() .
master	master layout name where layout is located. Only required in case of several masters if layout is not unique.
...	Key-value pairs of the form "short form location" = object passed to phs_with . See section "Short forms" in phs_with for details, available short forms and examples.
.dots	List of key-value pairs of the form list("short form location" = object). Alternative to ... See phs_with for details.

See Also

[print.rpptx\(\)](#), [read_pptx\(\)](#), [layout_summary\(\)](#), [plot_layout_properties\(\)](#), [ph_with\(\)](#), [phs_with\(\)](#), [layout_default\(\)](#)

Other functions to manipulate slides: [move_slide\(\)](#), [on_slide\(\)](#), [remove_slide\(\)](#), [set_notes\(\)](#)

Examples

```
x <- read_pptx()

layout_summary(x) # available layouts

x <- add_slide(x, layout = "Two Content")

x <- layout_default(x, "Title Slide") # set default layout for `add_slide()`
x <- add_slide(x) # uses default layout

# use `...` to fill placeholders when adding slide
x <- add_slide(x,
  layout = "Two Content", `Title 1` = "A title",
  dt = "Jan. 26, 2025", `body[2]` = "Body 2",
  left = "Left side", `6` = "Footer"
)
```

annotate_base	<i>Placeholder parameters annotation</i>
---------------	--

Description

generates a slide from each layout in the base document to identify the placeholder indexes, types, names, master names and layout names.

This is to be used when need to know what parameters should be used with `ph_location*` calls. The parameters are printed in their corresponding shapes.

Note that if there are duplicated `ph_label`, you should not use `ph_location_label()`. Hint: You can dedupe labels using [layout_dedupe_ph_labels\(\)](#).

Usage

```
annotate_base(path = NULL, output_file = "annotated_layout.pptx")
```

Arguments

<code>path</code>	path to the pptx file to use as base document or NULL to use the officer default
<code>output_file</code>	filename to store the annotated powerpoint file or NULL to suppress generation

Value

rpptx object of the annotated PowerPoint file

See Also

Other functions for reading presentation information: [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
# To generate an anotation of the default base document with officer:
annotate_base(output_file = tempfile(fileext = ".pptx"))

# To generate an annotation of the base document 'mydoc.pptx' and place the
# annotated output in 'mydoc_annotate.pptx'
# annotate_base(path = 'mydoc.pptx', output_file='mydoc_annotate.pptx')
```

as.matrix.rpptx	<i>PowerPoint table to matrix</i>
-----------------	-----------------------------------

Description

Convert the data in an a 'PowerPoint' table to a matrix or all data to a list of matrices.

Usage

```
## S3 method for class 'rpptx'
as.matrix(
  x,
  ...,
  slide_id = NA_integer_,
  id = NA_character_,
  span = c(NA_character_, "fill")
)
```

Arguments

x	The rpptx object to convert (as created by read_pptx())
...	Ignored
slide_id	The slide number to load from (NA indicates first slide with a table, NULL indicates all slides and all tables)
id	The table ID to load from (ignored if is.null(slide_id), NA indicates to load the first table from the slide_id)
span	How should col_span/row_span values be handled? NA means to leave the value as NA, and "fill" means to fill matrix cells with the value.

Value

A matrix with the data, or if slide_id=NULL, a list of matrices

Examples

```
library(officer)
pptx_file <- system.file(package="officer", "doc_examples", "example.pptx")
z <- read_pptx(pptx_file)
as.matrix(z, slide_id = NULL)
```

block_caption	<i>Caption block</i>
---------------	----------------------

Description

Create a representation of a caption that can be used for cross reference.

Usage

```
block_caption(label, style = NULL, autonum = NULL)
```

Arguments

label	a scalar character representing label to display
style	paragraph style name
autonum	an object generated with function run_autonum

See Also

Other block functions for reporting: [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
library(officer)

run_num <- run_autonum(seq_id = "tab", pre_label = "tab. ",
  bkm = "mtcars_table")
caption <- block_caption("mtcars table",
  style = "Normal",
  autonum = run_num
)

doc_1 <- read_docx()
doc_1 <- body_add(doc_1, "A title", style = "heading 1")
doc_1 <- body_add(doc_1, "Hello world!", style = "Normal")
doc_1 <- body_add(doc_1, caption)
doc_1 <- body_add(doc_1, mtcars, style = "table_template")

print(doc_1, target = tempfile(fileext = ".docx"))
```

block_gg	<i>'ggplot' block</i>
----------	-----------------------

Description

A simple wrapper to add a 'ggplot' object as a png in a document. It produces an object of class 'block_gg' with a corresponding method [to_wml\(\)](#) that can be used to convert the object to a WordML string.

Usage

```
block_gg(
  value,
  fp_p = fp_par(),
  width = 6,
  height = 5,
  res = 300,
  scale = 1,
  unit = "in"
)
```

Arguments

value	'ggplot' object
fp_p	paragraph formatting properties, see fp_par()
width, height	image size in units expressed by the unit argument. Defaults to "in"ches.
res	resolution of the png image in ppi
scale	Multiplicative scaling factor, same as in ggsave
unit	One of the following units in which the width and height arguments are expressed: "in", "cm" or "mm".

See Also

Other block functions for reporting: [block_caption\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
library(officer)
if (require("ggplot2")) {
  set.seed(2)
  doc <- read_docx()

  z <- body_append_start_context(doc)

  for (i in seq_len(3)) {
```

```

df <- data.frame(x = runif(10), y = runif(10))
gg <- ggplot(df, aes(x = x, y = y)) + geom_point()

write_elements_to_context(
  context = z,
  block_gg(
    value = gg
  )
)
}

doc <- body_append_stop_context(z)

print(doc, target = tempfile(fileext = ".docx"))
}

```

block_list

List of blocks

Description

A list of blocks can be used to gather several blocks (paragraphs, tables, ...) into a single object. The result can be added into a Word document or a PowerPoint presentation.

Usage

```
block_list(...)
```

Arguments

... a list of blocks. When output is only for Word, objects of class `external_img()` can also be used in fpar construction to mix text and images in a single paragraph. Supported objects are: `block_caption()`, `block_pour_docx()`, `block_section()`, `block_table()`, `block_toc()`, `fpar()`, `plot_instr()`.

See Also

`ph_with()`, `body_add_blocks()`, `fpar()`

Other block functions for reporting: `block_caption()`, `block_gg()`, `block_pour_docx()`, `block_section()`, `block_table()`, `block_toc()`, `fpar()`, `plot_instr()`, `unordered_list()`

Examples

```

# block list -----

img.file <- file.path( R.home("doc"), "html", "logo.jpg" )
fpt_blue_bold <- fp_text(color = "#006699", bold = TRUE)
fpt_red_italic <- fp_text(color = "#C32900", italic = TRUE)

```

```
## This can be only be used in a MS word output as pptx does
## not support paragraphs made of text and images.
## (actually it can be used but image will not appear in the
## pptx output)
value <- block_list(
  fpar(ftext("hello world", fpt_blue_bold)),
  fpar(ftext("hello", fpt_blue_bold), " ",
    ftext("world", fpt_red_italic)),
  fpar(
    ftext("hello world", fpt_red_italic),
    external_img(
      src = img.file, height = 1.06, width = 1.39)))
value

doc <- read_docx()
doc <- body_add(doc, value)
print(doc, target = tempfile(fileext = ".docx"))

value <- block_list(
  fpar(ftext("hello world", fpt_blue_bold)),
  fpar(ftext("hello", fpt_blue_bold), " ",
    ftext("world", fpt_red_italic)),
  fpar(
    ftext("blah blah blah", fpt_red_italic)))
value

doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, value, location = ph_location_type(type = "body"))
print(doc, target = tempfile(fileext = ".pptx"))
```

block_pour_docx

External Word document placeholder

Description

Pour the content of a docx file in the resulting docx from an 'R Markdown' document.

Usage

```
block_pour_docx(file)
```

Arguments

file	external docx file path
------	-------------------------

See Also

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
library(officer)
docx <- tempfile(fileext = ".docx")
doc <- read_docx()
doc <- body_add(doc, iris[1:20,], style = "table_template")
print(doc, target = docx)

target <- tempfile(fileext = ".docx")
doc_1 <- read_docx()
doc_1 <- body_add(doc_1, block_pour_docx(docx))
print(doc_1, target = target)
```

block_section

Section for 'Word'

Description

Create a representation of a section.

A section affects preceding paragraphs or tables; i.e. a section starts at the end of the previous section (or the beginning of the document if no preceding section exists), and stops where the section is declared.

When a new landscape section is needed, it is recommended to add a block_section with type = "continuous", to add the content to be appened in the new section and finally to add a block_section with page_size = page_size(orient = "landscape").

Usage

```
block_section(property)
```

Arguments

property section properties defined with function [prop_section](#)

See Also

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
ps <- prop_section(
  page_size = page_size(orient = "landscape"),
  page_margins = page_mar(top = 2),
  type = "continuous"
)
block_section(ps)
```

block_table	<i>Table block</i>
-------------	--------------------

Description

Create a representation of a table

Usage

```
block_table(x, header = TRUE, properties = prop_table(), alignment = NULL)
```

Arguments

x	a data.frame to add as a table
header	display header if TRUE
properties	table properties, see prop_table() . Table properties are not handled identically between Word and PowerPoint output format. They are fully supported with Word but for PowerPoint (which does not handle as many things as Word for tables), only conditional formatting properties are supported.
alignment	alignment for each columns, 'l' for left, 'r' for right and 'c' for center. Default to NULL.

See Also

[prop_table\(\)](#)
Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
block_table(x = head(iris))

block_table(x = mtcars, header = TRUE,
  properties = prop_table(
    tcf = table_conditional_formatting(
      first_row = TRUE, first_column = TRUE)
  ))
```

block_toc	<i>Table of content for 'Word'</i>
-----------	------------------------------------

Description

Create a representation of a table of content for Word documents.

Usage

```
block_toc(level = 3, style = NULL, seq_id = NULL, separator = ";")
```

Arguments

- level max title level of the table
- style optional. If not NULL, its value is used as style in the document that will be used to build entries of the TOC.
- seq_id optional. If not NULL, its value is used as sequence identifier in the document that will be used to build entries of the TOC. See also [run_autonum\(\)](#) to specify a sequence identifier.
- separator optional. Some configurations need "," (i.e. from Canada) separator instead of ";"

See Also

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
block_toc(level = 2)
block_toc(style = "Table Caption")
```

body_add_blocks	<i>Add a list of blocks into a 'Word' document</i>
-----------------	--

Description

add a list of blocks produced by [block_list\(\)](#) into into an rdocx object.

Usage

```
body_add_blocks(x, blocks, pos = "after")
```

Arguments

x	an rdocx object
blocks	set of blocks to be used as footnote content returned by function block_list() .
pos	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

Other functions for adding content: [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
library(officer)

img.file <- file.path(R.home("doc"), "html", "logo.jpg")

bl <- block_list(
  fpar(ftext("hello", shortcuts$fp_bold(color = "red"))),
  fpar(
    ftext("hello world", shortcuts$fp_bold()),
    external_img(src = img.file, height = 1.06, width = 1.39),
    fp_p = fp_par(text.align = "center")
  )
)

doc_1 <- read_docx()
doc_1 <- body_add_blocks(doc_1, blocks = bl)
print(doc_1, target = tempfile(fileext = ".docx"))
```

body_add_break	<i>Add a page break in a 'Word' document</i>
----------------	--

Description

add a page break into an rdocx object

Usage

```
body_add_break(x, pos = "after")
```

Arguments

x	an rdocx object
pos	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()
doc <- body_add_break(doc)
print(doc, target = tempfile(fileext = ".docx"))
```

body_add_caption	<i>Add Word caption in a 'Word' document</i>
------------------	--

Description

Add a Word caption into an rdocx object.

Usage

```
body_add_caption(x, value, pos = "after")
```

Arguments

x	an rdocx object
value	an object returned by block_caption()
pos	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()

if (capabilities(what = "png")) {
  doc <- body_add_plot(doc,
    value = plot_instr(
      code = {
        barplot(1:5, col = 2:6)
      }
    ),
    style = "centered"
  )
}
```

```

}
run_num <- run_autonum(
  seq_id = "fig", pre_label = "Figure ",
  bkm = "barplot"
)
caption <- block_caption("a barplot",
  style = "Normal",
  autonum = run_num
)
doc <- body_add_caption(doc, caption)
print(doc, target = tempfile(fileext = ".docx"))

```

body_add_docx

Add an external docx in a 'Word' document

Description

Add content of a docx into an rdocx object.

The function is using a 'Microsoft Word' feature: when the document will be edited, the content of the file will be inserted in the main document.

This feature is unlikely to work as expected if the resulting document is edited by another software.

The file is added when the method `print()` that produces the final Word file is called, so don't remove file defined with `src` before.

Usage

```
body_add_docx(x, src, pos = "after")
```

Arguments

<code>x</code>	an rdocx object
<code>src</code>	docx filename, the path of the file must not contain any '&' and the basename must not contain any space.
<code>pos</code>	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```

file1 <- tempfile(fileext = ".docx")
file2 <- tempfile(fileext = ".docx")
file3 <- tempfile(fileext = ".docx")
x <- read_docx()
x <- body_add_par(x, "hello world 1", style = "Normal")
print(x, target = file1)

x <- read_docx()
x <- body_add_par(x, "hello world 2", style = "Normal")
print(x, target = file2)

x <- read_docx(path = file1)
x <- body_add_break(x)
x <- body_add_docx(x, src = file2)
print(x, target = file3)

```

body_add_fpar	<i>Add fpar in a 'Word' document</i>
---------------	--------------------------------------

Description

Add an [fpar\(\)](#) (a formatted paragraph) into an rdocx object.

Usage

```
body_add_fpar(x, value, style = NULL, pos = "after")
```

Arguments

x	a docx device
value	a character
style	paragraph style. If NULL, paragraph settings from fpar will be used. If not NULL, it must be a paragraph style name (located in the template provided as <code>read_docx(path = ...)</code>); in that case, paragraph settings from fpar will be ignored.
pos	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

[fpar\(\)](#)

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
bold_face <- shortcuts$fp_bold(font.size = 30)
bold_redface <- update(bold_face, color = "red")
fpar_ <- fpar(
  ftext("Hello ", prop = bold_face),
  ftext("World", prop = bold_redface),
  ftext(", how are you?", prop = bold_face)
)
doc <- read_docx()
doc <- body_add_fpar(doc, fpar_)

print(doc, target = tempfile(fileext = ".docx"))

# a way of using fpar to center an image in a Word doc ----
rlogo <- file.path(R.home("doc"), "html", "logo.jpg")
img_in_par <- fpar(
  external_img(src = rlogo, height = 1.06 / 2, width = 1.39 / 2),
  hyperlink_ftext(
    href = "https://cran.r-project.org/index.html",
    text = "cran", prop = bold_redface
  ),
  fp_p = fp_par(text.align = "center")
)

doc <- read_docx()
doc <- body_add_fpar(doc, img_in_par)
print(doc, target = tempfile(fileext = ".docx"))
```

body_add_gg

Add a 'ggplot' in a 'Word' document

Description

add a ggplot as a png image into an rdocx object.

Usage

```
body_add_gg(
  x,
  value,
  width = 6,
  height = 5,
  res = 300,
  style = "Normal",
  scale = 1,
  pos = "after",
  unit = "in",
  ...
)
```

Arguments

x	an rdocx object
value	ggplot object
width, height	plot size in units expressed by the unit argument. Defaults to a width of 6 and a height of 5 "in"ches.
res	resolution of the png image in ppi
style	paragraph style
scale	Multiplicative scaling factor, same as in ggsave
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
unit	One of the following units in which the width and height arguments are expressed: "in", "cm" or "mm".
...	Arguments to be passed to png function.

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
if (require("ggplot2")) {
  doc <- read_docx()

  gg_plot <- ggplot(data = iris) +
    geom_point(mapping = aes(Sepal.Length, Petal.Length))

  if (capabilities(what = "png")) {
    doc <- body_add_gg(doc, value = gg_plot, style = "centered")

    # Set the unit in which the width and height arguments are expressed
    doc <- body_add_gg(doc, value = gg_plot, style = "centered", unit = "cm")
  }

  print(doc, target = tempfile(fileext = ".docx"))
}
```

body_add_img

Add an image in a 'Word' document

Description

add an image into an rdocx object.

Usage

```
body_add_img(x, src, style = NULL, width, height, pos = "after", unit = "in")
```

Arguments

x	an rdocx object
src	image filename, the basename of the file must not contain any blank.
style	paragraph style
width, height	image size in units expressed by the unit argument. Defaults to "in"ches.
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
unit	One of the following units in which the width and height arguments are expressed: "in", "cm" or "mm".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()

img.file <- file.path(R.home("doc"), "html", "logo.jpg")
if (file.exists(img.file)) {
  doc <- body_add_img(x = doc, src = img.file, height = 1.06, width = 1.39)

  # Set the unit in which the width and height arguments are expressed
  doc <- body_add_img(
    x = doc, src = img.file,
    height = 2.69, width = 3.53,
    unit = "cm"
  )
}

print(doc, target = tempfile(fileext = ".docx"))
```

body_add_par

Add paragraphs of text in a 'Word' document

Description

add a paragraph of text into an rdocx object

Usage

```
body_add_par(x, value, style = NULL, pos = "after")
```

Arguments

x	a docx device
value	a character
style	paragraph style name
pos	where to add the new element relative to the cursor, one of "after", "before", "on".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()
doc <- body_add_par(doc, "A title", style = "heading 1")
doc <- body_add_par(doc, "Hello world!", style = "Normal")
doc <- body_add_par(doc, "centered text", style = "centered")

print(doc, target = tempfile(fileext = ".docx"))
```

body_add_plot	<i>Add plot in a 'Word' document</i>
---------------	--------------------------------------

Description

Add a plot as a png image into an rdocx object.

Usage

```
body_add_plot(
  x,
  value,
  width = 6,
  height = 5,
  res = 300,
  style = "Normal",
  pos = "after",
  unit = "in",
  ...
)
```

Arguments

x	an rdocx object
value	plot instructions, see plot_instr() .
width, height	plot size in units expressed by the unit argument. Defaults to a width of 6 and a height of 5 "in"ches.
res	resolution of the png image in ppi
style	paragraph style
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
unit	One of the following units in which the width and height arguments are expressed: "in", "cm" or "mm".
...	Arguments to be passed to png function.

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()

if (capabilities(what = "png")) {
  p <- plot_instr(
    code = {
      barplot(1:5, col = 2:6)
    }
  )

  doc <- body_add_plot(doc, value = p, style = "centered")

  # Set the unit in which the width and height arguments are expressed
  doc <- body_add_plot(doc, value = p, style = "centered", unit = "cm")
}

print(doc, target = tempfile(fileext = ".docx"))
```

body_add_table

Add table in a 'Word' document

Description

Add a table into an rdocx object.

Usage

```
body_add_table(
    x,
    value,
    style = NULL,
    pos = "after",
    header = TRUE,
    alignment = NULL,
    align_table = "center",
    stylenames = table_stylenames(),
    first_row = TRUE,
    first_column = FALSE,
    last_row = FALSE,
    last_column = FALSE,
    no_hband = FALSE,
    no_vband = TRUE
)
```

Arguments

x	a docx device
value	a data.frame to add as a table
style	table style
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
header	display header if TRUE
alignment	columns alignment, argument length must match with columns length, values must be "l" (left), "r" (right) or "c" (center).
align_table	table alignment within document, value must be "left", "center" or "right"
stylenames	columns styles defined by table_stylenames()
first_row	Specifies that the first column conditional formatting should be applied. Details for this and other conditional formatting options can be found at http://officeopenxml.com/WPtblLook.php
first_column	Specifies that the first column conditional formatting should be applied.
last_row	Specifies that the first column conditional formatting should be applied.
last_column	Specifies that the first column conditional formatting should be applied.
no_hband	Specifies that the first column conditional formatting should be applied.
no_vband	Specifies that the first column conditional formatting should be applied.

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_toc\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()
doc <- body_add_table(doc, iris, style = "table_template")

print(doc, target = tempfile(fileext = ".docx"))
```

body_add_toc

Add table of content in a 'Word' document

Description

Add a table of content into an rdocx object. The TOC will be generated by Word, if the document is not edited with Word (i.e. Libre Office) the TOC will not be generated.

Usage

```
body_add_toc(x, level = 3, pos = "after", style = NULL, separator = ";")
```

Arguments

x	an rdocx object
level	max title level of the table
pos	where to add the new element relative to the cursor, one of "after", "before", "on".
style	optional. style in the document that will be used to build entries of the TOC.
separator	optional. Some configurations need "," (i.e. from Canada) separator instead of ";".

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_append_start_context\(\)](#)

Examples

```
doc <- read_docx()
doc <- body_add_toc(doc)

print(doc, target = tempfile(fileext = ".docx"))
```

body_append_start_context

Fast Append context to a Word document

Description

This function is used to append content to a Word document in a fast way.

It does not use the XML tree of the document neither the cursor that is responsible for increasing the performance of Word document generation when looping over a large number of elements.

This function must be used with the write_elements_to_context() and body_append_stop_context() functions:

1. body_append_start_context() creates a context and returns a list with the context and the file connection.
2. write_elements_to_context() writes the elements to the context file connection.
3. body_append_stop_context() closes the file connection and replaces the XML in the document with the new XML.

Usage

```
body_append_start_context(x)
```

```
write_elements_to_context(context, ...)
```

```
body_append_stop_context(context)
```

Arguments

x	an rdocx object
context	the context object created by body_append_start_context().
...	elements to be written to the context. These can be paragraphs, tables, images, etc. The elements should have an associated to_wml() method that converts them to WML format.

Value

body_append_start_context() returns a list representing the context that contains:

- doc: the original document object
- file_con: the file connection to the context
- file_path: the path to the context file
- final_str: the final XML string to be appended to the document later when calling body_append_stop_context().

This object should not be modified by the user but instead passed to `write_elements_to_context()` and `body_append_stop_context()`.

`write_elements_to_context()` returns the context object.

`body_append_stop_context()` returns the rdocx object with the cursor position set to the end of the document.

See Also

Other functions for adding content: [body_add_blocks\(\)](#), [body_add_break\(\)](#), [body_add_caption\(\)](#), [body_add_docx\(\)](#), [body_add_fpar\(\)](#), [body_add_gg\(\)](#), [body_add_img\(\)](#), [body_add_par\(\)](#), [body_add_plot\(\)](#), [body_add_table\(\)](#), [body_add_toc\(\)](#)

Examples

```
library(officer)

doc <- read_docx()
doc <- body_add_par(doc, value = "blah blah blah", style = "Normal")

z <- body_append_start_context(doc)

for (i in seq_len(50)) {
  write_elements_to_context(
    context = z,
    fpar(
      "Hello World, ", i,
      fp_p = fp_par(word_style = "heading 1")),
    fpar(run_pagebreak())
  )
}
doc <- body_append_stop_context(z)

print(doc, target = tempfile(fileext = ".docx"))
```

body_bookmark

Add bookmark in a 'Word' document

Description

Add a bookmark at the cursor location. The bookmark is added on the first run of text in the current paragraph.

Usage

```
body_bookmark(x, id)
```

Arguments

x	an rdocx object
id	bookmark name

Examples

```
# cursor_bookmark ----

doc <- read_docx()
doc <- body_add_par(doc, "centered text", style = "centered")
doc <- body_bookmark(doc, "text_to_replace")
```

body_comment	<i>Add comment in a 'Word' document</i>
--------------	---

Description

Add a comment at the cursor location. The comment is added on the first run of text in the current paragraph.

Usage

```
body_comment(x, cmt = ftext(""), author = "", date = "", initials = "")
```

Arguments

x	an rdocx object
cmt	a set of blocks to be used as comment content returned by function block_list() .
author	comment author.
date	comment date
initials	comment initials

Examples

```
doc <- read_docx()
doc <- body_add_par(doc, "Paragraph")
doc <- body_comment(doc, block_list("This is a comment."))
docx_file <- print(doc, target = tempfile(fileext = ".docx"))
docx_comments(read_docx(docx_file))
```

`body_end_block_section`*Add any section*

Description

Add a section to the document. You can define any section with a [block_section](#) object. All other `body_end_section_*` are specialized, this one is highly flexible but it's up to the user to define the section properties.

Usage

```
body_end_block_section(x, value)
```

Arguments

<code>x</code>	an rdocx object
<code>value</code>	a block_section object

Illustrations

See Also

Other functions for Word sections: [body_end_section_columns\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_landscape\(\)](#), [body_end_section_portrait\(\)](#), [body_set_default_section\(\)](#)

Examples

```
library(officer)
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 20)
str1 <- paste(str1, collapse = " ")

ps <- prop_section(
  page_size = page_size(orient = "landscape"),
  page_margins = page_mar(top = 2),
  type = "continuous"
)

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")

doc_1 <- body_end_block_section(doc_1, block_section(ps))

doc_1 <- body_add_par(doc_1, value = str1, style = "centered")
```

```
print(doc_1, target = tempfile(fileext = ".docx"))
```

body_end_section_columns

Add multi columns section

Description

A section with multiple columns is added to the document.

You may prefer to use [body_end_block_section\(\)](#) that is more flexible.

Usage

```
body_end_section_columns(x, widths = c(2.5, 2.5), space = 0.25, sep = FALSE)
```

Arguments

x	an rdocx object
widths	columns widths in inches. If 3 values, 3 columns will be produced.
space	space in inches between columns.
sep	if TRUE a line is separating columns.

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_landscape\(\)](#), [body_end_section_portrait\(\)](#), [body_set_default_section\(\)](#)

Examples

```
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 5)
str1 <- paste(str1, collapse = " ")

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_end_section_columns(doc_1)
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
print(doc_1, target = tempfile(fileext = ".docx"))
```

body_end_section_columns_landscape

Add a landscape multi columns section

Description

A landscape section with multiple columns is added to the document.

Usage

```
body_end_section_columns_landscape(
  x,
  widths = c(2.5, 2.5),
  space = 0.25,
  sep = FALSE,
  w = 16838/1440,
  h = 11906/1440
)
```

Arguments

x	an rdocx object
widths	columns widths in inches. If 3 values, 3 columns will be produced.
space	space in inches between columns.
sep	if TRUE a line is separating columns.
w, h	page width, page height (in inches)

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_landscape\(\)](#), [body_end_section_portrait\(\)](#), [body_set_default_section\(\)](#)

Examples

```
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 5)
str1 <- paste(str1, collapse = " ")

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_end_section_columns_landscape(doc_1, widths = c(6, 2))
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
print(doc_1, target = tempfile(fileext = ".docx"))
```

body_end_section_continuous
Add continuous section

Description

Section break starts the new section on the same page. This type of section break is often used to change the number of columns without starting a new page.

Usage

```
body_end_section_continuous(x)
```

Arguments

x an rdocx object

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_landscape\(\)](#), [body_end_section_portrait\(\)](#), [body_set_default_section\(\)](#)

Examples

```
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 5)
str1 <- paste(str1, collapse = " ")
str2 <- "Aenean venenatis varius elit et fermentum vivamus vehicula."
str2 <- rep(str2, 5)
str2 <- paste(str2, collapse = " ")

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = "Default section", style = "heading 1")
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_add_par(doc_1, value = str2, style = "Normal")
doc_1 <- body_end_section_continuous(doc_1)

print(doc_1, target = tempfile(fileext = ".docx"))
```

body_end_section_landscape
Add landscape section

Description

A section with landscape orientation is added to the document.

Usage

```
body_end_section_landscape(x, w = 16838/1440, h = 11906/1440)
```

Arguments

x	an rdocx object
w, h	page width, page height (in inches)

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_portrait\(\)](#), [body_set_default_section\(\)](#)

Examples

```
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 5)
str1 <- paste(str1, collapse = " ")

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_end_section_landscape(doc_1)

print(doc_1, target = tempfile(fileext = ".docx"))
```

body_end_section_portrait
Add portrait section

Description

A section with portrait orientation is added to the document.

Usage

```
body_end_section_portrait(x, w = 16838/1440, h = 11906/1440)
```

Arguments

x an rdocx object
 w, h page width, page height (in inches)

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_landscape\(\)](#), [body_set_default_section\(\)](#)

Examples

```
str1 <- "Lorem ipsum dolor sit amet, consectetur adipiscing elit."
str1 <- rep(str1, 5)
str1 <- paste(str1, collapse = " ")

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
doc_1 <- body_end_section_portrait(doc_1)
doc_1 <- body_add_par(doc_1, value = str1, style = "Normal")
print(doc_1, target = tempfile(fileext = ".docx"))
```

body_remove

*Remove an element in a 'Word' document***Description**

Remove element pointed by cursor from a 'Word' document.

Usage

```
body_remove(x)
```

Arguments

x an rdocx object

Examples

```
library(officer)

str1 <- rep("Lorem ipsum dolor sit amet, consectetur adipiscing elit. ", 20)
str1 <- paste(str1, collapse = "")

str2 <- "Drop that text"

str3 <- rep("Aenean venenatis varius elit et fermentum vivamus vehicula. ", 20)
str3 <- paste(str3, collapse = "")
```

```

my_doc <- read_docx()
my_doc <- body_add_par(my_doc, value = str1, style = "Normal")
my_doc <- body_add_par(my_doc, value = str2, style = "centered")
my_doc <- body_add_par(my_doc, value = str3, style = "Normal")

new_doc_file <- print(my_doc,
  target = tempfile(fileext = ".docx")
)

my_doc <- read_docx(path = new_doc_file)
my_doc <- cursor_reach(my_doc, keyword = "that text")
my_doc <- body_remove(my_doc)

print(my_doc, target = tempfile(fileext = ".docx"))

```

body_replace_all_text *Replace text anywhere in the document*

Description

Replace text anywhere in the document, or at a cursor.

Replace all occurrences of `old_value` with `new_value`. This method uses `grepl()/gsub()` for pattern matching; you may supply arguments as required (and therefore use `regex()` features) using the optional `...` argument.

Note that by default, `grepl/gsub` will use `fixed=FALSE`, which means that `old_value` and `new_value` will be interpreted as regular expressions.

Chunking of text

Note that the behind-the-scenes representation of text in a Word document is frequently not what you might expect! Sometimes a paragraph of text is broken up (or "chunked") into several "runs," as a result of style changes, pauses in text entry, later revisions and edits, etc. If you have not styled the text, and have entered it in an "all-at-once" fashion, e.g. by pasting it or by outputting it programmatically into your Word document, then this will likely not be a problem. If you are working with a manually-edited document, however, this can lead to unexpected failures to find text.

You can use the officer function `docx_show_chunk()` to show how the paragraph of text at the current cursor has been chunked into runs, and what text is in each chunk. This can help troubleshoot unexpected failures to find text.

Usage

```

body_replace_all_text(
  x,
  old_value,
  new_value,
  only_at_cursor = FALSE,
  warn = TRUE,

```

```
    ...
)

headers_replace_all_text(
  x,
  old_value,
  new_value,
  only_at_cursor = FALSE,
  warn = TRUE,
  ...
)

footers_replace_all_text(
  x,
  old_value,
  new_value,
  only_at_cursor = FALSE,
  warn = TRUE,
  ...
)
```

Arguments

x	a docx device
old_value	the value to replace
new_value	the value to replace it with
only_at_cursor	if TRUE, only search-and-replace at the current cursor; if FALSE (default), search-and-replace in the entire document (this can be slow on large documents!)
warn	warn if old_value could not be found.
...	optional arguments to grepl/gsub (e.g. fixed=TRUE)

header_replace_all_text

Replacements will be performed in each header of all sections.

Replacements will be performed in each footer of all sections.

Author(s)

Frank Hangler, <frank@plotandscatter.com>

See Also

[grepl\(\)](#), [regex\(\)](#), [docx_show_chunk\(\)](#)

Examples

```

doc <- read_docx()
doc <- body_add_par(doc, "Placeholder one")
doc <- body_add_par(doc, "Placeholder two")

# Show text chunk at cursor
docx_show_chunk(doc) # Output is 'Placeholder two'

# Simple search-and-replace at current cursor, with regex turned off
doc <- body_replace_all_text(doc, old_value = "Placeholder",
  new_value = "new", only_at_cursor = TRUE, fixed = TRUE)
docx_show_chunk(doc) # Output is 'new two'

# Do the same, but in the entire document and ignoring case
doc <- body_replace_all_text(doc, old_value = "placeholder",
  new_value = "new", only_at_cursor=FALSE, ignore.case = TRUE)
doc <- cursor_backward(doc)
docx_show_chunk(doc) # Output is 'new one'

# Use regex : replace all words starting with "n" with the word "example"
doc <- body_replace_all_text(doc, "\\bn.*?\\b", "example")
docx_show_chunk(doc) # Output is 'example one'

```

body_replace_gg_at_bkm

Add plots at bookmark location in a 'Word' document

Description

Use these functions if you want to replace a paragraph containing a bookmark with a 'ggplot' or a base plot.

Usage

```

body_replace_gg_at_bkm(
  x,
  bookmark,
  value,
  width = 6,
  height = 5,
  res = 300,
  style = "Normal",
  scale = 1,
  keep = FALSE,
  ...
)

body_replace_plot_at_bkm(

```

```

    x,
    bookmark,
    value,
    width = 6,
    height = 5,
    res = 300,
    style = "Normal",
    keep = FALSE,
    ...
  )

```

Arguments

x	an rdocx object
bookmark	bookmark id
value	a ggplot object for body_replace_gg_at_bkm() or a set plot instructions body_replace_plot_at_bkm(), see plot_instr().
width, height	plot size in units expressed by the unit argument. Defaults to a width of 6 and a height of 5 "in"ches.
res	resolution of the png image in ppi
style	paragraph style
scale	Multiplicative scaling factor, same as in ggsave
keep	Should the bookmark be preserved? Defaults to FALSE, i.e.the bookmark will be lost as a side effect.
...	Arguments to be passed to png function.

Examples

```

if (require("ggplot2")) {
  gg_plot <- ggplot(data = iris) +
    geom_point(mapping = aes(Sepal.Length, Petal.Length))

  doc <- read_docx()
  doc <- body_add_par(doc, "insert_plot_here")
  doc <- body_bookmark(doc, "plot")
  doc <- body_replace_gg_at_bkm(doc, bookmark = "plot", value = gg_plot)
  print(doc, target = tempfile(fileext = ".docx"))
}

doc <- read_docx()
doc <- body_add_par(doc, "insert_plot_here")
doc <- body_bookmark(doc, "plot")
if (capabilities(what = "png")) {
  doc <- body_replace_plot_at_bkm(
    doc, bookmark = "plot",
    value = plot_instr(
      code = {
        barplot(1:5, col = 2:6)
      }
    )
  )
}

```

```

    )
  )
}
print(doc, target = tempfile(fileext = ".docx"))

```

body_replace_text_at_bkm

Replace text at a bookmark location

Description

Replace text content enclosed in a bookmark with different text. A bookmark will be considered as valid if enclosing words within a paragraph; i.e., a bookmark along two or more paragraphs is invalid, a bookmark set on a whole paragraph is also invalid, but bookmarking few words inside a paragraph is valid.

Usage

```

body_replace_text_at_bkm(x, bookmark, value)

body_replace_img_at_bkm(x, bookmark, value)

headers_replace_text_at_bkm(x, bookmark, value)

headers_replace_img_at_bkm(x, bookmark, value)

footers_replace_text_at_bkm(x, bookmark, value)

footers_replace_img_at_bkm(x, bookmark, value)

```

Arguments

x	a docx device
bookmark	bookmark id
value	the replacement string, of type character

Examples

```

doc <- read_docx()
doc <- body_add_par(doc, "a paragraph to replace", style = "centered")
doc <- body_bookmark(doc, "text_to_replace")
doc <- body_replace_text_at_bkm(doc, "text_to_replace", "new text")

# demo usage of bookmark and images ----
template <- system.file(package = "officer", "doc_examples/example.docx")

img.file <- file.path( R.home("doc"), "html", "logo.jpg" )

```



```
doc <- read_docx(path = template)
doc <- headers_replace_img_at_bkm(x = doc, bookmark = "bmk_header",
                                value = external_img(src = img.file, width = .53, height = .7))
doc <- footers_replace_img_at_bkm(x = doc, bookmark = "bmk_footer",
                                value = external_img(src = img.file, width = .53, height = .7))
print(doc, target = tempfile(fileext = ".docx"))
```

body_set_default_section

Define Default Section

Description

Define default section of the document. You can define section properties (page size, orientation, ...) with a [prop_section](#) object.

Usage

```
body_set_default_section(x, value)
```

Arguments

x	an rdocx object
value	a prop_section object

Illustrations

See Also

Other functions for Word sections: [body_end_block_section\(\)](#), [body_end_section_columns\(\)](#), [body_end_section_columns_landscape\(\)](#), [body_end_section_continuous\(\)](#), [body_end_section_landscape\(\)](#), [body_end_section_portrait\(\)](#)

Examples

```
default_sect_properties <- prop_section(
  page_size = page_size(orient = "landscape"), type = "continuous",
  page_margins = page_mar(bottom = .75, top = 1.5, right = 2, left = 2)
)

doc_1 <- read_docx()
doc_1 <- body_add_table(doc_1, value = mtcars[1:10, ], style = "table_template")
doc_1 <- body_add_par(doc_1, value = paste(rep(letters, 40), collapse = " "))
doc_1 <- body_set_default_section(doc_1, default_sect_properties)

print(doc_1, target = tempfile(fileext = ".docx"))
```

change_styles	<i>Replace styles in a 'Word' Document</i>
---------------	--

Description

Replace styles with others in a 'Word' document. This function can be used for paragraph, run/character and table styles.

Usage

```
change_styles(x, mapstyles)
```

Arguments

- x an rdocx object
- mapstyles a named list, names are the replacement style, content (as a character vector) are the styles to be replaced. Use [styles_info\(\)](#) to display available styles.

Examples

```
# creating a sample docx so that we can illustrate how
# to change styles
doc_1 <- read_docx()

doc_1 <- body_add_par(doc_1, "A title", style = "heading 1")
doc_1 <- body_add_par(doc_1, "Another title", style = "heading 2")
doc_1 <- body_add_par(doc_1, "Hello world!", style = "Normal")
file <- print(doc_1, target = tempfile(fileext = ".docx"))

# now we can illustrate how
# to change styles with `change_styles`
doc_2 <- read_docx(path = file)
mapstyles <- list(
  "centered" = c("Normal", "heading 2"),
  "strong" = "Default Paragraph Font"
)
doc_2 <- change_styles(doc_2, mapstyles = mapstyles)
print(doc_2, target = tempfile(fileext = ".docx"))
```

color_scheme	<i>Color scheme of a PowerPoint file</i>
--------------	--

Description

Get the color scheme of a 'PowerPoint' master layout into a data.frame.

Usage

```
color_scheme(x)
```

Arguments

x an rpptx object

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
x <- read_pptx()
color_scheme ( x = x )
```

cursor_begin	<i>Set cursor in a 'Word' document</i>
--------------	--

Description

A set of functions is available to manipulate the position of a virtual cursor. This cursor will be used when inserting, deleting or updating elements in the document.

Usage

```
cursor_begin(x)

cursor_bookmark(x, id)

cursor_end(x)

cursor_reach(x, keyword, fixed = FALSE)

cursor_reach_test(x, keyword)

cursor_forward(x)

cursor_backward(x)
```

Arguments

x	a docx device
id	bookmark id
keyword	keyword to look for as a regular expression
fixed	logical. If TRUE, pattern is a string to be matched as is.

cursor_begin

Set the cursor at the beginning of the document, on the first element of the document (usually a paragraph or a table).

cursor_bookmark

Set the cursor at a bookmark that has previously been set.

cursor_end

Set the cursor at the end of the document, on the last element of the document.

cursor_reach

Set the cursor on the first element of the document that contains text specified in argument keyword. The argument keyword is a regexp pattern.

cursor_reach_test

Test if an expression has a match in the document that contains text specified in argument keyword. The argument keyword is a regexp pattern.

cursor_forward

Move the cursor forward, it increments the cursor in the document.

cursor_backward

Move the cursor backward, it decrements the cursor in the document.

Examples

```
library(officer)

# create a template ----
doc <- read_docx()
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "Hello text to replace")
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "blah blah blah")
doc <- body_add_par(doc, "Hello text to replace")
doc <- body_add_par(doc, "blah blah blah")
template_file <- print(
  x = doc,
  target = tempfile(fileext = ".docx")
)

# replace all pars containing "to replace" ----
```

```

doc <- read_docx(path = template_file)
while (cursor_reach_test(doc, "to replace")) {
  doc <- cursor_reach(doc, "to replace")

  doc <- body_add_fpar(
    x = doc,
    pos = "on",
    value = fpar(
      "Here is a link: ",
      hyperlink_ftext(
        text = "yopyop",
        href = "https://cran.r-project.org/"
      )
    )
  )
}

doc <- cursor_end(doc)
doc <- body_add_par(doc, "Yap yap yap yap...")

result_file <- print(
  x = doc,
  target = tempfile(fileext = ".docx")
)

# cursor_bookmark ----

doc <- read_docx()
doc <- body_add_par(doc, "centered text", style = "centered")
doc <- body_bookmark(doc, "text_to_replace")
doc <- body_add_par(doc, "A title", style = "heading 1")
doc <- body_add_par(doc, "Hello world!", style = "Normal")
doc <- cursor_bookmark(doc, "text_to_replace")
doc <- body_add_table(doc, value = iris, style = "table_template")

print(doc, target = tempfile(fileext = ".docx"))

```

docx_bookmarks

List Word bookmarks

Description

List bookmarks id that can be found in a 'Word' document.

Usage

```
docx_bookmarks(x)
```

Arguments

x an rdocx object

See Also

Other functions for Word document informations: `doc_properties()`, `docx_dim()`, `length.rdocx()`, `set_doc_properties()`, `styles_info()`

Examples

```
library(officer)

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, "centered text", style = "centered")
doc_1 <- body_bookmark(doc_1, "text_to_replace_1")
doc_1 <- body_add_par(doc_1, "centered text", style = "centered")
doc_1 <- body_bookmark(doc_1, "text_to_replace_2")

docx_bookmarks(doc_1)

docx_bookmarks(read_docx())
```

docx_comments

Get comments in a Word document as a data.frame

Description

return a data.frame representing the comments in a Word document.

Usage

```
docx_comments(x)
```

Arguments

x an rdocx object

Details

Each row of the returned data frame contains data for one comment. The columns contain the following information:

- "comment_id" - unique comment id
- "author" - name of the comment author
- "initials" - initials of the comment author
- "date" - timestamp of the comment
- "text" - a list column of characters containing the comment text. Elements can be vectors of length > 1 if a comment contains multiple paragraphs, blocks or runs or of length 0 if the comment is empty.

- "para_id" - a list column of characters containing the parent paragraph IDs. Elements can be vectors of length > 1 if a comment spans multiple paragraphs or of length 0 if the comment has no parent paragraph.
- "commented_text" - a list column of characters containing the commented text. Elements can be vectors of length > 1 if a comment spans multiple paragraphs or runs or of length 0 if the commented text is empty.

Examples

```
bl <- block_list(
  fpar("Comment multiple words."),
  fpar("Second line")
)

a_par <- fpar(
  "This paragraph contains",
  run_comment(
    cmt = bl,
    run = ftext("a comment."),
    author = "Author Me",
    date = "2023-06-01"
  )
)

doc <- read_docx()
doc <- body_add_fpar(doc, value = a_par, style = "Normal")

docx_file <- print(doc, target = tempfile(fileext = ".docx"))

docx_comments(read_docx(docx_file))
```

docx_dim

'Word' page layout

Description

Get page width, page height and margins (in inches). The return values are those corresponding to the section where the cursor is.

Usage

```
docx_dim(x)
```

Arguments

x an rdocx object

See Also

Other functions for Word document informations: [doc_properties\(\)](#), [docx_bookmarks\(\)](#), [length.rdocx\(\)](#), [set_doc_properties\(\)](#), [styles_info\(\)](#)

Examples

```
docx_dim(read_docx())
```

```
docx_set_character_style
```

Add character style in a Word document

Description

The function lets you add or modify Word character styles.

Usage

```
docx_set_character_style(
  x,
  style_id,
  style_name,
  base_on,
  fp_t = fp_text_lite()
)
```

Arguments

<code>x</code>	an rdocx object
<code>style_id</code>	a unique style identifier for Word.
<code>style_name</code>	a unique label associated with the style identifier. This label is the name of the style when Word edit the document.
<code>base_on</code>	the character style name used as base style
<code>fp_t</code>	Text formatting properties, see fp_text() .

Examples

```
library(officer)
doc <- read_docx()

doc <- docx_set_character_style(
  doc,
  style_id = "newcharstyle",
  style_name = "label for char style",
  base_on = "Default Paragraph Font",
  fp_text_lite(
    shading.color = "red",
```



```

        color = "white")
    )
    paragraph <- fpar(
      run_wordtext("hello",
        style_id = "newcharstyle"))

    doc <- body_add_fpar(doc, value = paragraph)
    docx_file <- print(doc, target = tempfile(fileext = ".docx"))
    docx_file

```

docx_set_paragraph_style

Add or replace paragraph style in a Word document

Description

The function lets you add or replace a Word paragraph style.

Usage

```

docx_set_paragraph_style(
  x,
  style_id,
  style_name,
  base_on = "Normal",
  fp_p = fp_par(),
  fp_t = NULL
)

```

Arguments

x	an rdocx object
style_id	a unique style identifier for Word.
style_name	a unique label associated with the style identifier. This label is the name of the style when Word edit the document.
base_on	the style name used as base style
fp_p	paragraph formatting properties, see fp_par() .
fp_t	default text formatting properties. This is used as text formatting properties, see fp_text() . If NULL (default), the paragraph will used the default text formatting properties (defined by the base_on argument).

Examples

```
library(officer)

doc <- read_docx()

doc <- docx_set_paragraph_style(
  doc,
  style_id = "rightaligned",
  style_name = "Explicit label",
  fp_p = fp_par(text.align = "right", padding = 20),
  fp_t = fp_text_lite(
    bold = TRUE,
    shading.color = "#FD34F0",
    color = "white")
)

doc <- body_add_par(doc,
  value = "This is a test",
  style = "Explicit label")

docx_file <- print(doc, target = tempfile(fileext = ".docx"))
docx_file
```

docx_show_chunk

*Show underlying text tag structure***Description**

Show the structure of text tags at the current cursor. This is most useful when trying to troubleshoot search-and-replace functionality using [body_replace_all_text\(\)](#).

Usage

```
docx_show_chunk(x)
```

Arguments

x a docx device

See Also

[body_replace_all_text\(\)](#)

Examples

```
doc <- read_docx()
doc <- body_add_par(doc, "Placeholder one")
doc <- body_add_par(doc, "Placeholder two")
```

```
# Show text chunk at cursor
docx_show_chunk(doc) # Output is 'Placeholder two'
```

docx_summary	<i>Get Word content in a data.frame</i>
--------------	---

Description

read content of a Word document and return a data.frame representing the document.

Usage

```
docx_summary(x, preserve = FALSE, remove_fields = FALSE, detailed = FALSE)
```

Arguments

x	an rdocx object
preserve	If FALSE (default), text in table cells is collapsed into a single line. If TRUE, line breaks in table cells are preserved as a "\n" character. This feature is adapted from docxtractr::docx_extract_tbl() published under a MIT licensed in the 'docxtractr' package by Bob Rudis.
remove_fields	if TRUE, prevent field codes from appearing in the returned data.frame.
detailed	Should information on runs be included in summary dataframe? Defaults to FALSE. If TRUE a list column run is added to the summary containing a summary of formatting properties of runs as a dataframe with rows corresponding to a single run and columns containing the information on formatting properties.

Note

Documents included with [body_add_docx\(\)](#) will not be accessible in the results.

Examples

```
example_docx <- system.file(
  package = "officer",
  "doc_examples/example.docx"
)
doc <- read_docx(example_docx)

docx_summary(doc)

docx_summary(doc, preserve = TRUE)[28, ]
```

doc_properties	<i>Read document properties</i>
----------------	---------------------------------

Description

Read Word or PowerPoint document properties and get results in a data.frame.

Usage

```
doc_properties(x)
```

Arguments

x an rdocx or rpptx object

Value

a data.frame

See Also

Other functions for Word document informations: [docx_bookmarks\(\)](#), [docx_dim\(\)](#), [length.rdocx\(\)](#), [set_doc_properties\(\)](#), [styles_info\(\)](#)

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
x <- read_docx()
doc_properties(x)
```

empty_content	<i>Empty block for 'PowerPoint'</i>
---------------	-------------------------------------

Description

Create an empty object to include as an empty placeholder shape in a presentation. This comes in handy when presentation are updated through R, but a user still wants to add some comments in this new content.

Empty content also works with layout fields (slide number and date) to preserve them: they are included on the slide and keep being updated by PowerPoint, i.e. update to the when the slide number when the slide moves in the deck, update to the date.

Usage

```
empty_content()
```

See Also

[ph_with\(\)](#), [body_add_blocks\(\)](#)

Examples

```
fileout <- tempfile(fileext = ".pptx")
doc <- read_pptx()
doc <- add_slide(doc, layout = "Two Content",
  master = "Office Theme")
doc <- ph_with(x = doc, value = empty_content(),
  location = ph_location_type(type = "title") )

doc <- add_slide(doc, "Title and Content")
# add slide number as a computer field
doc <- ph_with(
  x = doc, value = empty_content(),
  location = ph_location_type(type = "sldNum"))

print(doc, target = fileout )
```

external_img

External image

Description

Wraps an image in an object that can then be embedded in a PowerPoint slide or within a Word paragraph.

The image is added as a shape in PowerPoint (it is not possible to mix text and images in a PowerPoint form). With a Word document, the image will be added inside a paragraph.

Usage

```
external_img(
  src,
  width = 0.5,
  height = 0.2,
  unit = "in",
  guess_size = FALSE,
  alt = ""
)
```

Arguments

src	image file path
width, height	size of the image file. It can be ignored if parameter guess_size=TRUE, see parameter guess_size.
unit	unit for width and height, one of "in", "cm", "mm".

<code>guess_size</code>	If package 'magick' is installed, this option can be used (set it to TRUE). The images will be read and width and height will be guessed.
<code>alt</code>	alternative text for images

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package *officetdown*.

See Also

[ph_with](#), [body_add](#), [fpar](#)

Other run functions for reporting: [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonom\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
# wrap r logo with external_img ----
srcfile <- file.path(R.home("doc"), "html", "logo.jpg")
extimg <- external_img(
  src = srcfile, height = 1.06 / 2,
  width = 1.39 / 2
)

# pptx example ----
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(
  x = doc, value = extimg,
  location = ph_location_type(type = "body"),
  use_loc_size = FALSE
)
print(doc, target = tempfile(fileext = ".pptx"))

fp_t <- fp_text(font.size = 20, color = "red")
an_fpar <- fpar(extimg, ftext(" is cool!", fp_t))

# docx example ----
x <- read_docx()
x <- body_add(x, an_fpar)
print(x, target = tempfile(fileext = ".docx"))
```

Description

Create a paragraph representation by concatenating formatted text or images. The result can be inserted in a Word document or a PowerPoint presentation and can also be inserted in a [block_list\(\)](#) call.

All its arguments will be concatenated to create a paragraph where chunks of text and images are associated with formatting properties.

fpar() supports [ftext\(\)](#), [external_img\(\)](#), [run_*\(\)](#) functions (i.e. [run_autonum\(\)](#), [run_word_field\(\)](#)) when output is Word, and simple strings.

Default text and paragraph formatting properties can also be modified with function [update\(\)](#).

Usage

```
fpar(..., fp_p = fp_par(), fp_t = fp_text_lite(), values = NULL)
```

```
## S3 method for class 'fpar'
update(object, fp_p = NULL, fp_t = NULL, ...)
```

Arguments

...	cot objects (ftext() , external_img())
fp_p	paragraph formatting properties, see fp_par()
fp_t	default text formatting properties. This is used as text formatting properties when simple text is provided as argument, see fp_text() .
values	a list of cot objects. If provided, argument ... will be ignored.
object	fpar object

See Also

[block_list\(\)](#), [body_add_fpar\(\)](#), [ph_with\(\)](#)

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [plot_instr\(\)](#), [unordered_list\(\)](#)

Examples

```
fpar(ftext("hello", shortcuts$fp_bold()))

# mix text and image ----
img.file <- file.path( R.home("doc"), "html", "logo.jpg" )

bold_face <- shortcuts$fp_bold(font.size = 12)
bold_redface <- update(bold_face, color = "red")
fpar_1 <- fpar(
  "Hello World, ",
  ftext("how ", prop = bold_redface ),
  external_img(src = img.file, height = 1.06/2, width = 1.39/2),
  ftext(" you?", prop = bold_face ) )
fpar_1
```

```
img_in_par <- fpar(
  external_img(src = img.file, height = 1.06/2, width = 1.39/2),
  fp_p = fp_par(text.align = "center") )
```

fp_border

*Border properties object***Description**

create a border properties object.

Usage

```
fp_border(color = "black", style = "solid", width = 1)
```

```
## S3 method for class 'fp_border'
update(object, color, style, width, ...)
```

Arguments

color	border color - single character value (e.g. "#000000" or "black")
style	border style - single character value : See Details for supported border styles.
width	border width - an integer value : 0 >= value
object	fp_border object
...	further arguments - not used

Details

For Word output the following border styles are supported:

- "none" or "nil" - No Border
- "solid" or "single" - Single Line Border
- "thick" - Single Line Border
- "double" - Double Line Border
- "dotted" - Dotted Line Border
- "dashed" - Dashed Line Border
- "dotDash" - Dot Dash Line Border
- "dotDotDash" - Dot Dot Dash Line Border
- "triple" - Triple Line Border
- "thinThickSmallGap" - Thin, Thick Line Border
- "thickThinSmallGap" - Thick, Thin Line Border
- "thinThickThinSmallGap" - Thin, Thick, Thin Line Border

- "thinThickMediumGap" - Thin, Thick Line Border
- "thickThinMediumGap" - Thick, Thin Line Border
- "thinThickThinMediumGap" - Thin, Thick, Thin Line Border
- "thinThickLargeGap" - Thin, Thick Line Border
- "thickThinLargeGap" - Thick, Thin Line Border
- "thinThickThinLargeGap" - Thin, Thick, Thin Line Border
- "wave" - Wavy Line Border
- "doubleWave" - Double Wave Line Border
- "dashSmallGap" - Dashed Line Border
- "dashDotStroked" - Dash Dot Strokes Line Border
- "threeDEmboss" or "ridge" - 3D Embossed Line Border
- "threeDEngrave" or "groove" - 3D Engraved Line Border
- "outset" - Outset Line Border
- "inset" - Inset Line Border

For HTML output only a limited amount of border styles are supported:

- "none" or "nil" - No Border
- "solid" or "single" - Single Line Border
- "double" - Double Line Border
- "dotted" - Dotted Line Border
- "dashed" - Dashed Line Border
- "threeDEmboss" or "ridge" - 3D Embossed Line Border
- "threeDEngrave" or "groove" - 3D Engraved Line Border
- "outset" - Outset Line Border
- "inset" - Inset Line Border

Non-supported Word border styles will default to "solid".

See Also

Other functions for defining formatting properties: [fp_cell\(\)](#), [fp_par\(\)](#), [fp_tab\(\)](#), [fp_tabs\(\)](#), [fp_text\(\)](#)

Examples

```
fp_border()
fp_border(color = "orange", style = "solid", width = 1)
fp_border(color = "gray", style = "dotted", width = 1)

# modify object -----
border <- fp_border()
update(border, style = "dotted", width = 3)
```

fp_cell	<i>Cell formatting properties</i>
---------	-----------------------------------

Description

Create a fp_cell object that describes cell formatting properties.

Usage

```
fp_cell(  
  border = fp_border(width = 0),  
  border.bottom,  
  border.left,  
  border.top,  
  border.right,  
  vertical.align = "center",  
  margin = 0,  
  margin.bottom,  
  margin.top,  
  margin.left,  
  margin.right,  
  background.color = "transparent",  
  text.direction = "lrbt",  
  rowspan = 1,  
  colspan = 1  
)
```

```
## S3 method for class 'fp_cell'  
format(x, type = "wml", ...)
```

```
## S3 method for class 'fp_cell'  
print(x, ...)
```

```
## S3 method for class 'fp_cell'  
update(  
  object,  
  border,  
  border.bottom,  
  border.left,  
  border.top,  
  border.right,  
  vertical.align,  
  margin = 0,  
  margin.bottom,  
  margin.top,  
  margin.left,  
  margin.right,
```

```

background.color,
text.direction,
rowspan = 1,
colspan = 1,
...
)

```

Arguments

border shortcut for all borders.
border.bottom, border.left, border.top, border.right
[fp_border\(\)](#) for borders.

vertical.align cell content vertical alignment - a single character value, expected value is one of "center" or "top" or "bottom"

margin shortcut for all margins.
margin.bottom, margin.top, margin.left, margin.right
 cell margins - 0 or positive integer value.

background.color
 cell background color - a single character value specifying a valid color (e.g. "#000000" or "black").

text.direction cell text rotation - a single character value, expected value is one of "lrb", "tblr", "btlr".

rowspan specify how many rows the cell is spanned over

colspan specify how many columns the cell is spanned over

x, object fp_cell object

type output type - one of 'wml', 'pml', 'html', 'rtf'.

... further arguments - not used

See Also

Other functions for defining formatting properties: [fp_border\(\)](#), [fp_par\(\)](#), [fp_tab\(\)](#), [fp_tabs\(\)](#), [fp_text\(\)](#)

Examples

```

obj <- fp_cell(margin = 1)
update(obj, margin.bottom = 5)

```

fp_par

*Paragraph formatting properties***Description**

Create a fp_par object that describes paragraph formatting properties.

Function fp_par_lite() is generating properties with only entries for the parameters users provided. The undefined properties will inherit from the default settings.

Usage

```
fp_par(
  text.align = "left",
  padding = 0,
  line_spacing = 1,
  border = fp_border(width = 0),
  padding.bottom,
  padding.top,
  padding.left,
  padding.right,
  border.bottom,
  border.left,
  border.top,
  border.right,
  shading.color = "transparent",
  keep_with_next = FALSE,
  tabs = NULL,
  word_style = "Normal"
)
```

```
fp_par_lite(
  text.align = NA,
  padding = NA,
  line_spacing = NA,
  border = FALSE,
  padding.bottom = NA,
  padding.top = NA,
  padding.left = NA,
  padding.right = NA,
  border.bottom = FALSE,
  border.left = FALSE,
  border.top = FALSE,
  border.right = FALSE,
  shading.color = NA,
  keep_with_next = NA,
  tabs = FALSE,
```

```

        word_style = NA
    )

## S3 method for class 'fp_par'
print(x, ...)

## S3 method for class 'fp_par'
update(
  object,
  text.align,
  padding,
  border,
  padding.bottom,
  padding.top,
  padding.left,
  padding.right,
  border.bottom,
  border.left,
  border.top,
  border.right,
  shading.color,
  keep_with_next,
  word_style,
  ...
)

```

Arguments

text.align	text alignment - a single character value, expected value is one of 'left', 'right', 'center', 'justify'.
padding	paragraph paddings - 0 or positive integer value. Argument padding overwrites arguments padding.bottom, padding.top, padding.left, padding.right.
line_spacing	line spacing, 1 is single line spacing, 2 is double line spacing.
border	shortcut for all borders.
padding.bottom, padding.top, padding.left, padding.right	paragraph paddings - 0 or positive integer value.
border.bottom, border.left, border.top, border.right	fp_border() for borders. overwrite other border properties.
shading.color	shading color - a single character value specifying a valid color (e.g. "#000000" or "black").
keep_with_next	a scalar logical. Specifies that the paragraph (or at least part of it) should be rendered on the same page as the next paragraph when possible.
tabs	NULL (default) for no tabulation marks setting or an object returned by fp_tabs() . Note this can only have effect with Word or RTF outputs.
word_style	Word paragraph style name
x, object	fp_par object
...	further arguments - not used

Value

a fp_par object

See Also

[fpar](#)

Other functions for defining formatting properties: [fp_border\(\)](#), [fp_cell\(\)](#), [fp_tab\(\)](#), [fp_tabs\(\)](#), [fp_text\(\)](#)

Examples

```
fp_par(text.align = "center", padding = 5)
obj <- fp_par(text.align = "center", padding = 1)
update(obj, padding.bottom = 5)
```

fp_tab	<i>Tabulation mark properties object</i>
--------	--

Description

create a tabulation mark properties setting object for Word or RTF. Results can be used as arguments of [fp_tabs\(\)](#).
Once tabulation marks settings are defined, tabulation marks can be added with [run_tab\(\)](#) inside a call to [fpar\(\)](#) or with \t within 'flextable' content.

Usage

```
fp_tab(pos, style = "decimal")
```

Arguments

- pos Specifies the position of the tab stop (in inches).
- style style of the tab. Possible values are: "decimal", "left", "right" or "center".

See Also

Other functions for defining formatting properties: [fp_border\(\)](#), [fp_cell\(\)](#), [fp_par\(\)](#), [fp_tabs\(\)](#), [fp_text\(\)](#)

Examples

```
fp_tab(pos = 0.4, style = "decimal")
fp_tab(pos = 1, style = "right")
```

fp_tabs	<i>Tabs properties object</i>
---------	-------------------------------

Description

create a set of tabulation mark properties object for Word or RTF. Results can be used as arguments tabs of `fp_par()` and will only have effects in Word or RTF outputs.

Once a set of tabulation marks settings is defined, tabulation marks can be added with `run_tab()` inside a call to `fp_par()` or with `\t` within 'flextable' content.

Usage

```
fp_tabs(...)
```

Arguments

... `fp_tab` objects

See Also

Other functions for defining formatting properties: `fp_border()`, `fp_cell()`, `fp_par()`, `fp_tab()`, `fp_text()`

Examples

```
z <- fp_tabs(
  fp_tab(pos = 0.4, style = "decimal"),
  fp_tab(pos = 1, style = "decimal")
)
fp_par(
  run_tab(), ftext("88."),
  run_tab(), ftext("987.45"),
  fp_p = fp_par(
    tabs = z
  )
)
```

fp_text	<i>Text formatting properties</i>
---------	-----------------------------------

Description

Create an `fp_text` object that describes text formatting properties.

Function `fp_text_lite()` is generating properties with only entries for the parameters users provided. The undefined properties will inherit from the default settings.

Usage

```
fp_text(  
  color = "black",  
  font.size = 10,  
  bold = FALSE,  
  italic = FALSE,  
  underlined = FALSE,  
  font.family = "Arial",  
  cs.family = NULL,  
  eastasia.family = NULL,  
  hansa.family = NULL,  
  vertical.align = "baseline",  
  shading.color = "transparent"  
)  
  
fp_text_lite(  
  color = NA,  
  font.size = NA,  
  font.family = NA,  
  cs.family = NA,  
  eastasia.family = NA,  
  hansa.family = NA,  
  bold = NA,  
  italic = NA,  
  underlined = NA,  
  vertical.align = "baseline",  
  shading.color = NA  
)  
  
## S3 method for class 'fp_text'  
format(x, type = "wml", ...)  
  
## S3 method for class 'fp_text'  
print(x, ...)  
  
## S3 method for class 'fp_text'  
update(  
  object,  
  color,  
  font.size,  
  bold,  
  italic,  
  underlined,  
  font.family,  
  cs.family,  
  eastasia.family,  
  hansa.family,  
  vertical.align,
```



```

        shading.color,
        ...
    )

```

Arguments

color	font color - a single character value specifying a valid color (e.g. "#000000" or "black").
font.size	font size (in point) - 0 or positive integer value.
bold	is bold
italic	is italic
underlined	is underlined
font.family	single character value. Specifies the font to be used to format characters in the Unicode range (U+0000-U+007F).
cs.family	optional font to be used to format characters in a complex script Unicode range. For example, Arabic text might be displayed using the "Arial Unicode MS" font.
eastasia.family	optional font to be used to format characters in an East Asian Unicode range. For example, Japanese text might be displayed using the "MS Mincho" font.
hansi.family	optional. Specifies the font to be used to format characters in a Unicode range which does not fall into one of the other categories.
vertical.align	single character value specifying font vertical alignments. Expected value is one of the following : default 'baseline' or 'subscript' or 'superscript'
shading.color	shading color - a single character value specifying a valid color (e.g. "#000000" or "black").
x	fp_text object
type	output type - one of 'wml', 'pml', 'html', 'rtf'.
...	further arguments - not used
object	fp_text object to modify
format	format type, wml for MS word, pml for MS PowerPoint and html.

Value

a fp_text object

See Also

[ftext\(\)](#), [fpar\(\)](#)

Other functions for defining formatting properties: [fp_border\(\)](#), [fp_cell\(\)](#), [fp_par\(\)](#), [fp_tab\(\)](#), [fp_tabs\(\)](#)

Examples

```

fp_text()
fp_text(color = "red")
fp_text(bold = TRUE, shading.color = "yellow")
print(fp_text(color = "red", font.size = 12))

```

ftext	<i>Formatted chunk of text</i>
-------	--------------------------------

Description

Format a chunk of text with text formatting properties (bold, color, ...). The function allows you to create pieces of text formatted the way you want.

Usage

```
ftext(text, prop = NULL)
```

Arguments

text	text value, a single character value
prop	formatting text properties returned by fp_text . It also can be NULL in which case, no formatting is defined (the default is applied).

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package `officedown`.

See Also

[fp_text](#)

Other run functions for reporting: [external_img\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
ftext("hello", fp_text())

properties1 <- fp_text(color = "red")
properties2 <- fp_text(bold = TRUE, shading.color = "yellow")
ftext1 <- ftext("hello", properties1)
ftext2 <- ftext("World", properties2)
paragraph <- fpar(ftext1, " ", ftext2)

x <- read_docx()
x <- body_add(x, paragraph)
print(x, target = tempfile(fileext = ".docx"))
```

hyperlink_ftext	<i>Formatted chunk of text with hyperlink</i>
-----------------	---

Description

Format a chunk of text with text formatting properties (bold, color, ...), the chunk is associated with an hyperlink.

Usage

```
hyperlink_ftext(text, prop = NULL, href)
```

Arguments

text	text value, a single character value
prop	formatting text properties returned by fp_text . It also can be NULL in which case, no formatting is defined (the default is applied).
href	URL value

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package `officetdown`.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
ft <- fp_text(font.size = 12, bold = TRUE)
hyperlink_ftext(
  href = "https://cran.r-project.org/index.html",
  text = "some text", prop = ft
)
```

 layout_dedupe_ph_labels

Detect and handle duplicate placeholder labels

Description

PowerPoint does not enforce unique placeholder labels in a layout. Selecting a placeholder via its label using [ph_location_label](#) will throw an error, if the label is not unique. [layout_dedupe_ph_labels](#) helps to detect, rename, or delete duplicate placeholder labels.

Usage

```
layout_dedupe_ph_labels(x, action = "detect", print_info = FALSE)
```

Arguments

x	An rpptx object.
action	Action to perform on duplicate placeholder labels. One of: • detect (default) = show info on dupes only, make no changes • rename = create unique labels. Labels are renamed by appending a sequential number separated by dot to duplicate labels. For example, c("title", "title") becomes c("title.1", "title.2"). • delete = only keep one of the placeholders with a duplicate label
print_info	Print action information (e.g. renamed placeholders) to console? Default is FALSE. Always TRUE for action detect.

Value

A rpptx object (with modified placeholder labels).

Examples

```
x <- read_pptx()
layout_dedupe_ph_labels(x)

file <- system.file("doc_examples", "ph_dupes.pptx", package = "officer")
x <- read_pptx(file)
layout_dedupe_ph_labels(x)
layout_dedupe_ph_labels(x, "rename", print_info = TRUE)
```

layout_default	<i>Default layout for new slides</i>
----------------	--------------------------------------

Description

Set or remove the default layout used when calling `add_slide()`.

Usage

```
layout_default(x, layout = NULL, master = NULL, as_list = FALSE)
```

Arguments

<code>x</code>	An <code>rpptx</code> object.
<code>layout</code>	Layout name. If <code>NULL</code> (default), removes the default layout.
<code>master</code>	Name of master. Only required if layout name is not unique across masters.
<code>as_list</code>	If <code>TRUE</code> , return a list with layout and master instead of the <code>rpptx</code> object.

Value

The `rpptx` object.

See Also

[add_slide\(\)](#)

Examples

```
# set and remove the default layout
x <- read_pptx()
layout_default(x) # no defaults
x <- layout_default(x, "Title and Content") # set default
layout_default(x)
x <- add_slide(x) # new slide with default layout
x <- layout_default(x, NULL) # remove default
layout_default(x) # no defaults

# use when repeatedly adding slides with same layout
x <- read_pptx()
x <- layout_default(x, "Title and Content")
x <- add_slide(x, title = "1. Slide", body = "Some content")
x <- add_slide(x, title = "2. Slide", body = "Some more content")
x <- add_slide(x, title = "3. Slide", body = "Even more content")
```

layout_properties	<i>Slide layout properties</i>
-------------------	--------------------------------

Description

Detailed information about the placeholders on the slide layouts (label, position, etc.). See *Value* section below for more info.

Usage

```
layout_properties(x, layout = NULL, master = NULL)
```

Arguments

x	an rpptx object
layout	slide layout name. If NULL, returns all layouts.
master	master layout name where layout is located. If NULL, returns all masters.

Value

Returns a data frame with one row per placeholder and the following columns:

- master_name: Name of master (a .pptx file may have more than one)
- name: Name of layout
- type: Placeholder type
- type_idx: Running index for phs of the same type. Ordering by ph position (top -> bottom, left -> right)
- id: A unique placeholder id (assigned by PowerPoint automatically, starts at 2, potentially non-consecutive)
- ph_label: Placeholder label (can be set by the user in PowerPoint)
- ph: Placeholder XML fragment (usually not needed)
- offx,offy: placeholder's distance from left and top edge (in inch)
- cx,cy: width and height of placeholder (in inch)
- rotation: rotation in degrees
- fld_id is generally stored as a hexadecimal or GUID value
- fld_type: a unique identifier for a particular field

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
x <- read_pptx()
layout_properties(x = x, layout = "Title Slide", master = "Office Theme")
layout_properties(x = x, master = "Office Theme")
layout_properties(x = x, layout = "Two Content")
layout_properties(x = x)
```

layout_rename_ph_labels

Change ph labels in a layout

Description

There are two versions of the function. The first takes a set of key-value pairs to rename the ph labels. The second uses a right hand side (rhs) assignment to specify the new ph labels. See section *Details*.

NB: You can also rename ph labels directly in PowerPoint. Open the master template view (Alt + F10) and go to Home > Arrange > Selection Pane.

Usage

```
layout_rename_ph_labels(x, layout, master = NULL, ..., .dots = NULL)
```

```
layout_rename_ph_labels(x, layout, master = NULL, id = NULL) <- value
```

Arguments

x	An rpptx object.
layout	Layout name or index. Index is the row index of layout_summary() .
master	Name of master. Only required if the layout name is not unique across masters.
...	Comma separated list of key-value pairs to rename phs. Either reference a ph via its label ("old label" = "new label") or its unique id ("id" = "new label").
.dots	Provide a named list or vector of key-value pairs to rename phs (list("old label" = "new label").
id	Unique placeholder id (see column id in layout_properties() or plot_layout_properties()).
value	Not relevant for user. A pure technical necessity for rhs assignments.

Details

- Note the difference between the terms id and index. Both can be found in the output of [layout_properties\(\)](#). The unique ph id is found in column id. The index refers to the index of the data frame row.
- In a right hand side (rhs) label assignment (<- new_labels), there are two ways to optionally specify a subset of phs to rename. In both cases, the length of the rhs vector (the new labels) must match the length of the id or index:

1. use the id argument to specify ph ids to rename: `layout_rename_ph_labels(..., id = 2:3) <- new_labels`
2. use an index in squared brackets: `layout_rename_ph_labels(...)[1:2] <- new_labels`

Value

Vector of renamed ph labels.

Examples

```
x <- read_pptx()

# INFO -----

# Returns layout's ph_labels by default in same order as layout_properties()
layout_rename_ph_labels(x, "Comparison")
layout_properties(x, "Comparison")$ph_label

# BASICS -----
#
# HINT: run `plot_layout_properties(x, "Comparison")` to see how labels change

# rename using key-value pairs: 'old label' = 'new label' or 'id' = 'new label'
layout_rename_ph_labels(x, "Comparison", "Title 1" = "LABEL MATCHED") # label matching
layout_rename_ph_labels(x, "Comparison", "3" = "ID MATCHED") # id matching
layout_rename_ph_labels(x, "Comparison", "Date Placeholder 6" = "DATE", "8" = "FOOTER") # label, id

# rename using a named list and the .dots arg
renames <- list("Content Placeholder 3" = "CONTENT_1", "6" = "CONTENT_2")
layout_rename_ph_labels(x, "Comparison", .dots = renames)

# rename via rhs assignment and optional index (not id!)
layout_rename_ph_labels(x, "Comparison") <- LETTERS[1:8]
layout_rename_ph_labels(x, "Comparison")[1:3] <- paste("CHANGED", 1:3)

# rename via rhs assignment and ph id (not index)
layout_rename_ph_labels(x, "Comparison", id = c(2, 4)) <- paste("ID =", c(2, 4))

# MORE -----

# make all labels lower case
labels <- layout_rename_ph_labels(x, "Comparison")
layout_rename_ph_labels(x, "Comparison") <- tolower(labels)

# rename all labels to type [type_idx]
lp <- layout_properties(x, "Comparison")
layout_rename_ph_labels(x, "Comparison") <- paste0(lp$type, " [", lp$type_idx, "]")

# rename duplicated placeholders (see also `layout_dedupe_ph_labels()`)
file <- system.file("doc_examples", "ph_dupes.pptx", package = "officer")
```



```

x <- read_pptx(file)
lp <- layout_properties(x, "2-dupes")
idx <- which(lp$ph_label == "Content 7") # exists twice
layout_rename_ph_labels(x, "2-dupes")[idx] <- paste("DUPLICATE", seq_along(idx))

# warning: in case of duped labels only the first occurrence is renamed
x <- read_pptx(file)
layout_rename_ph_labels(x, "2-dupes", "Content 7" = "new label")

```

layout_summary	<i>Presentation layouts summary</i>
----------------	-------------------------------------

Description

Get information about slide layouts and master layouts into a data.frame. This function returns a data.frame containing all layout and master names.

Usage

```
layout_summary(x)
```

Arguments

x an rpptx object

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```

my_pres <- read_pptx()
layout_summary ( x = my_pres )

```

length.rdocx	<i>Number of blocks inside an rdocx object</i>
--------------	--

Description

return the number of blocks inside an rdocx object. This number also include the default section definition of a Word document - default Word section is an invisible element.

Usage

```

## S3 method for class 'rdocx'
length(x)

```

Arguments

x an rdocx object

See Also

Other functions for Word document informations: [doc_properties\(\)](#), [docx_bookmarks\(\)](#), [docx_dim\(\)](#), [set_doc_properties\(\)](#), [styles_info\(\)](#)

Examples

```
# how many elements are there in an new document produced
# with the default template.
length( read_docx() )
```

length.rpptx	<i>Number of slides</i>
--------------	-------------------------

Description

Function length will return the number of slides.

Usage

```
## S3 method for class 'rpptx'
length(x)
```

Arguments

x an rpptx object

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
my_pres <- read_pptx()
my_pres <- add_slide(my_pres, "Title and Content")
my_pres <- add_slide(my_pres, "Title and Content")
length(my_pres)
```

media_extract	<i>Extract media from a document object</i>
---------------	---

Description

Extract files from a rpptx object.

Usage

```
media_extract(x, path, target)
```

Arguments

x	an rpptx object
path	media path, should be a relative path
target	target file

Examples

```
example_pptx <- system.file(package = "officer",  
  "doc_examples/example.pptx")  
doc <- read_pptx(example_pptx)  
content <- pptx_summary(doc)  
image_row <- content[content$content_type %in% "image", ]  
media_file <- image_row$media_file  
png_file <- tempfile(fileext = ".png")  
media_extract(doc, path = media_file, target = png_file)
```

move_slide	<i>Move a slide</i>
------------	---------------------

Description

Move a slide in a pptx presentation.

Usage

```
move_slide(x, index = NULL, to)
```

Arguments

x	an rpptx object
index	slide index, default to current slide position.
to	new slide index.

Note

cursor is set on the last slide.

See Also

[read_pptx\(\)](#)

Other functions to manipulate slides: [add_slide\(\)](#), [on_slide\(\)](#), [remove_slide\(\)](#), [set_notes\(\)](#)

Examples

```
x <- read_pptx()
x <- add_slide(x, "Title and Content")
x <- ph_with(x, "Hello world 1", location = ph_location_type())
x <- add_slide(x, "Title and Content")
x <- ph_with(x, "Hello world 2", location = ph_location_type())
x <- move_slide(x, index = 1, to = 2)
```

notes_location_label *Location of a named placeholder for notes*

Description

The function will use the label of a placeholder to find the corresponding location in the slide notes.

Usage

```
notes_location_label(ph_label, ...)
```

Arguments

ph_label	placeholder label of the used notes master
...	unused arguments

notes_location_type *Location of a placeholder for notes*

Description

The function will use the type name of the placeholder (e.g. body, hdr), to find the corresponding location.

Usage

```
notes_location_type(type = "body", ...)
```

Arguments

type	placeholder label of the used notes master
...	unused arguments

officer

*Manipulate Microsoft Word and PowerPoint Documents with 'officer'***Description**

The officer package facilitates access to and manipulation of 'Microsoft Word' and 'Microsoft PowerPoint' documents from R. It also supports the writing of 'RTF' documents.

Examples of usage are:

- Create Word documents with tables, titles, TOC and graphics
- Importation of Word and PowerPoint files into data objects
- Write updated content back to a PowerPoint presentation
- Clinical reporting automation
- Production of reports from a shiny application

To start with officer, read about [read_docx\(\)](#), [read_pptx\(\)](#) or [rtf_doc\(\)](#).

The package is also providing several objects that can be printed in 'R Markdown' documents for advanced Word or PowerPoint reporting as [run_autonum\(\)](#) and [block_caption\(\)](#).

Author(s)

Maintainer: David Gohel <david.gohel@ardata.fr>

Authors:

- Stefan Moog <moogs@gmx.de>
- Mark Heckmann <heckmann.mark@gmail.com> ([ORCID](#))

Other contributors:

- ArData [copyright holder]
- Frank Hanger <frank@plotandscatter.com> (function `body_replace_all_text`) [contributor]
- Liz Sander <lsander@civisanalytics.com> (several documentation fixes) [contributor]
- Anton Victorson <anton@victorson.se> (fixes xml structures) [contributor]
- Jon Calder <jonmcalders@gmail.com> (update vignettes) [contributor]
- John Harrold <john.m.harrold@gmail.com> (function `annotate_base`) [contributor]
- John Muschelli <muschelli2@gmail.com> (google doc compatibility) [contributor]
- Bill Denney <wdenney@humanpredictions.com> ([ORCID](#)) (function `as.matrix.rpptx`) [contributor]

- Nikolai Beck <beck.nikolai@gmail.com> (set speaker notes for .pptx documents) [contributor]
- Greg Leleu <gregoire.leleu@gmail.com> (fields functionality in ppt) [contributor]
- Majid Eismann [contributor]
- Hongyuan Jia <hongyuanjia@cqust.edu.cn> ([ORCID](#)) [contributor]
- Michael Stackhouse <mike.stackhouse@atorusresearch.com> [contributor]

See Also

The user documentation: <https://ardata-fr.github.io/officeverse/> and manuals <https://davidgohel.github.io/officer/>

officer-defunct

Defunct Functions in Package officer

Description

Defunct Functions in Package officer

Usage

`slip_in_seqfield(...)`

`slip_in_column_break(...)`

`slip_in_xml(...)`

`slip_in_text(...)`

`slip_in_footnote(...)`

Arguments

`...` unused arguments

Details

`slip_in_seqfield()` is replaced by `run_word_field()`.

`slip_in_column_break()` is replaced by `run_columnbreak()`.

`slip_in_xml()` is replaced by `fpar()`.

`slip_in_text()` is replaced by `fpar()`.

`slip_in_footnote()` is replaced by `run_footnote()`.

on_slide	<i>Change current slide</i>
----------	-----------------------------

Description

Change current slide index of an rpptx object.

Usage

```
on_slide(x, index)
```

Arguments

x	an rpptx object
index	slide index

See Also

[read_pptx\(\)](#), [ph_with\(\)](#)

Other functions to manipulate slides: [add_slide\(\)](#), [move_slide\(\)](#), [remove_slide\(\)](#), [set_notes\(\)](#)

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- add_slide(doc, "Title and Content")
doc <- add_slide(doc, "Title and Content")
doc <- on_slide(doc, index = 1)
doc <- ph_with(
  x = doc, "First title",
  location = ph_location_type(type = "title")
)
doc <- on_slide(doc, index = 3)
doc <- ph_with(
  x = doc, "Third title",
  location = ph_location_type(type = "title")
)

file <- tempfile(fileext = ".pptx")
print(doc, target = file)
```

page_mar

Page margins object

Description

Define margins for each page of a section.

The function creates a representation of the dimensions of a page. The dimensions are defined by length, width and orientation. If the orientation is in landscape mode then the length becomes the width and the width becomes the length.

Usage

```
page_mar(
  bottom = 1417/1440,
  top = 1417/1440,
  right = 1417/1440,
  left = 1417/1440,
  header = 708/1440,
  footer = 708/1440,
  gutter = 0/1440
)
```

Arguments

bottom, top	distance (in inches) between the bottom/top of the text margin and the bottom/top of the page. The text is placed at the greater of the value of this attribute and the extent of the header/footer text. A negative value indicates that the content should be measured from the bottom/top of the page regardless of the footer/header, and so will overlap the footer/header. For example, header=-0.5, bottom=1 means that the footer must start one inch from the bottom of the page and the main document text must start a half inch from the bottom of the page. In this case, the text and footer overlap since bottom is negative.
left, right	distance (in inches) from the left/right edge of the page to the left/right edge of the text.
header	distance (in inches) from the top edge of the page to the top edge of the header.
footer	distance (in inches) from the bottom edge of the page to the bottom edge of the footer.
gutter	page gutter (in inches).

See Also

Other functions for section definition: [page_size\(\)](#), [prop_section\(\)](#), [section_columns\(\)](#)

Examples

```
page_mar()
```

page_size	<i>Page size object</i>
-----------	-------------------------

Description

The function creates a representation of the dimensions of a page. The dimensions are defined by length, width and orientation. If the orientation is in landscape mode then the length becomes the width and the width becomes the length.

Usage

```
page_size(
  width = 11906/1440,
  height = 16838/1440,
  orient = "portrait",
  unit = "in"
)
```

Arguments

width, height	page width, page height, default to A4 format If NULL the value will be ignored and Word will use the default value.
orient	page orientation, either 'landscape', either 'portrait'.
unit	unit for width and height, one of "in", "cm", "mm".

See Also

Other functions for section definition: [page_mar\(\)](#), [prop_section\(\)](#), [section_columns\(\)](#)

Examples

```
page_size(orient = "landscape")
```

phs_with	<i>Fill multiple placeholders using key value syntax</i>
----------	--

Description

A sibling of [ph_with](#) that fills mutiple placeholders at once. Placeholder locations are specfied using the short form syntax. The location and corresponding object are passed as key value pairs (`phs_with("short form location" = object)`). Under the hood, [ph_with](#) is called for each pair. Note that `phs_with` does not cover all options from the `ph_location_*` family and is also less customization. It is a convenience wrapper for the most common use cases. The implemented short forms are listed in section "Short forms".

Usage

```
phs_with(x, ..., .dots = NULL, .slide_idx = NULL)
```

Arguments

<code>x</code>	A rpptx object.
<code>...</code>	Key-value pairs of the form "short form location" = object. If the short form is an integer or a string with blanks, you must wrap it in quotes or back-ticks.
<code>.dots</code>	List of key-value pairs "short form location" = object. Alternative to <code>...</code>
<code>.slide_idx</code>	Numeric indexes of slides to process. NULL (default) processes the current slide only. Use keyword <code>all</code> for all slides.

Short forms

The following short forms are implemented and can be used as the parameter in the function call. The corresponding function from the `ph_location_*` family (called under the hood) is displayed on the right.

Short form	Description	Location function
"left"	Keyword string	ph_location_left()
"right"	Keyword string	ph_location_right()
"fullsize"	Keyword string	ph_location_fullsize()
"body [1]"	String: type + index in brackets (1 if omitted)	ph_location_type("body", 1)
"my_label"	Any string not matching a keyword or type	ph_location_label("my_label")
1	Length 1 integer	ph_location_id(1)

See Also

[ph_with\(\)](#), [add_slide\(\)](#)

Examples

```
library(officer)

# use key-value format to fill phs
x <- read_pptx()
x <- add_slide(x, "Two Content")
x <- phs_with(x,
  `Title 1` = "A title", # ph label
  dt = "Jan. 26, 2025", # ph type
  `body[2]` = "Body 2", # ph type + type index
  left = "Left side", # ph keyword
  `6` = "Footer" # ph index
)

# reuse ph content via the .dots arg
x <- read_pptx()
```

```

my_ph_list <- list(`6` = "Footer", dt = "Jan. 26, 2025")
x <- add_slide(x, "Two Content")
x <- phs_with(x, `Title 1` = "Title A", `body[2]` = "Body A", .dots = my_ph_list)
x <- add_slide(x, "Two Content")
x <- phs_with(x, `Title 1` = "Title B", `body[2]` = "Body B", .dots = my_ph_list)

# use the .slide_idx arg to select which slide(s) to process
x <- read_pptx()
x <- add_slide(x, "Two Content")
x <- add_slide(x, "Two Content")
x <- phs_with(x, `6` = "Footer", dt = "Jan. 26, 2025", .slide_idx = 1:2)

# run to see results
## Not run:
file <- tempfile(fileext = ".pptx")
print(x, file)
browseURL(file) # may not work on all systems

## End(Not run)

```

ph_hyperlink

*Hyperlink a placeholder***Description**

Add hyperlink to a placeholder in the current slide.

Usage

```
ph_hyperlink(x, type = "body", id = 1, id_chr = NULL, ph_label = NULL, href)
```

Arguments

x	an rpptx object
type	placeholder type
id	placeholder index (integer) for a duplicated type. This is to be used when a placeholder type is not unique in the layout of the current slide, e.g. two placeholders with type 'body'. To add onto the first, use id = 1 and id = 2 for the second one. Values can be read from slide_summary() .
id_chr	deprecated.
ph_label	label associated to the placeholder. Use column ph_label of result returned by slide_summary() . If used, type and id are ignored.
href	hyperlink (do not forget http or https prefix)

See Also

[ph_with\(\)](#)

Other functions for placeholders manipulation: [ph_remove\(\)](#), [ph_slidelink\(\)](#)

Examples

```

fileout <- tempfile(fileext = ".pptx")
loc_manual <- ph_location(bg = "red", newlabel = "mytitle")
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(x = doc, "Un titre 1", location = loc_manual)
slide_summary(doc) # read column ph_label here
doc <- ph_hyperlink(
  x = doc, ph_label = "mytitle",
  href = "https://cran.r-project.org"
)

print(doc, target = fileout)

```

ph_location	<i>Location for a placeholder from scratch</i>
-------------	--

Description

The function will return a list that complies with expected format for argument location of function `ph_with()`.

Usage

```

ph_location(
  left = 1,
  top = 1,
  width = 4,
  height = 3,
  newlabel = "",
  bg = NULL,
  rotation = NULL,
  ln = NULL,
  geom = NULL,
  ...
)

```

Arguments

left, top, width, height	place holder coordinates in inches.
newlabel	a label for the placeholder. See section details.
bg	background color
rotation	rotation angle
ln	a <code>sp_line()</code> object specifying the outline style.
geom	shape geometry, see http://www.datypic.com/sc/ooxml/t-a_ST_ShapeType.html
...	unused arguments

Details

The location of the bounding box associated to a placeholder within a slide is specified with the left top coordinate, the width and the height. These are defined in inches:

left left coordinate of the bounding box

top top coordinate of the bounding box

width width of the bounding box

height height of the bounding box

In addition to these attributes, a label can be associated with the shape. Shapes, text boxes, images and other objects will be identified with that label in the *Selection Pane* of PowerPoint. This label can then be reused by other functions such as `ph_location_label()`. It can be set with argument `newlabel`.

See Also

Other functions for placeholder location: `ph_location_fullsize()`, `ph_location_id()`, `ph_location_label()`, `ph_location_left()`, `ph_location_right()`, `ph_location_template()`, `ph_location_type()`

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, "Hello world",
  location = ph_location(width = 4, height = 3, newlabel = "hello")
)
print(doc, target = tempfile(fileext = ".pptx"))

# Set geometry and outline
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
loc <- ph_location(
  left = 1, top = 1, width = 4, height = 3, bg = "steelblue",
  ln = sp_line(color = "red", lwd = 2.5),
  geom = "trapezoid"
)
doc <- ph_with(doc, "", loc = loc)
print(doc, target = tempfile(fileext = ".pptx"))
```

`ph_location_fullsize` *Location of a full size element*

Description

The function will return the location corresponding to a full size display.

Usage

```
ph_location_fullsize(newlabel = "", ...)
```

Arguments

newlabel	a label to associate with the placeholder.
...	unused arguments

See Also

Other functions for placeholder location: [ph_location\(\)](#), [ph_location_id\(\)](#), [ph_location_label\(\)](#), [ph_location_left\(\)](#), [ph_location_right\(\)](#), [ph_location_template\(\)](#), [ph_location_type\(\)](#)

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, "Hello world", location = ph_location_fullsize())
print(doc, target = tempfile(fileext = ".pptx"))
```

ph_location_id	<i>Location of a placeholder based on its id</i>
----------------	--

Description

Each placeholder has an id (a low integer value). The ids are unique across a single layout. The function uses the placeholder's id to reference it. Different from a ph label, the id is auto-assigned by PowerPoint and cannot be modified by the user. Use [layout_properties\(\)](#) (column id) and [plot_layout_properties\(\)](#) (upper right corner, in green) to find a placeholder's id.

Usage

```
ph_location_id(id, newlabel = NULL, ...)
```

Arguments

id	placeholder id.
newlabel	a new label to associate with the placeholder.
...	not used.

Details

The location of the bounding box associated to a placeholder within a slide is specified with the left top coordinate, the width and the height. These are defined in inches:

left left coordinate of the bounding box

top top coordinate of the bounding box

width width of the bounding box

height height of the bounding box

In addition to these attributes, a label can be associated with the shape. Shapes, text boxes, images and other objects will be identified with that label in the *Selection Pane* of PowerPoint. This label can then be reused by other functions such as `ph_location_label()`. It can be set with argument `newlabel`.

See Also

Other functions for placeholder location: `ph_location()`, `ph_location_fullsize()`, `ph_location_label()`, `ph_location_left()`, `ph_location_right()`, `ph_location_template()`, `ph_location_type()`

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Comparison")
plot_layout_properties(doc, "Comparison")

doc <- ph_with(doc, "The Title", location = ph_location_id(id = 2)) # title
doc <- ph_with(doc, "Left Header", location = ph_location_id(id = 3)) # left header
doc <- ph_with(doc, "Left Content", location = ph_location_id(id = 4)) # left content
doc <- ph_with(doc, "The Footer", location = ph_location_id(id = 8)) # footer

file <- tempfile(fileext = ".pptx")
print(doc, file)
## Not run:
file.show(file) # may not work on your system

## End(Not run)
```

ph_location_label	<i>Location of a named placeholder</i>
-------------------	--

Description

The function will use the label of a placeholder to find the corresponding location.

Usage

```
ph_location_label(ph_label, newlabel = NULL, ...)
```

Arguments

ph_label	placeholder label of the used layout. It can be read in PowerPoint or with function <code>layout_properties()</code> in column <code>ph_label</code> .
newlabel	a label to associate with the placeholder.
...	unused arguments

Details

The location of the bounding box associated to a placeholder within a slide is specified with the left top coordinate, the width and the height. These are defined in inches:

left left coordinate of the bounding box

top top coordinate of the bounding box

width width of the bounding box

height height of the bounding box

In addition to these attributes, a label can be associated with the shape. Shapes, text boxes, images and other objects will be identified with that label in the *Selection Pane* of PowerPoint. This label can then be reused by other functions such as `ph_location_label()`. It can be set with argument `newlabel`.

See Also

Other functions for placeholder location: `ph_location()`, `ph_location_fullsize()`, `ph_location_id()`, `ph_location_left()`, `ph_location_right()`, `ph_location_template()`, `ph_location_type()`

Examples

```
# ph_location_label demo ----

doc <- read_pptx()
doc <- add_slide(doc, layout = "Title and Content")

# all ph_label can be read here
layout_properties(doc, layout = "Title and Content")

doc <- ph_with(doc, head(iris),
  location = ph_location_label(ph_label = "Content Placeholder 2")
)
doc <- ph_with(doc, format(Sys.Date()),
  location = ph_location_label(ph_label = "Date Placeholder 3")
)
doc <- ph_with(doc, "This is a title",
  location = ph_location_label(ph_label = "Title 1")
)

print(doc, target = tempfile(fileext = ".pptx"))
```

ph_location_left	<i>Location of a left body element</i>
------------------	--

Description

The function will return the location corresponding to a left bounding box. The function assume the layout 'Two Content' is existing. This is an helper function, if you don't have a layout named 'Two Content', use `ph_location_type()` and set arguments to your specific needs.

Usage

```
ph_location_left(newlabel = NULL, ...)
```

Arguments

```
newlabel      a label to associate with the placeholder.
...           unused arguments
```

See Also

Other functions for placeholder location: [ph_location\(\)](#), [ph_location_fullsize\(\)](#), [ph_location_id\(\)](#), [ph_location_label\(\)](#), [ph_location_right\(\)](#), [ph_location_template\(\)](#), [ph_location_type\(\)](#)

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, "Hello left", location = ph_location_left())
doc <- ph_with(doc, "Hello right", location = ph_location_right())
print(doc, target = tempfile(fileext = ".pptx"))
```

ph_location_right	<i>Location of a right body element</i>
-------------------	---

Description

The function will return the location corresponding to a right bounding box. The function assume the layout 'Two Content' is existing. This is an helper function, if you don't have a layout named 'Two Content', use [ph_location_type\(\)](#) and set arguments to your specific needs.

Usage

```
ph_location_right(newlabel = NULL, ...)
```

Arguments

```
newlabel      a label to associate with the placeholder.
...           unused arguments
```

See Also

Other functions for placeholder location: [ph_location\(\)](#), [ph_location_fullsize\(\)](#), [ph_location_id\(\)](#), [ph_location_label\(\)](#), [ph_location_left\(\)](#), [ph_location_template\(\)](#), [ph_location_type\(\)](#)

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, "Hello left", location = ph_location_left())
doc <- ph_with(doc, "Hello right", location = ph_location_right())
print(doc, target = tempfile(fileext = ".pptx"))
```

ph_location_template *Location for a placeholder based on a template*

Description

The function will return a list that complies with expected format for argument location of function `ph_with()`. A placeholder will be used as template and its positions will be updated with values left, top, width, height.

Usage

```
ph_location_template(
  left = 1,
  top = 1,
  width = 4,
  height = 3,
  newlabel = "",
  type = NULL,
  id = 1,
  ...
)
```

Arguments

left, top, width, height	place holder coordinates in inches.
newlabel	a label for the placeholder. See section details.
type	placeholder type to look for in the slide layout, one of 'body', 'title', 'ctrTitle', 'subTitle', 'dt', 'ftr', 'sldNum'. It will be used as a template placeholder.
id	index of the placeholder template. If two body placeholder, there can be two different index: 1 and 2 for the first and second body placeholders defined in the layout.
...	unused arguments

Details

The location of the bounding box associated to a placeholder within a slide is specified with the left top coordinate, the width and the height. These are defined in inches:

left left coordinate of the bounding box

top top coordinate of the bounding box

width width of the bounding box

height height of the bounding box

In addition to these attributes, a label can be associated with the shape. Shapes, text boxes, images and other objects will be identified with that label in the *Selection Pane* of PowerPoint. This label can then be reused by other functions such as `ph_location_label()`. It can be set with argument `newlabel`.

See Also

Other functions for placeholder location: `ph_location()`, `ph_location_fullsize()`, `ph_location_id()`, `ph_location_label()`, `ph_location_left()`, `ph_location_right()`, `ph_location_type()`

Examples

```
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(doc, "Title",
  location = ph_location_type(type = "title")
)
doc <- ph_with(doc, "Hello world",
  location = ph_location_template(top = 4, type = "title")
)
print(doc, target = tempfile(fileext = ".pptx"))
```

ph_location_type	<i>Location of a placeholder based on a type</i>
------------------	--

Description

The function will use the type name of the placeholder (e.g. body, title), the layout name and few other criterias to find the corresponding location.

Usage

```
ph_location_type(
  type = "body",
  type_idx = NULL,
  position_right = TRUE,
  position_top = TRUE,
  newlabel = NULL,
  id = NULL,
  ...
)
```

Arguments

type	placeholder type to look for in the slide layout, one of 'body', 'title', 'ctrTitle', 'subTitle', 'dt', 'ftr', 'sldNum'.
type_idx	Type index of the placeholder. If there is more than one placeholder of a type (e.g., body), the type index can be supplied to uniquely identify a ph. The index is a running number starting at 1. It is assigned by placeholder position (top -> bottom, left -> right). See plot_layout_properties() for details. If idx argument is used, position_right and position_top are ignored.
position_right	the parameter is used when a selection with above parameters does not provide a unique position (for example layout 'Two Content' contains two element of type 'body'). If TRUE, the element the most on the right side will be selected, otherwise the element the most on the left side will be selected.
position_top	same than position_right but applied to top versus bottom.
newlabel	a label to associate with the placeholder.
id	(DEPRECATED, use type_idx instead) Index of the placeholder. If two body placeholder, there can be two different index: 1 and 2 for the first and second body placeholders defined in the layout. If this argument is used, position_right and position_top will be ignored.
...	unused arguments

Details

The location of the bounding box associated to a placeholder within a slide is specified with the left top coordinate, the width and the height. These are defined in inches:

left left coordinate of the bounding box

top top coordinate of the bounding box

width width of the bounding box

height height of the bounding box

In addition to these attributes, a label can be associated with the shape. Shapes, text boxes, images and other objects will be identified with that label in the *Selection Pane* of PowerPoint. This label can then be reused by other functions such as [ph_location_label\(\)](#). It can be set with argument newlabel.

See Also

Other functions for placeholder location: [ph_location\(\)](#), [ph_location_fullsize\(\)](#), [ph_location_id\(\)](#), [ph_location_label\(\)](#), [ph_location_left\(\)](#), [ph_location_right\(\)](#), [ph_location_template\(\)](#)

Examples

```
# ph_location_type demo ----

loc_title <- ph_location_type(type = "title")
loc_footer <- ph_location_type(type = "ftr")
loc_dt <- ph_location_type(type = "dt")
```

```

loc_slidenum <- ph_location_type(type = "sldNum")
loc_body <- ph_location_type(type = "body")

doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(x = doc, "Un titre", location = loc_title)
doc <- ph_with(x = doc, "pied de page", location = loc_footer)
doc <- ph_with(x = doc, format(Sys.Date()), location = loc_dt)
doc <- ph_with(x = doc, "slide 1", location = loc_slidenum)
doc <- ph_with(x = doc, letters[1:10], location = loc_body)

loc_subtitle <- ph_location_type(type = "subTitle")
loc_ctrtitle <- ph_location_type(type = "ctrTitle")
doc <- add_slide(doc, layout = "Title Slide")
doc <- ph_with(x = doc, "Un sous titre", location = loc_subtitle)
doc <- ph_with(x = doc, "Un titre", location = loc_ctrtitle)

fileout <- tempfile(fileext = ".pptx")
print(doc, target = fileout)

```

ph_remove

Remove a shape

Description

Remove a shape in a slide.

Usage

```
ph_remove(x, type = "body", id = 1, ph_label = NULL, id_chr = NULL)
```

Arguments

x	an rpptx object
type	placeholder type
id	placeholder index (integer) for a duplicated type. This is to be used when a placeholder type is not unique in the layout of the current slide, e.g. two placeholders with type 'body'. To add onto the first, use id = 1 and id = 2 for the second one. Values can be read from slide_summary() .
ph_label	label associated to the placeholder. Use column ph_label of result returned by slide_summary() . If used, type and id are ignored.
id_chr	deprecated.

See Also

[ph_with\(\)](#)

Other functions for placeholders manipulation: [ph_hyperlink\(\)](#), [ph_slidelink\(\)](#)

Examples

```

fileout <- tempfile(fileext = ".pptx")
dummy_fun <- function(doc) {
  doc <- add_slide(doc,
    layout = "Two Content",
    master = "Office Theme"
  )
  doc <- ph_with(
    x = doc, value = "Un titre",
    location = ph_location_type(type = "title")
  )
  doc <- ph_with(
    x = doc, value = "Un corps 1",
    location = ph_location_type(type = "body", id = 1)
  )
  doc <- ph_with(
    x = doc, value = "Un corps 2",
    location = ph_location_type(type = "body", id = 2)
  )
  doc
}
doc <- read_pptx()
for (i in 1:3) {
  doc <- dummy_fun(doc)
}

doc <- on_slide(doc, index = 1)
doc <- ph_remove(x = doc, type = "title")

doc <- on_slide(doc, index = 2)
doc <- ph_remove(x = doc, type = "body", id = 2)

doc <- on_slide(doc, index = 3)
doc <- ph_remove(x = doc, type = "body", id = 1)

print(doc, target = fileout)

```

ph_slidelink

*Slide link to a placeholder***Description**

Add slide link to a placeholder in the current slide.

Usage

```

ph_slidelink(
  x,
  type = "body",

```

```

    id = 1,
    id_chr = NULL,
    ph_label = NULL,
    slide_index
  )

```

Arguments

x	an rpptx object
type	placeholder type
id	placeholder index (integer) for a duplicated type. This is to be used when a placeholder type is not unique in the layout of the current slide, e.g. two placeholders with type 'body'. To add onto the first, use id = 1 and id = 2 for the second one. Values can be read from slide_summary() .
id_chr	deprecated.
ph_label	label associated to the placeholder. Use column ph_label of result returned by slide_summary() . If used, type and id are ignored.
slide_index	slide index to reach

See Also

[ph_with\(\)](#)

Other functions for placeholders manipulation: [ph_hyperlink\(\)](#), [ph_remove\(\)](#)

Examples

```

fileout <- tempfile(fileext = ".pptx")
loc_title <- ph_location_type(type = "title")
doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(x = doc, "Un titre 1", location = loc_title)
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(x = doc, "Un titre 2", location = loc_title)
doc <- on_slide(doc, 1)
slide_summary(doc) # read column ph_label here
doc <- ph_slidelink(x = doc, ph_label = "Title 1", slide_index = 2)

print(doc, target = fileout)

```

ph_with

Add objects on the current slide

Description

add object into a new shape in the current slide. This function is able to add all supported outputs to a presentation. See section **Methods (by class)** to see supported outputs.

Usage

```

ph_with(x, value, location, ...)

ph_with.character(x, value, location, ...)

ph_with.numeric(x, value, location, format_fun = format, ...)

ph_with.factor(x, value, location, ...)

ph_with.logical(x, value, location, format_fun = format, ...)

ph_with.block_list(x, value, location, level_list = integer(0), ...)

ph_with.unordered_list(x, value, location, ...)

ph_with.data.frame(
  x,
  value,
  location,
  header = TRUE,
  tcf = table_conditional_formatting(),
  alignment = NULL,
  ...
)

ph_with.gg(x, value, location, res = 300, alt_text = "", scale = 1, ...)

ph_with.plot_instr(x, value, location, res = 300, ...)

ph_with.external_img(x, value, location, use_loc_size = TRUE, ...)

ph_with.fpar(x, value, location, ...)

ph_with.empty_content(x, value, location, ...)

ph_with.xml_document(x, value, location, ...)

```

Arguments

x	an rpptx object
value	object to add as a new shape. Supported objects are vectors, data.frame, graphics, block of formatted paragraphs, unordered list of formatted paragraphs, pretty tables with package flextable, editable graphics with package rvg, 'Microsoft' charts with package mschart.
location	a placeholder location object or a location short form. It will be used to specify the location of the new shape. This location can be defined with a call to one of the ph_location_* functions (see section "see also"). In ph_with(), several location short forms can be used, as listed in section "Short forms".

...	further arguments passed to or from other methods. When adding a ggplot object or plot_instr, these arguments will be used by png function.
format_fun	format function for non character vectors
level_list	The list of levels for hierarchy structure as integer values. If used the object is formatted as an unordered list. If 1 and 2, item 1 level will be 1, item 2 level will be 2.
header	display header if TRUE
tcf	conditional formatting settings defined by table_conditional_formatting()
alignment	alignment for each columns, 'l' for left, 'r' for right and 'c' for center. Default to NULL.
res	resolution of the png image in ppi
alt_text	Alt-text for screen-readers. Defaults to "". If "" or NULL an alt text added with <code>ggplot2::labs(alt = ...)</code> will be used if any.
scale	Multiplicative scaling factor, same as in ggsave
use_loc_size	if set to FALSE, external_img width and height will be used.

Functions

- `ph_with.character()`: add a character vector to a new shape on the current slide, values will be added as paragraphs.
- `ph_with.numeric()`: add a numeric vector to a new shape on the current slide, values will be first formatted then added as paragraphs.
- `ph_with.factor()`: add a factor vector to a new shape on the current slide, values will be converted as character and then added as paragraphs.
- `ph_with.block_list()`: add a [block_list\(\)](#) made of [fpar\(\)](#) to a new shape on the current slide.
- `ph_with.unordered_list()`: add a [unordered_list\(\)](#) made of [fpar\(\)](#) to a new shape on the current slide.
- `ph_with.data.frame()`: add a data.frame to a new shape on the current slide with function [block_table\(\)](#). Use package 'flextable' instead for more advanced formatings.
- `ph_with.gg()`: add a ggplot object to a new shape on the current slide. Use package 'rvg' for more advanced graphical features.
- `ph_with.plot_instr()`: add an R plot to a new shape on the current slide. Use package 'rvg' for more advanced graphical features.
- `ph_with.external_img()`: add a [external_img\(\)](#) to a new shape on the current slide.
When value is a external_img object, image will be copied into the PowerPoint presentation. The width and height specified in call to [external_img\(\)](#) will be ignored, their values will be those of the location, unless use_loc_size is set to FALSE.
- `ph_with.fpar()`: add an [fpar\(\)](#) to a new shape on the current slide as a single paragraph in a [block_list\(\)](#).
- `ph_with.empty_content()`: add an [empty_content\(\)](#) to a new shape on the current slide.
- `ph_with.xml_document()`: add an xml_document object to a new shape on the current slide. This function is to be used to add custom openxml code.

Short forms

The location argument of `ph_with()` either expects a location object as returned by the `ph_location_*` functions or a corresponding location *short form* (string or numeric):

Location function	Short form	Description
<code>ph_location_left()</code>	"left"	Keyword string
<code>ph_location_right()</code>	"right"	Keyword string
<code>ph_location_fullsize()</code>	"fullsize"	Keyword string
<code>ph_location_type("body", 1)</code>	"body [1]"	String: type + index in brackets (1 if omitted)
<code>ph_location_label("my_label")</code>	"my_label"	Any string not matching a keyword or type
<code>ph_location_id(1)</code>	1	Length 1 integer
<code>ph_location(0, 0, 4, 5)</code>	<code>c(0,0,4,5)</code>	Length 4 numeric, optionally named, <code>c(top=0, left=0, ...)</code>

Illustrations

See Also

Specify placeholder locations with `ph_location_type`, `ph_location`, `ph_location_label`, `ph_location_left`, `ph_location_right`, `ph_location_fullsize`, `ph_location_template`. `phs_with` is a sibling of `ph_with` that fills multiple placeholders at once.

Examples

```
# this name will be used to print the file
# change it to "youfile.pptx" to write the pptx
# file in your working directory.
fileout <- tempfile(fileext = ".pptx")

doc_1 <- read_pptx()
sz <- slide_size(doc_1)
# add text and a table ----
doc_1 <- add_slide(doc_1, layout = "Two Content", master = "Office Theme")
doc_1 <- ph_with(
  x = doc_1, value = c("Table cars"),
  location = ph_location_type(type = "title")
)
doc_1 <- ph_with(
  x = doc_1, value = names(cars),
  location = ph_location_left()
)
doc_1 <- ph_with(
  x = doc_1, value = cars,
  location = ph_location_right()
)

# add a base plot ----
anyplot <- plot_instr(code = {
  col <- c(
```

```

      "#440154FF", "#443A83FF", "#31688EFF",
      "#21908CFF", "#35B779FF", "#8FD744FF", "#FDE725FF"
    )
    barplot(1:7, col = col, yaxt = "n")
  })

doc_1 <- add_slide(doc_1, "Title and Content")
doc_1 <- ph_with(doc_1, anyplot,
  location = ph_location_fullsize(),
  bg = "#006699"
)

# add a ggplot2 plot ----
if (require("ggplot2")) {
  doc_1 <- add_slide(doc_1, "Title and Content")
  gg_plot <- ggplot(data = iris) +
    geom_point(
      mapping = aes(Sepal.Length, Petal.Length),
      size = 3
    ) +
    theme_minimal()
  doc_1 <- ph_with(
    x = doc_1, value = gg_plot,
    location = ph_location_type(type = "body"),
    bg = "transparent"
  )
  doc_1 <- ph_with(
    x = doc_1, value = "graphic title",
    location = ph_location_type(type = "title")
  )
}

# add a external images ----
doc_1 <- add_slide(doc_1,
  layout = "Title and Content",
  master = "Office Theme"
)
doc_1 <- ph_with(
  x = doc_1, value = empty_content(),
  location = ph_location(
    left = 0, top = 0,
    width = sz$width, height = sz$height, bg = "black"
  )
)

svg_file <- file.path(R.home(component = "doc"), "html/Rlogo.svg")
if (require("rsvg")) {
  doc_1 <- ph_with(
    x = doc_1, value = "External images",
    location = ph_location_type(type = "title")
  )
  doc_1 <- ph_with(
    x = doc_1, external_img(svg_file, 100 / 72, 76 / 72),

```

```

    location = ph_location_right(), use_loc_size = FALSE
  )
doc_1 <- ph_with(
  x = doc_1, external_img(svg_file),
  location = ph_location_left(),
  use_loc_size = TRUE
)
}

# add a block_list ----
dummy_text <- readLines(system.file(
  package = "officer",
  "doc_examples/text.txt"
))
fp_1 <- fp_text(bold = TRUE, color = "pink", font.size = 0)
fp_2 <- fp_text(bold = TRUE, font.size = 0)
fp_3 <- fp_text(italic = TRUE, color = "red", font.size = 0)
bl <- block_list(
  fpar(ftext("hello world", fp_1)),
  fpar(
    ftext("hello", fp_2),
    ftext("hello", fp_3)
  ),
  dummy_text
)
doc_1 <- add_slide(doc_1, "Title and Content")
doc_1 <- ph_with(
  x = doc_1, value = bl,
  location = ph_location_type(type = "body")
)

# fpar -----
fpt <- fp_text(
  bold = TRUE, font.family = "Bradley Hand",
  font.size = 150, color = "#F5595B"
)
hw <- fpar(
  ftext("hello ", fpt),
  hyperlink_ftext(
    href = "https://cran.r-project.org/index.html",
    text = "cran", prop = fpt
  )
)
doc_1 <- add_slide(doc_1, "Title and Content")
doc_1 <- ph_with(
  x = doc_1, value = hw,
  location = ph_location_type(type = "body")
)
# unordered_list ----
ul <- unordered_list(
  level_list = c(1, 2, 2, 3, 3, 1),
  str_list = c("Level1", "Level2", "Level2", "Level3", "Level3", "Level1"),

```

```

    style = fp_text(color = "red", font.size = 0)
  )
doc_1 <- add_slide(doc_1, "Title and Content")
doc_1 <- ph_with(
  x = doc_1, value = ul,
  location = ph_location_type()
)

print(doc_1, target = fileout)

# Example using short form locations ----
x <- read_pptx()
x <- add_slide(x, "Title Slide")
x <- ph_with(x, "A title", "Title 1")      # label
x <- ph_with(x, "A subtitle", 3)          # id
x <- ph_with(x, "A left text", "left")    # keyword
x <- ph_with(x, "A date", "dt[1]")        # type + index
x <- ph_with(x, "More content", c(5,.5,9,2)) # numeric vector
file <- tempfile(fileext = ".pptx")
print(x, file)
# browseURL(file) # opens file on some systems

```

plot_instr

Wrap plot instructions for png plotting in Powerpoint or Word

Description

A simple wrapper to capture plot instructions that will be executed and copied in a document. It produces an object of class 'plot_instr' with a corresponding method [ph_with\(\)](#) and [body_add_plot\(\)](#).

The function enable usage of any R plot with argument code. Wrap your code between curly bracket if more than a single expression.

Usage

```
plot_instr(code)
```

Arguments

code plotting instructions

See Also

[ph_with\(\)](#), [body_add_plot\(\)](#)

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [unordered_list\(\)](#)

Examples

```
# plot_instr demo ----

anyplot <- plot_instr(code = {
  barplot(1:5, col = 2:6)
})

doc <- read_docx()
doc <- body_add(doc, anyplot, width = 5, height = 4)
print(doc, target = tempfile(fileext = ".docx"))

doc <- read_pptx()
doc <- add_slide(doc, "Title and Content")
doc <- ph_with(
  doc, anyplot,
  location = ph_location_fullsize(),
  bg = "#00000066", pointsize = 12)
print(doc, target = tempfile(fileext = ".pptx"))
```

plot_layout_properties

Slide layout properties plot

Description

Plot slide layout properties into corresponding placeholders. This can be useful to help visualize placeholders locations and identifiers. *All* information in the plot stems from the [layout_properties\(\)](#) output. See *Details* section for more info.

Usage

```
plot_layout_properties(
  x,
  layout = NULL,
  master = NULL,
  labels = TRUE,
  title = TRUE,
  type = TRUE,
  id = TRUE,
  cex = c(labels = 0.5, type = 0.5, id = 0.5),
  legend = FALSE
)
```

Arguments

x an rpptx object

layout	slide layout name or numeric index (row index from layout_summary()). If NULL (default), it plots the current slide's layout or the default layout (if set and there are not slides yet).
master	master layout name where layout is located. Can be omitted if layout is unambiguous.
labels	if TRUE (default), adds placeholder labels (centered in <i>red</i>).
title	if TRUE (default), adds a title with the layout name at the top.
type	if TRUE (default), adds the placeholder type and its index (in square brackets) in the upper left corner (in <i>blue</i>).
id	if TRUE (default), adds the placeholder's unique id (see column id from layout_properties()) in the upper right corner (in <i>green</i>).
cex	List or vector to specify font size for labels, type, and id. Default is <code>c(labels = .5, type = .5, id = .5)</code> . See graphics::text() for details on how cex works. Matching by position and partial name matching is supported. A single numeric value will apply to all three parameters.
legend	Add a legend to the plot (default FALSE).

Details

The plot contains all relevant information to reference a placeholder via the `ph_location_*` function family:

- `label`: ph label (red, center) to be used in [ph_location_label\(\)](#). *NB*: The label can be assigned by the user in PowerPoint.
- `type[idx]`: ph type + type index in brackets (blue, upper left) to be used in [ph_location_type\(\)](#). *NB*: The index is consecutive and is sorted by ph position (top -> bottom, left -> right).
- `id`: ph id (green, upper right) to be used in `ph_location_id()` (forthcoming). *NB*: The id is set by PowerPoint automatically and lack a meaningful order.

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [slide_size\(\)](#), [slide_summary\(\)](#)

Examples

```
x <- read_pptx()

# select layout explicitly
plot_layout_properties(x = x, layout = "Title Slide", master = "Office Theme")
plot_layout_properties(x = x, layout = "Title Slide") # no master needed if layout name unique
plot_layout_properties(x = x, layout = 1) # use layout index instead of name

# plot current slide's layout (default if no layout is passed)
x <- read_pptx()
x <- add_slide(x, "Title Slide")
plot_layout_properties(x)
```

```
# change appearance: what to show, font size, legend etc.
plot_layout_properties(x, layout = "Two Content", title = FALSE, type = FALSE, id = FALSE)
plot_layout_properties(x, layout = 4, cex = c(labels = .8, id = .7, type = .7))
plot_layout_properties(x, 1, legend = TRUE)
```

pptx_summary	<i>PowerPoint content in a data.frame</i>
--------------	---

Description

Read content of a PowerPoint document and return a dataset representing the document.

Usage

```
pptx_summary(x, preserve = FALSE)
```

Arguments

x	an rpptx object
preserve	If FALSE (default), text in table cells is collapsed into a single line. If TRUE, line breaks in table cells are preserved as a "\n" character. This feature is adapted from docxtractr::docx_extract_tbl() published under a MIT licensed in the 'docxtractr' package by Bob Rudis.

Examples

```
example_pptx <- system.file(package = "officer",
  "doc_examples/example.pptx")
doc <- read_pptx(example_pptx)
pptx_summary(doc)
pptx_summary(example_pptx)
```

print.rpptx	<i>Write a 'PowerPoint' file.</i>
-------------	-----------------------------------

Description

Create a 'PowerPoint' file from an rpptx object (created by [read_pptx\(\)](#)).

Usage

```
## S3 method for class 'rpptx'
print(x, target = NULL, ...)
```


Arguments

x	an rpptx object.
target	path to the .pptx file to write. If target is NULL (default), the rpptx object is printed to the console.
...	unused.

See Also

[read_pptx\(\)](#)

Examples

```
# write an rpptx object to a .pptx file ----
file <- tempfile(fileext = ".pptx")
x <- read_pptx()
print(x, target = file)
```

print.rtf	<i>Write an 'RTF' document to a file</i>
-----------	--

Description

Write the RTF object and its content to a file.

Usage

```
## S3 method for class 'rtf'
print(x, target = NULL, ...)
```

Arguments

x	an 'rtf' object created with rtf_doc()
target	path to the RTF file to write
...	unused

See Also

[rtf_doc\(\)](#)

Examples

```
# write a rdocx object in a rtf file ----
doc <- rtf_doc()
print(doc, target = tempfile(fileext = ".rtf"))
```

prop_section	<i>Section properties</i>
--------------	---------------------------

Description

A section is a grouping of blocks (ie. paragraphs and tables) that have a set of properties that define pages on which the text will appear.

A Section properties object stores information about page composition, such as page size, page orientation, borders and margins.

Usage

```
prop_section(
  page_size = NULL,
  page_margins = NULL,
  type = "continuous",
  section_columns = NULL,
  header_default = NULL,
  header_even = NULL,
  header_first = NULL,
  footer_default = NULL,
  footer_even = NULL,
  footer_first = NULL
)
```

Arguments

page_size	page dimensions, an object generated with function page_size .
page_margins	page margins, an object generated with function page_mar .
type	Section type. It defines how the contents of the section will be placed relative to the previous section. Available types are "continuous" (begins the section on the next paragraph), "evenPage" (begins on the next even-numbered page), "nextColumn" (begins on the next column on the page), "nextPage" (begins on the following page), "oddPage" (begins on the next odd-numbered page).
section_columns	section columns, an object generated with function section_columns . Use NULL (default value) for no content.
header_default	content as a block_list() for the default page header. Use NULL (default value) for no content.
header_even	content as a block_list() for the even page header. Use NULL (default value) for no content.
header_first	content as a block_list() for the first page header. Use NULL (default value) for no content.
footer_default	content as a block_list() for the default page footer. Use NULL (default value) for no content.

footer_even	content as a block_list() for the even page footer. Use NULL (default value) for no content.
footer_first	content as a block_list() for the default page footer. Use NULL (default value) for no content.

Illustrations

See Also

[block_section](#)

Other functions for section definition: [page_mar\(\)](#), [page_size\(\)](#), [section_columns\(\)](#)

Examples

```
library(officer)

landscape_one_column <- block_section(
  prop_section(
    page_size = page_size(orient = "landscape"), type = "continuous"
  )
)
landscape_two_columns <- block_section(
  prop_section(
    page_size = page_size(orient = "landscape"), type = "continuous",
    section_columns = section_columns(widths = c(4.75, 4.75))
  )
)

doc_1 <- read_docx()
# there starts section with landscape_one_column
doc_1 <- body_add_table(doc_1, value = mtcars[1:10, ], style = "table_template")
doc_1 <- body_end_block_section(doc_1, value = landscape_one_column)
# there stops section with landscape_one_column

# there starts section with landscape_two_columns
doc_1 <- body_add_par(doc_1, value = paste(rep(letters, 50), collapse = " "))
doc_1 <- body_end_block_section(doc_1, value = landscape_two_columns)
# there stops section with landscape_two_columns

doc_1 <- body_add_table(doc_1, value = mtcars[1:25, ], style = "table_template")

print(doc_1, target = tempfile(fileext = ".docx"))

# an example with headers and footers -----
txt_lorem <- rep(
  "Purus lectus eros metus turpis mattis platea praesent sed. ",
  50
)
```

```

txt_lorem <- paste0(txt_lorem, collapse = "")

header_first <- block_list(fpar(ftext("text for first page header")))
header_even <- block_list(fpar(ftext("text for even page header")))
header_default <- block_list(fpar(ftext("text for default page header")))
footer_first <- block_list(fpar(ftext("text for first page footer")))
footer_even <- block_list(fpar(ftext("text for even page footer")))
footer_default <- block_list(fpar(ftext("text for default page footer")))

ps <- prop_section(
  header_default = header_default, footer_default = footer_default,
  header_first = header_first, footer_first = footer_first,
  header_even = header_even, footer_even = footer_even
)
x <- read_docx()
for (i in 1:20) {
  x <- body_add_par(x, value = txt_lorem)
}
x <- body_set_default_section(
  x,
  value = ps
)
print(x, target = tempfile(fileext = ".docx"))

```

prop_table

Table properties

Description

Define table properties such as fixed or autofit layout, table width in the document, eventually column widths.

Usage

```

prop_table(
  style = NA_character_,
  layout = table_layout(),
  width = table_width(),
  stylenames = table_stylenames(),
  colwidths = table_colwidths(),
  tcf = table_conditional_formatting(),
  align = "center",
  word_title = NULL,
  word_description = NULL
)

```

Arguments

style	table style to be used to format table
layout	layout defined by table_layout() ,
width	table width in the document defined by table_width()
stylenames	columns styles defined by table_stylenames()
colwidths	column widths defined by table_colwidths()
tcf	conditional formatting settings defined by table_conditional_formatting()
align	table alignment (one of left, center or right)
word_title	alternative text for Word table (used as title of the table)
word_description	alternative text for Word table (used as description of the table)

See Also

Other functions for table definition: [table_colwidths\(\)](#), [table_conditional_formatting\(\)](#), [table_layout\(\)](#), [table_stylenames\(\)](#), [table_width\(\)](#)

Examples

```
prop_table()
to_wml(prop_table())
```

read_docx

Create a 'Word' document object

Description

read and import a docx file as an R object representing the document. When no file is specified, it uses a default empty file.

Use then this object to add content to it and create Word files from R.

Usage

```
read_docx(path = NULL)

## S3 method for class 'rdocx'
print(
  x,
  target = NULL,
  copy_header_refs = FALSE,
  copy_footer_refs = FALSE,
  ...
)
```

Arguments

path	path to the docx file to use as base document. dotx file are supported.
x	an rdocx object
target	path to the docx file to write
copy_header_refs, copy_footer_refs	logical, default is FALSE. If TRUE, copy the references to the header and footer in each section of the body of the document. This parameter is experimental and my change in a future version.
...	unused

Value

an object of class rdocx.

Functions

- `print(rdocx)`: write docx to a file. It returns the path of the result file.

styles

`read_docx()` uses a Word file as the initial document. This is the original Word document from which the document layout, paragraph styles, or table styles come.

You will be able to add formatted text, change the paragraph style with the R api but also use the styles from the original document.

See `body_add_*` functions to add content.

Illustrations**See Also**

[body_add_par](#), [body_add_plot](#), [body_add_table](#)

Examples

```
library(officer)

pinst <- plot_instr({
  z <- c(rnorm(100), rnorm(50, mean = 5))
  plot(density(z))
})

doc_1 <- read_docx()
doc_1 <- body_add_par(doc_1, "This is a table", style = "heading 2")
doc_1 <- body_add_table(doc_1, value = mtcars, style = "table_template")
doc_1 <- body_add_par(doc_1, "This is a plot", style = "heading 2")
doc_1 <- body_add_plot(doc_1, pinst)
```

```
docx_file_1 <- print(doc_1, target = tempfile(fileext = ".docx"))

template <- system.file(package = "officer",
  "doc_examples", "landscape.docx")
doc_2 <- read_docx(path = template)
doc_2 <- body_add_par(doc_2, "This is a table", style = "heading 2")
doc_2 <- body_add_table(doc_2, value = mtcars)
doc_2 <- body_add_par(doc_2, "This is a plot", style = "heading 2")
doc_2 <- body_add_plot(doc_2, pinst)
docx_file_2 <- print(doc_2, target = tempfile(fileext = ".docx"))
```

read_pptx

Create a 'PowerPoint' document object

Description

Read and import a pptx file as an R object representing the document.

The function is called `read_pptx` because it allows you to initialize an object of class `rpptx` from an existing PowerPoint file. Content will be added to the existing presentation. By default, an empty document is used.

Usage

```
read_pptx(path = NULL)
```

Arguments

`path` path to the pptx file to use as base document. potx file are supported.

master layouts and slide layouts

`read_pptx()` uses a PowerPoint file as the initial document. This is the original PowerPoint document where all slide layouts, placeholders for shapes and styles come from. Major points to be aware of are:

- Slide layouts are relative to a master layout. A document can contain one or more master layouts; a master layout can contain one or more slide layouts.
- A slide layout inherits design properties from its master layout but some properties can be overwritten.
- Designs and formatting properties of layouts and shapes (placeholders in a layout) are defined within the initial document. There is no R function to modify these values - they must be defined in the initial document.

See Also

[print.rpptx\(\)](#), [add_slide\(\)](#), [plot_layout_properties\(\)](#), [ph_with\(\)](#)

Examples

```
read_pptx()
```

read_xlsx	Create an 'Excel' document object
-----------	-----------------------------------

Description

Read and import an xlsx file as an R object representing the document. This function is experimental.

Usage

```
read_xlsx(path = NULL)

## S3 method for class 'rxlsx'
length(x)

## S3 method for class 'rxlsx'
print(x, target = NULL, ...)
```

Arguments

path	path to the xlsx file to use as base document.
x	an rxlsx object
target	path to the xlsx file to write
...	unused

Examples

```
read_xlsx()
x <- read_xlsx()
print(x, target = tempfile(fileext = ".xlsx"))
```

remove_slide	Remove a slide
--------------	----------------

Description

Remove a slide from a pptx presentation.

Usage

```
remove_slide(x, index = NULL, rm_images = FALSE)
```


Arguments

x	an rpptx object
index	slide index, default to current slide position.
rm_images	if TRUE (defaults to FALSE), images presented in the slide to remove are also removed from the file.

Note

cursor is set on the last slide.

See Also

[read_pptx\(\)](#), [ph_with\(\)](#), [ph_remove\(\)](#)

Other functions to manipulate slides: [add_slide\(\)](#), [move_slide\(\)](#), [on_slide\(\)](#), [set_notes\(\)](#)

Examples

```
my_pres <- read_pptx()
my_pres <- add_slide(my_pres, "Title and Content")
my_pres <- remove_slide(my_pres)
```

rtf_add

Add content into an RTF document

Description

This function add 'officer' objects into an RTF document. Values are added as new paragraphs. See section 'Methods (by class)' that list supported objects.

Usage

```
rtf_add(x, value, ...)

## S3 method for class 'block_section'
rtf_add(x, value, ...)

## S3 method for class 'character'
rtf_add(x, value, ...)

## S3 method for class 'factor'
rtf_add(x, value, ...)

## S3 method for class 'double'
rtf_add(x, value, formatter = formatC, ...)

## S3 method for class 'fpar'
```

```

rtf_add(x, value, ...)

## S3 method for class 'block_list'
rtf_add(x, value, ...)

## S3 method for class 'gg'
rtf_add(
  x,
  value,
  width = 6,
  height = 5,
  res = 300,
  scale = 1,
  ppr = fp_par(text.align = "center"),
  ...
)

## S3 method for class 'plot_instr'
rtf_add(
  x,
  value,
  width = 6,
  height = 5,
  res = 300,
  scale = 1,
  ppr = fp_par(text.align = "center"),
  ...
)

```

Arguments

x	rtf object, created by rtf_doc() .
value	object to add in the document. Supported objects are vectors, graphics, block of formatted paragraphs. Use package 'flextable' to add tables.
...	further arguments passed to or from other methods. When adding a ggplot object or plot_instr , these arguments will be used by png function. See section 'Methods' to see what arguments can be used.
formatter	function used to format the numerical values
width	height in inches
height	height in inches
res	resolution of the png image in ppi
scale	Multiplicative scaling factor, same as in ggsave
ppr	fp_par() to apply to paragraph.

Methods (by class)

- `rtf_add(block_section)`: add a new section definition

- `rtf_add(character)`: add characters as new paragraphs
- `rtf_add(factor)`: add a factor vector as new paragraphs
- `rtf_add(double)`: add a double vector as new paragraphs
- `rtf_add(fpar)`: add an `fpar()`
- `rtf_add(block_list)`: add an `block_list()`
- `rtf_add(gg)`: add a `ggplot2`
- `rtf_add(plot_instr)`: add a `plot_instr()` object

Examples

```
library(officer)

def_text <- fp_text_lite(color = "#006699", bold = TRUE)
center_par <- fp_par(text.align = "center", padding = 3)

doc <- rtf_doc(
  normal_par = fp_par(line_spacing = 1.4, padding = 3)
)

doc <- rtf_add(
  x = doc,
  value = fpar(
    ftext("how are you?", prop = def_text),
    fp_p = fp_par(text.align = "center")
  )
)

a_paragraph <- fpar(
  ftext("Here is a date: ", prop = def_text),
  run_word_field(field = "Date \@ \"MMMM d yyyy\"",
    fp_p = center_par
  )
)
doc <- rtf_add(
  x = doc,
  value = block_list(
    a_paragraph,
    a_paragraph,
    a_paragraph
  )
)

if (require("ggplot2")) {
  gg <- gg_plot <- ggplot(data = iris) +
    geom_point(mapping = aes(Sepal.Length, Petal.Length))
  doc <- rtf_add(doc, gg,
    width = 3, height = 4,
    ppr = center_par
  )
}
anyplot <- plot_instr(code = {
```

```

    barplot(1:5, col = 2:6)
  })
  doc <- rtf_add(doc, anyplot,
    width = 5, height = 4,
    ppr = center_par
  )

  print(doc, target = tempfile(fileext = ".rtf"))

```

rtf_doc

Create an RTF document object

Description

Creation of the object representing an RTF document which can then receive contents with the [rtf_add\(\)](#) function and be written to a file with the `print(x, target="doc.rtf")` function.

Usage

```

rtf_doc(
  def_sec = prop_section(),
  normal_par = fp_par(),
  normal_chunk = fp_text(font.family = "Arial", font.size = 11)
)

```

Arguments

<code>def_sec</code>	a block_section object used to defined default section.
<code>normal_par</code>	an object generated by fp_par()
<code>normal_chunk</code>	an object generated by fp_text()

Value

an object of class `rtf` representing an empty RTF document.

See Also

[read_docx\(\)](#), [print.rtf\(\)](#), [rtf_add\(\)](#)

Examples

```
rtf_doc(normal_par = fp_par(padding = 3))
```

run_autonum	<i>Auto number</i>
-------------	--------------------

Description

Create an autonumbered chunk, i.e. a string representation of a sequence, each item will be numbered. These runs can also be bookmarked and be used later for cross references.

Usage

```
run_autonum(
  seq_id = "table",
  pre_label = "Table ",
  post_label = ": ",
  bkm = NULL,
  bkm_all = FALSE,
  prop = NULL,
  start_at = NULL,
  tnd = 0,
  tns = "-"
)
```

Arguments

seq_id	sequence identifier
pre_label, post_label	text to add before and after number
bkm	bookmark id to associate with autonumber run. If NULL, no bookmark is added. Value can only be made of alpha numeric characters, ':', '-' and '_'.
bkm_all	if TRUE, the bookmark will be set on the whole string, if FALSE, the bookmark will be set on the number only. Default to FALSE. As an effect when a reference to this bookmark is used, the text can be like "Table 1" or "1" (pre_label is not included in the referenced text).
prop	formatting text properties returned by fp_text .
start_at	If not NULL, it must be a positive integer, it specifies the new number to use, at which number the auto numbering will restart.
tnd	<i>title number depth</i> , a positive integer (only applies if positive) that specify the depth (or heading of level <i>depth</i>) to use for prefixing the caption number with this last reference number. For example, setting tnd=2 will generate numbered captions like '4.3-2' (figure 2 of chapter 4.3).
tns	separator to use between title number and table number. Default is "-".

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package `officetdown`.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Other Word computed fields: [run_reference\(\)](#), [run_word_field\(\)](#)

Examples

```
run_autonum()
run_autonum(seq_id = "fig", pre_label = "fig. ")
run_autonum(seq_id = "tab", pre_label = "Table ", bkm = "anytable")
run_autonum(
  seq_id = "tab", pre_label = "Table ", bkm = "anytable",
  tnd = 2, tns = " "
)
```

run_bookmark	<i>Bookmark for 'Word'</i>
--------------	----------------------------

Description

Add a bookmark on a run object.

Usage

```
run_bookmark(bkm, run)
```

Arguments

bkm	bookmark id to associate with run. Value can only be made of alpha numeric characters, '-' and '_'.
run	a run object, made with a call to one of the "run functions for reporting".

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package [officetext](#).

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
ft <- fp_text(font.size = 12, bold = TRUE)
run_bookmark("par1", ftext("some text", ft))
```

run_columnbreak	<i>Column break for 'Word'</i>
-----------------	--------------------------------

Description

Create a representation of a column break.

Usage

```
run_columnbreak()
```

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package [officetdown](#).

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
run_columnbreak()
```

run_comment	<i>Comment for 'Word'</i>
-------------	---------------------------

Description

Add a comment on a run object.

Usage

```
run_comment(
  cmt,
  run = ftext(""),
  author = "",
  date = "",
  initials = "",
  prop = NULL
)
```

Arguments

cmt	a set of blocks to be used as comment content returned by function <code>block_list()</code> . the "run functions for reporting".
run	a run object, made with a call to one of
author	comment author.
date	comment date
initials	comment initials
prop	formatting text properties returned by <code>fp_text_lite()</code> or <code>fp_text()</code> . It also can be NULL in which case, no formatting is defined (the default is applied).

See Also

Other run functions for reporting: `external_img()`, `ftext()`, `hyperlink_ftext()`, `run_autonum()`, `run_bookmark()`, `run_columnbreak()`, `run_footnote()`, `run_footnoteref()`, `run_linebreak()`, `run_pagebreak()`, `run_reference()`, `run_tab()`, `run_word_field()`, `run_wordtext()`

Examples

```
fp_bold <- fp_text_lite(bold = TRUE)
fp_red <- fp_text_lite(color = "red")

bl <- block_list(
  fpar(ftext("Comment multiple words.", fp_bold)),
  fpar(
    ftext("Second line.", fp_red)
  )
)

comment1 <- run_comment(
  cmt = bl,
  run = ftext("with a comment"),
  author = "Author Me",
  date = Sys.Date(),
  initials = "AM"
)
par1 <- fpar("A paragraph ", comment1)

bl <- block_list(
  fpar(ftext("Comment a paragraph."))
)

comment2 <- run_comment(
  cmt = bl, run = ftext("A commented paragraph"),
  author = "Author You",
  date = Sys.Date(),
  initials = "AY"
)
par2 <- fpar(comment2)

doc <- read_docx()
```



```

doc <- body_add_fpar(doc, value = par1, style = "Normal")
doc <- body_add_fpar(doc, value = par2, style = "Normal")

print(doc, target = tempfile(fileext = ".docx"))

```

run_footnote

Footnote for 'Word'

Description

Wraps a footnote in an object that can then be inserted as a run/chunk with `fpar()` or within an R Markdown document.

Usage

```
run_footnote(x, prop = NULL)
```

Arguments

<code>x</code>	a set of blocks to be used as footnote content returned by function <code>block_list()</code> .
<code>prop</code>	formatting text properties returned by <code>fp_text_lite()</code> or <code>fp_text()</code> . It also can be <code>NULL</code> in which case, no formatting is defined (the default is applied).

See Also

Other run functions for reporting: `external_img()`, `ftext()`, `hyperlink_ftext()`, `run_autonum()`, `run_bookmark()`, `run_columnbreak()`, `run_comment()`, `run_footnoteref()`, `run_linebreak()`, `run_pagebreak()`, `run_reference()`, `run_tab()`, `run_word_field()`, `run_wordtext()`

Examples

```

library(officer)

fp_bold <- fp_text_lite(bold = TRUE)
fp_refnote <- fp_text_lite(vertical.align = "superscript")

img.file <- file.path(R.home("doc"), "html", "logo.jpg")
bl <- block_list(
  fpar(ftext("hello", fp_bold)),
  fpar(
    ftext("hello world", fp_bold),
    external_img(src = img.file, height = 1.06, width = 1.39)
  )
)

a_par <- fpar(
  "this paragraph contains a note ",
  run_footnote(x = bl, prop = fp_refnote),
  ". "
)

```

```

)

doc <- read_docx()
doc <- body_add_fpar(doc, value = a_par, style = "Normal")

print(doc, target = tempfile(fileext = ".docx"))

```

run_footnoteref	<i>Word footnote reference</i>
-----------------	--------------------------------

Description

Wraps a footnote reference in an object that can then be inserted as a run/chunk with [fpar\(\)](#) or within an R Markdown document.

Usage

```
run_footnoteref(prop = NULL)
```

Arguments

prop formatting text properties returned by [fp_text_lite\(\)](#) or [fp_text\(\)](#). It also can be NULL in which case, no formatting is defined (the default is applied).

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
run_footnoteref()
to_wml(run_footnoteref())
```

run_linebreak	<i>Page break for 'Word'</i>
---------------	------------------------------

Description

Object representing a line break for a Word document. The result must be used within a call to [fpar](#).

Usage

```
run_linebreak()
```

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package *officedown*.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
fp_t <- fp_text(font.size = 12, bold = TRUE)
an_fpar <- fpar("let's add a line break", run_linebreak(), ftext("and blah blah!", fp_t))

x <- read_docx()
x <- body_add(x, an_fpar)
print(x, target = tempfile(fileext = ".docx"))
```

run_pagebreak	<i>Page break for 'Word'</i>
---------------	------------------------------

Description

Object representing a page break for a Word document.

Usage

```
run_pagebreak()
```

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package *officedown*.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Examples

```
fp_t <- fp_text(font.size = 12, bold = TRUE)
an_fpar <- fpar("let's add a break page", run_pagebreak(), ftext("and blah blah!", fp_t))

x <- read_docx()
x <- body_add(x, an_fpar)
print(x, target = tempfile(fileext = ".docx"))
```

run_reference

Cross reference

Description

Create a representation of a reference

Usage

```
run_reference(id, prop = NULL)
```

Arguments

id	reference id, a string
prop	formatting text properties returned by fp_text .

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package `officetext`.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#), [run_wordtext\(\)](#)

Other Word computed fields: [run_autonum\(\)](#), [run_word_field\(\)](#)

Examples

```
run_reference("a_ref")
```

run_tab	<i>Tab for 'Word'</i>
---------	-----------------------

Description

Object representing a tab in a Word document. The result must be used within a call to `fpar`. It will only have effects in Word output.

Tabulation marks settings can be defined with `fp_tabs()` in paragraph settings defined with `fp_par()`.

Usage

```
run_tab()
```

usage

You can use this function in conjunction with `fpar` to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package `officedown`.

See Also

Other run functions for reporting: `external_img()`, `ftext()`, `hyperlink_ftext()`, `run_autonum()`, `run_bookmark()`, `run_columnbreak()`, `run_comment()`, `run_footnote()`, `run_footnoteref()`, `run_linebreak()`, `run_pagebreak()`, `run_reference()`, `run_word_field()`, `run_wordtext()`

Examples

```
z <- fp_tabs(
  fp_tab(pos = 0.5, style = "decimal"),
  fp_tab(pos = 1.5, style = "decimal")
)
par1 <- fpar(
  run_tab(), ftext("88."),
  run_tab(), ftext("987.45"),
  fp_p = fp_par(
    tabs = z
  )
)
par2 <- fpar(
  run_tab(), ftext("8."),
  run_tab(), ftext("670987.45"),
  fp_p = fp_par(
    tabs = z
  )
)
x <- read_docx()
x <- body_add(x, par1)
x <- body_add(x, par2)
print(x, target = tempfile(fileext = ".docx"))
```

run_wordtext	<i>Word chunk of text with a style</i>
--------------	--

Description

Format a chunk of text associated with a 'Word' character style. The style is defined with its unique identifier.

Usage

```
run_wordtext(text, style_id = NULL)
```

Arguments

- text text value, a single character value
- style_id 'Word' unique style identifier associated with the style to use.

See Also

[ftext\(\)](#)
Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_word_field\(\)](#)

Examples

```
run1 <- run_wordtext("hello", "DefaultParagraphFont")
paragraph <- fpar(run1)

x <- read_docx()
x <- body_add_fpar(x, paragraph)
print(x, target = tempfile(fileext = ".docx"))
```

run_word_field	<i>'Word' computed field</i>
----------------	------------------------------

Description

Create a 'Word' computed field.

Usage

```
run_word_field(field, prop = NULL, seqfield = NULL)

run_seqfield(field, prop = NULL, seqfield = NULL)
```

Arguments

field	Value for a "Word Computed Field" as a string.
prop	formatting text properties returned by fp_text .
seqfield	deprecated in favor of field.

usage

You can use this function in conjunction with [fpar](#) to create paragraphs consisting of differently formatted text parts. You can also use this function as an *r chunk* in an R Markdown document made with package *officetdown*.

Note

In the previous version, this function was called `run_seqfield` but the name was wrong and should have been `run_word_field`.

See Also

Other run functions for reporting: [external_img\(\)](#), [ftext\(\)](#), [hyperlink_ftext\(\)](#), [run_autonum\(\)](#), [run_bookmark\(\)](#), [run_columnbreak\(\)](#), [run_comment\(\)](#), [run_footnote\(\)](#), [run_footnoteref\(\)](#), [run_linebreak\(\)](#), [run_pagebreak\(\)](#), [run_reference\(\)](#), [run_tab\(\)](#), [run_wordtext\(\)](#)

Other Word computed fields: [run_autonum\(\)](#), [run_reference\(\)](#)

Examples

```
run_word_field(field = "PAGE \\* MERGEFORMAT")
run_word_field(field = "Date \@ \"MMM d yyyy\")
```

section_columns	<i>Section columns</i>
-----------------	------------------------

Description

The function creates a representation of the columns of a section.

Usage

```
section_columns(widths = c(2.5, 2.5), space = 0.25, sep = FALSE)
```

Arguments

widths	columns widths in inches. If 3 values, 3 columns will be produced.
space	space in inches between columns.
sep	if TRUE a line is separating columns.

See Also

Other functions for section definition: [page_mar\(\)](#), [page_size\(\)](#), [prop_section\(\)](#)

Examples

```
section_columns()
```

set_autonum_bookmark	<i>Update bookmark of an autonumber run</i>
----------------------	---

Description

This function lets recycling a object made by [run_autonum\(\)](#) by changing the bookmark value. This is useful to avoid calling [run_autonum\(\)](#) several times because of many tables.

Usage

```
set_autonum_bookmark(x, bkm = NULL)
```

Arguments

x	an object of class run_autonum()
bkm	bookmark id to associate with autonumber run. Value can only be made of alpha numeric characters, ':', '-' and '_'.

See Also

[run_autonum\(\)](#)

Examples

```
z <- run_autonum(
  seq_id = "tab", pre_label = "Table ",
  bkm = "anytable"
)
set_autonum_bookmark(z, bkm = "anothertable")
```

set_doc_properties	<i>Set document properties</i>
--------------------	--------------------------------

Description

set Word or PowerPoint document properties. These are not visible in the document but are available as metadata of the document.

Any character property can be added as a document property. It provides an easy way to insert arbitrary fields. Given the challenges that can be encountered with find-and-replace in word with officer, the use of document fields and quick text fields provides a much more robust approach to automatic document generation from R.

Usage

```
set_doc_properties(
  x,
  title = NULL,
  subject = NULL,
  creator = NULL,
  description = NULL,
  created = NULL,
  ...,
  values = NULL
)
```

Arguments

x	an rdocx or rpptx object
title, subject, creator, description	text fields
created	a date object
...	named arguments (names are field names), each element is a single character value specifying value associated with the corresponding field name.
values	a named list (names are field names), each element is a single character value specifying value associated with the corresponding field name. If values is provided, argument ... will be ignored.

Note

The "last modified" and "last modified by" fields will be automatically be updated when the file is written.

See Also

Other functions for Word document informations: [doc_properties\(\)](#), [docx_bookmarks\(\)](#), [docx_dim\(\)](#), [length.rdocx\(\)](#), [styles_info\(\)](#)

Examples

```
x <- read_docx()
x <- set_doc_properties(x, title = "title",
  subject = "document subject", creator = "Me me me",
  description = "this document is empty",
  created = Sys.time(),
  yoyo = "yok yok",
  glop = "pas glop")
x <- doc_properties(x)
```

set_notes

Set notes for current slide

Description

Set speaker notes for the current slide in a pptx presentation.

Usage

```
set_notes(x, value, location, ...)

## S3 method for class 'character'
set_notes(x, value, location, ...)

## S3 method for class 'block_list'
set_notes(x, value, location, ...)
```

Arguments

x	an rpptx object
value	text to be added to notes
location	a placeholder location object. It will be used to specify the location of the new shape. This location can be defined with a call to one of the notes_ph functions. See section "see also".
...	further arguments passed to or from other methods.

Methods (by class)

- `set_notes(character)`: add a character vector to a place holder in the notes on the current slide, values will be added as paragraphs.
- `set_notes(block_list)`: add a `block_list()` to a place holder in the notes on the current slide.

See Also

`print.rpptx()`, `read_pptx()`, `add_slide()`, `notes_location_label()`, `notes_location_type()`
 Other functions to manipulate slides: `add_slide()`, `move_slide()`, `on_slide()`, `remove_slide()`

Examples

```
# this name will be used to print the file
# change it to "youfile.pptx" to write the pptx
# file in your working directory.
fileout <- tempfile(fileext = ".pptx")
fpt_blue_bold <- fp_text_lite(color = "#006699", bold = TRUE)
doc <- read_pptx()
# add a slide with some text ----
doc <- add_slide(doc, layout = "Title and Content")
doc <- ph_with(x = doc, value = "Slide Title 1",
  location = ph_location_type(type = "title") )
# set speaker notes for the slide ----
doc <- set_notes(doc, value = "This text will only be visible for the speaker.",
  location = notes_location_type("body"))

# add a slide with some text ----
doc <- add_slide(doc, layout = "Title and Content")
doc <- ph_with(x = doc, value = "Slide Title 2",
  location = ph_location_type(type = "title") )
bl <- block_list(
  fpar(ftext("hello world", fpt_blue_bold)),
  fpar(ftext("Turlututu chapeau pointu", fpt_blue_bold))
)
doc <- set_notes(doc, value = bl,
  location = notes_location_type("body"))

print(doc, target = fileout)
```

sheet_select

Select sheet

Description

Set a particular sheet selected when workbook will be edited.

Usage

```
sheet_select(x, sheet)
```

Arguments

x	xlsx object
sheet	sheet name

Examples

```
my_ws <- read_xlsx()
my_pres <- add_sheet(my_ws, label = "new sheet")
my_pres <- sheet_select(my_ws, sheet = "new sheet")
print(my_ws, target = tempfile(fileext = ".xlsx") )
```

shortcuts	<i>shortcuts for formatting properties</i>
-----------	--

Description

Shortcuts for [fp_text\(\)](#), [fp_par\(\)](#), [fp_cell\(\)](#) and [fp_border\(\)](#).

Usage

```
shortcuts
```

Examples

```
shortcuts$fp_bold()
shortcuts$fp_italic()
shortcuts$b_null()
```

slide_size	<i>Slides width and height</i>
------------	--------------------------------

Description

Get the width and height of slides in inches as a named vector.

Usage

```
slide_size(x)
```

Arguments

x an rpptx object

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_summary\(\)](#)

Examples

```
my_pres <- read_pptx()
my_pres <- add_slide(my_pres,
  layout = "Two Content", master = "Office Theme")
slide_size(my_pres)
```

slide_summary	<i>Slide content in a data.frame</i>
---------------	--------------------------------------

Description

Get content and positions of current slide into a data.frame. Data for any tables, images, or paragraphs are imported into the resulting data.frame.

Usage

```
slide_summary(x, index = NULL)
```

Arguments

x	an rpptx object
index	slide index

Note

The column id of the result is not to be used by users. This is a technical string id whose value will be used by office when the document will be rendered. This is not related to argument index required by functions [ph_with\(\)](#).

See Also

Other functions for reading presentation information: [annotate_base\(\)](#), [color_scheme\(\)](#), [doc_properties\(\)](#), [layout_properties\(\)](#), [layout_summary\(\)](#), [length.rpptx\(\)](#), [plot_layout_properties\(\)](#), [slide_size\(\)](#)

Examples

```
my_pres <- read_pptx()
my_pres <- add_slide(my_pres, "Title and Content")
my_pres <- ph_with(my_pres, format(Sys.Date()),
  location = ph_location_type(type="dt"))
my_pres <- add_slide(my_pres, "Title and Content")
my_pres <- ph_with(my_pres, iris[1:2,],
  location = ph_location_type(type="body"))
slide_summary(my_pres)
slide_summary(my_pres, index = 1)
```

slide_visible<- *Get or set slide visibility*

Description

PPTX slides can be visible or hidden. This function gets or sets the visibility of slides.

Usage

```
slide_visible(x) <- value

slide_visible(x, hide = NULL, show = NULL)
```

Arguments

x	An rpptx object.
value	Boolean vector with slide visibilities.
hide, show	Indexes of slides to hide or show.

Value

Boolean vector with slide visibilities or rpptx object if changes are made to the object.

Examples

```
path <- system.file("doc_examples/example.pptx", package = "officer")
x <- read_pptx(path)

slide_visible(x) # get slide visibilities

x <- slide_visible(x, hide = 1:2) # hide slides 1 and 2
x <- slide_visible(x, show = 1:2) # make slides 1 and 2 visible
x <- slide_visible(x, show = 1:2, hide = 3)

slide_visible(x) <- FALSE # hide all slides
slide_visible(x) <- c(TRUE, FALSE, TRUE) # set each slide separately
slide_visible(x) <- c(TRUE, FALSE) # warns that rhs values are recycled

slide_visible(x)[2] <- TRUE # set 2nd slide to visible
slide_visible(x)[c(1, 3)] <- FALSE # 1st and 3rd slide
slide_visible(x)[c(1, 3)] <- c(FALSE, FALSE) # identical
```

sp_line

*Line properties***Description**

Create a sp_line object that describes line properties.

Usage

```
sp_line(
  color = "transparent",
  lwd = 1,
  lty = "solid",
  linecompd = "sng",
  lineend = "rnd",
  linejoin = "round",
  headend = sp_lineend(type = "none"),
  tailend = sp_lineend(type = "none")
)
```

```
## S3 method for class 'sp_line'
print(x, ...)
```

```
## S3 method for class 'sp_line'
update(
  object,
  color,
  lwd,
  lty,
  linecompd,
  lineend,
  linejoin,
  headend,
  tailend,
  ...
)
```

Arguments

color	line color - a single character value specifying a valid color (e.g. "#000000" or "black").
lwd	line width (in point) - 0 or positive integer value.
lty	single character value specifying the line type. Expected value is one of the following: default 'solid' or 'dot' or 'dash' or 'lgDash' or 'dashDot' or 'lgDashDot' or 'lgDashDotDot' or 'sysDash' or 'sysDot' or 'sysDashDot' or 'sysDashDotDot'.

linecmpd	single character value specifying the compound line type. Expected value is one of the following : default 'sng' or 'dbl' or 'tri' or 'thinThick' or 'thickThin'
lineend	single character value specifying the line end style Expected value is one of the following : default 'rnd' or 'sq' or 'flat'
linejoin	single character value specifying the line join style Expected value is one of the following : default 'round' or 'bevel' or 'miter'
headend	a sp_lineend object specifying line head end style
tailend	a sp_lineend object specifying line tail end style
x, object	sp_line object
...	further arguments - not used

Value

a sp_line object

See Also

[sp_lineend](#)

Other functions for defining shape properties: [sp_lineend\(\)](#)

Examples

```
sp_line()
sp_line(color = "red", lwd = 2)
sp_line(lty = "dot", linecmpd = "dbl")
print( sp_line (color="red", lwd = 2) )
obj <- sp_line (color="red", lwd = 2)
update( obj, linecmpd = "dbl" )
```

sp_lineend

Line end properties

Description

Create a sp_lineend object that describes line end properties.

Usage

```
sp_lineend(type = "none", width = "med", length = "med")
```

```
## S3 method for class 'sp_lineend'
print(x, ...)
```

```
## S3 method for class 'sp_lineend'
update(object, type, width, length, ...)
```


Arguments

type	single character value specifying the line end type. Expected value is one of the following : default 'none' or 'triangle' or 'stealth' or 'diamond' or 'oval' or 'arrow'
width	single character value specifying the line end width Expected value is one of the following : default 'sm' or 'med' or 'lg'
length	single character value specifying the line end length Expected value is one of the following : default 'sm' or 'med' or 'lg'
x, object	sp_lineend object
...	further arguments - not used

Value

a sp_lineend object

See Also

[sp_line](#)
Other functions for defining shape properties: [sp_line\(\)](#)

Examples

```
sp_lineend()  
sp_lineend(type = "triangle")  
sp_lineend(type = "arrow", width = "lg", length = "lg")  
print(sp_lineend (type="triangle", width = "lg"))  
obj <- sp_lineend (type="triangle", width = "lg")  
update( obj, type = "arrow" )
```

styles_info	<i>Read 'Word' styles</i>
-------------	---------------------------

Description

read Word styles and get results in a data.frame.

Usage

```
styles_info(  
  x,  
  type = c("paragraph", "character", "table", "numbering"),  
  is_default = c(TRUE, FALSE)  
)
```

Arguments

x an rdocx object

type, is_default subsets for types (i.e. paragraph) and default style (when is_default is TRUE or FALSE)

See Also

Other functions for Word document informations: [doc_properties\(\)](#), [docx_bookmarks\(\)](#), [docx_dim\(\)](#), [length.rdocx\(\)](#), [set_doc_properties\(\)](#)

Examples

```
x <- read_docx()
styles_info(x)
styles_info(x, type = "paragraph", is_default = TRUE)
```

table_colwidths	<i>Column widths of a table</i>
-----------------	---------------------------------

Description

The function defines the size of each column of a table.

Usage

```
table_colwidths(widths = NULL)
```

Arguments

widths Column widths expressed in inches.

See Also

Other functions for table definition: [prop_table\(\)](#), [table_conditional_formatting\(\)](#), [table_layout\(\)](#), [table_stylenames\(\)](#), [table_width\(\)](#)

`table_conditional_formatting`*Table conditional formatting*

Description

Tables can be conditionally formatted based on few properties as whether the content is in the first row, last row, first column, or last column, or whether the rows or columns are to be banded.

Usage

```
table_conditional_formatting(  
  first_row = TRUE,  
  first_column = FALSE,  
  last_row = FALSE,  
  last_column = FALSE,  
  no_hband = FALSE,  
  no_vband = TRUE  
)
```

Arguments

`first_row`, `last_row`
apply or remove formatting from the first or last row in the table.

`first_column`, `last_column`
apply or remove formatting from the first or last column in the table.

`no_hband`, `no_vband`
don't display odd and even rows or columns with alternating shading for ease of reading.

Note

You must define a format for `first_row`, `first_column` and other properties if you need to use them. The format is defined in a docx template.

See Also

Other functions for table definition: [prop_table\(\)](#), [table_colwidths\(\)](#), [table_layout\(\)](#), [table_stylenames\(\)](#), [table_width\(\)](#)

Examples

```
table_conditional_formatting(first_row = TRUE, first_column = TRUE)
```

table_layout	<i>Algorithm for table layout</i>
--------------	-----------------------------------

Description

When a table is displayed in a document, it can either be displayed using a fixed width or autofit layout algorithm:

- fixed: uses fixed widths for columns. The width of the table is not changed regardless of the contents of the cells.
- autofit: uses the contents of each cell and the table width to determine the final column widths.

Usage

```
table_layout(type = "autofit")
```

Arguments

type 'autofit' or 'fixed' algorithm. Default to 'autofit'.

See Also

Other functions for table definition: [prop_table\(\)](#), [table_colwidths\(\)](#), [table_conditional_formatting\(\)](#), [table_stylenames\(\)](#), [table_width\(\)](#)

table_stylenames	<i>Paragraph styles for columns</i>
------------------	-------------------------------------

Description

The function defines the paragraph styles for columns.

Usage

```
table_stylenames(stylenames = list())
```

Arguments

stylenames a named character vector, names are column names, values are paragraph styles associated with each column. If a column is not specified, default value 'Normal' is used. Another form is as a named list, the list names are the styles and the contents are column names to be formatted with the corresponding style.

See Also

Other functions for table definition: [prop_table\(\)](#), [table_colwidths\(\)](#), [table_conditional_formatting\(\)](#), [table_layout\(\)](#), [table_width\(\)](#)

Examples

```
library(officer)

stylenames <- c(
  vs = "centered", am = "centered",
  gear = "centered", carb = "centered"
)

doc_1 <- read_docx()
doc_1 <- body_add_table(doc_1,
  value = mtcars, style = "table_template",
  stylenames = table_stylenames(stylenames = stylenames)
)

print(doc_1, target = tempfile(fileext = ".docx"))

stylenames <- list(
  "centered" = c("vs", "am", "gear", "carb")
)

doc_2 <- read_docx()
doc_2 <- body_add_table(doc_2,
  value = mtcars, style = "table_template",
  stylenames = table_stylenames(stylenames = stylenames)
)

print(doc_2, target = tempfile(fileext = ".docx"))
```

table_width	<i>Preferred width for a table</i>
-------------	------------------------------------

Description

Define the preferred width for a table.

Usage

```
table_width(width = 1, unit = "pct")
```

Arguments

- width value of the preferred width of the table.
- unit unit of the width. Possible values are 'in' (inches) and 'pct' (percent)

Word

All widths in a table are considered preferred because widths of columns can conflict and the table layout rules can require a preference to be overridden.

See Also

Other functions for table definition: [prop_table\(\)](#), [table_colwidths\(\)](#), [table_conditional_formatting\(\)](#), [table_layout\(\)](#), [table_stylenames\(\)](#)

<code>unordered_list</code>	<i>Unordered list</i>
-----------------------------	-----------------------

Description

unordered list of text for PowerPoint presentations. Each text is associated with a hierarchy level.

Usage

```
unordered_list(str_list = character(0), level_list = integer(0), style = NULL)
```

Arguments

- `str_list` list of strings to be included in the object
- `level_list` list of levels for hierarchy structure. Use 0 for 'no bullet', 1 for level 1, 2 for level 2 and so on.
- `style` text style, a `fp_text` object list or a single `fp_text` objects. Use `fp_text(font.size = 0, ...)` to inherit from default sizes of the presentation.

See Also

[ph_with\(\)](#)

Other block functions for reporting: [block_caption\(\)](#), [block_gg\(\)](#), [block_list\(\)](#), [block_pour_docx\(\)](#), [block_section\(\)](#), [block_table\(\)](#), [block_toc\(\)](#), [fpar\(\)](#), [plot_instr\(\)](#)

Examples

```
unordered_list(  
  level_list = c(1, 2, 2, 3, 3, 1),  
  str_list = c("Level1", "Level2", "Level2", "Level3", "Level3", "Level1"),  
  style = fp_text(color = "red", font.size = 0) )  
unordered_list(  
  level_list = c(1, 2, 1),  
  str_list = c("Level1", "Level2", "Level1"),  
  style = list(  
    fp_text(color = "red", font.size = 0),  
    fp_text(color = "pink", font.size = 0),  
    fp_text(color = "orange", font.size = 0)  
  ))
```

Index

- * **Word computed fields**
 - run_autonum, [117](#)
 - run_reference, [124](#)
 - run_word_field, [126](#)
- * **block functions for reporting**
 - block_caption, [9](#)
 - block_gg, [10](#)
 - block_list, [11](#)
 - block_pour_docx, [12](#)
 - block_section, [13](#)
 - block_table, [14](#)
 - block_toc, [15](#)
 - fpar, [54](#)
 - plot_instr, [101](#)
 - unordered_list, [142](#)
- * **functions for Word document informations**
 - doc_properties, [52](#)
 - docx_bookmarks, [45](#)
 - docx_dim, [47](#)
 - length.rdocx, [73](#)
 - set_doc_properties, [129](#)
 - styles_info, [137](#)
- * **functions for Word sections**
 - body_end_block_section, [30](#)
 - body_end_section_columns, [31](#)
 - body_end_section_columns_landscape, [32](#)
 - body_end_section_continuous, [33](#)
 - body_end_section_landscape, [34](#)
 - body_end_section_portrait, [34](#)
 - body_set_default_section, [41](#)
- * **functions for adding content**
 - body_add_blocks, [15](#)
 - body_add_break, [16](#)
 - body_add_caption, [17](#)
 - body_add_docx, [18](#)
 - body_add_fpar, [19](#)
 - body_add_gg, [20](#)
 - body_add_img, [21](#)
 - body_add_par, [22](#)
 - body_add_plot, [23](#)
 - body_add_table, [24](#)
 - body_add_toc, [26](#)
 - body_append_start_context, [27](#)
- * **functions for defining formatting properties**
 - fp_border, [56](#)
 - fp_cell, [58](#)
 - fp_par, [60](#)
 - fp_tab, [62](#)
 - fp_tabs, [63](#)
 - fp_text, [63](#)
- * **functions for defining shape properties**
 - sp_line, [135](#)
 - sp_lineend, [136](#)
- * **functions for placeholder location**
 - ph_location, [84](#)
 - ph_location_fullsize, [85](#)
 - ph_location_id, [86](#)
 - ph_location_label, [87](#)
 - ph_location_left, [88](#)
 - ph_location_right, [89](#)
 - ph_location_template, [90](#)
 - ph_location_type, [91](#)
- * **functions for placeholders manipulation**
 - ph_hyperlink, [83](#)
 - ph_remove, [93](#)
 - ph_slidelink, [94](#)
- * **functions for reading presentation information**
 - annotate_base, [7](#)
 - color_scheme, [42](#)
 - doc_properties, [52](#)
 - layout_properties, [70](#)
 - layout_summary, [73](#)
 - length.rpptx, [74](#)
 - plot_layout_properties, [102](#)

- slide_size, 132
- slide_summary, 133
- * **functions for section definition**
 - page_mar, 80
 - page_size, 81
 - prop_section, 106
 - section_columns, 127
- * **functions for table definition**
 - prop_table, 108
 - table_colwidths, 138
 - table_conditional_formatting, 139
 - table_layout, 140
 - table_stylenames, 140
 - table_width, 141
- * **run functions for reporting**
 - external_img, 53
 - ftext, 66
 - hyperlink_ftext, 67
 - run_autonum, 117
 - run_bookmark, 118
 - run_columnbreak, 119
 - run_comment, 119
 - run_footnote, 121
 - run_footnoteref, 122
 - run_linebreak, 122
 - run_pagebreak, 123
 - run_reference, 124
 - run_tab, 125
 - run_word_field, 126
 - run_wordtext, 126
- * **slide manipulation**
 - add_slide, 6
 - move_slide, 75
 - on_slide, 79
 - remove_slide, 112
 - set_notes, 130
- add_sheet, 5
- add_slide, 6, 76, 79, 113, 130
- add_slide(), 69, 82, 111, 130
- annotate_base, 7, 43, 52, 70, 73, 74, 103, 132, 133
- as.matrix.rpptx, 8
- block_caption, 9, 10, 11, 13–15, 55, 101, 142
- block_caption(), 11, 17, 77
- block_gg, 9, 10, 11, 13–15, 55, 101, 142
- block_list, 9, 10, 11, 13–15, 55, 101, 142
- block_list(), 15, 16, 29, 55, 97, 106, 107, 115, 120, 121, 130
- block_pour_docx, 9–11, 12, 13–15, 55, 101, 142
- block_pour_docx(), 11
- block_section, 9–11, 13, 13, 14, 15, 30, 55, 101, 107, 116, 142
- block_section(), 11
- block_table, 9–11, 13, 14, 15, 55, 101, 142
- block_table(), 11, 97
- block_toc, 9–11, 13, 14, 15, 55, 101, 142
- block_toc(), 11
- body_add, 54
- body_add_blocks, 15, 17–19, 21–26, 28
- body_add_blocks(), 11, 53
- body_add_break, 16, 16, 17–19, 21–26, 28
- body_add_caption, 16, 17, 17, 18, 19, 21–26, 28
- body_add_docx, 16, 17, 18, 19, 21–26, 28
- body_add_docx(), 51
- body_add_fpar, 16–18, 19, 21–26, 28
- body_add_fpar(), 55
- body_add_gg, 16–19, 20, 22–26, 28
- body_add_img, 16–19, 21, 21, 23–26, 28
- body_add_par, 16–19, 21, 22, 22, 24–26, 28, 110
- body_add_plot, 16–19, 21–23, 23, 25, 26, 28, 110
- body_add_plot(), 101
- body_add_table, 16–19, 21–24, 24, 26, 28, 110
- body_add_toc, 16–19, 21–25, 26, 28
- body_append_start_context, 16–19, 21–26, 27
- body_append_stop_context
(body_append_start_context), 27
- body_bookmark, 28
- body_comment, 29
- body_end_block_section, 30, 31–35, 41
- body_end_block_section(), 31
- body_end_section_columns, 30, 31, 32–35, 41
- body_end_section_columns_landscape, 30, 31, 32, 33–35, 41
- body_end_section_continuous, 30–32, 33, 34, 35, 41
- body_end_section_landscape, 30–33, 34, 35, 41

- body_end_section_portrait, [30–34](#), [34](#), [41](#)
- body_remove, [35](#)
- body_replace_all_text, [36](#)
- body_replace_all_text(), [50](#)
- body_replace_gg_at_bkm, [38](#)
- body_replace_img_at_bkm
 - (body_replace_text_at_bkm), [40](#)
- body_replace_plot_at_bkm
 - (body_replace_gg_at_bkm), [38](#)
- body_replace_text_at_bkm, [40](#)
- body_set_default_section, [30–35](#), [41](#)
- change_styles, [42](#)
- color_scheme, [7](#), [42](#), [52](#), [70](#), [73](#), [74](#), [103](#), [132](#), [133](#)
- cursor_backward(cursor_begin), [43](#)
- cursor_begin, [43](#)
- cursor_bookmark(cursor_begin), [43](#)
- cursor_end(cursor_begin), [43](#)
- cursor_forward(cursor_begin), [43](#)
- cursor_reach(cursor_begin), [43](#)
- cursor_reach_test(cursor_begin), [43](#)
- doc_properties, [7](#), [43](#), [46](#), [48](#), [52](#), [70](#), [73](#), [74](#), [103](#), [129](#), [132](#), [133](#), [138](#)
- docx_bookmarks, [45](#), [48](#), [52](#), [74](#), [129](#), [138](#)
- docx_comments, [46](#)
- docx_dim, [46](#), [47](#), [52](#), [74](#), [129](#), [138](#)
- docx_set_character_style, [48](#)
- docx_set_paragraph_style, [49](#)
- docx_show_chunk, [50](#)
- docx_show_chunk(), [36](#), [37](#)
- docx_summary, [51](#)
- empty_content, [52](#)
- empty_content(), [97](#)
- external_img, [53](#), [66](#), [67](#), [118–127](#)
- external_img(), [11](#), [55](#), [97](#)
- footers_replace_all_text
 - (body_replace_all_text), [36](#)
- footers_replace_img_at_bkm
 - (body_replace_text_at_bkm), [40](#)
- footers_replace_text_at_bkm
 - (body_replace_text_at_bkm), [40](#)
- format.fp_cell(fp_cell), [58](#)
- format.fp_text(fp_text), [63](#)
- fp_border, [56](#), [59](#), [62](#), [63](#), [65](#)
- fp_border(), [59](#), [61](#), [132](#)
- fp_cell, [57](#), [58](#), [62](#), [63](#), [65](#)
- fp_cell(), [132](#)
- fp_par, [57](#), [59](#), [60](#), [62](#), [63](#), [65](#)
- fp_par(), [10](#), [49](#), [55](#), [63](#), [114](#), [116](#), [125](#), [132](#)
- fp_par_lite(fp_par), [60](#)
- fp_tab, [57](#), [59](#), [62](#), [62](#), [63](#), [65](#)
- fp_tabs, [57](#), [59](#), [62](#), [63](#), [65](#)
- fp_tabs(), [61](#), [62](#), [125](#)
- fp_text, [57](#), [59](#), [62](#), [63](#), [63](#), [66](#), [67](#), [117](#), [124](#), [127](#)
- fp_text(), [48](#), [49](#), [55](#), [116](#), [120–122](#), [132](#)
- fp_text_lite(fp_text), [63](#)
- fp_text_lite(), [120–122](#)
- fpar, [9–11](#), [13–15](#), [54](#), [54](#), [62](#), [66](#), [67](#), [101](#), [117–119](#), [122–125](#), [127](#), [142](#)
- fpar(), [11](#), [19](#), [62](#), [63](#), [65](#), [97](#), [115](#), [121](#), [122](#)
- ftext, [54](#), [66](#), [67](#), [118–127](#)
- ftext(), [55](#), [65](#), [126](#)
- graphics::text(), [103](#)
- grepl(), [36](#), [37](#)
- gsub(), [36](#)
- headers_replace_all_text
 - (body_replace_all_text), [36](#)
- headers_replace_img_at_bkm
 - (body_replace_text_at_bkm), [40](#)
- headers_replace_text_at_bkm
 - (body_replace_text_at_bkm), [40](#)
- hyperlink_ftext, [54](#), [66](#), [67](#), [118–127](#)
- layout_dedupe_ph_labels, [68](#), [68](#)
- layout_dedupe_ph_labels(), [7](#)
- layout_default, [69](#)
- layout_default(), [6](#)
- layout_properties, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [103](#), [132](#), [133](#)
- layout_properties(), [71](#), [86](#), [87](#), [102](#), [103](#)
- layout_rename_ph_labels, [71](#)
- layout_rename_ph_labels<-
 - (layout_rename_ph_labels), [71](#)
- layout_summary, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [103](#), [132](#), [133](#)
- layout_summary(), [6](#), [71](#), [103](#)
- length.rdocx, [46](#), [48](#), [52](#), [73](#), [129](#), [138](#)
- length.rpptx, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [103](#), [132](#), [133](#)
- length.xlsx(read_xlsx), [112](#)
- media_extract, [75](#)

- `move_slide`, [6](#), [75](#), [79](#), [113](#), [130](#)
- `notes_location_label`, [76](#)
- `notes_location_label()`, [130](#)
- `notes_location_type`, [76](#)
- `notes_location_type()`, [130](#)
- `officer`, [77](#)
- `officer-defunct`, [78](#)
- `officer-package (officer)`, [77](#)
- `on_slide`, [6](#), [76](#), [79](#), [113](#), [130](#)
- `page_mar`, [80](#), [81](#), [106](#), [107](#), [128](#)
- `page_size`, [80](#), [81](#), [106](#), [107](#), [128](#)
- `ph_hyperlink`, [83](#), [93](#), [95](#)
- `ph_location`, [84](#), [86–89](#), [91](#), [92](#), [98](#)
- `ph_location_fullsize`, [85](#), [85](#), [87–89](#), [91](#), [92](#), [98](#)
- `ph_location_id`, [85](#), [86](#), [86](#), [88](#), [89](#), [91](#), [92](#)
- `ph_location_label`, [68](#), [85–87](#), [87](#), [89](#), [91](#), [92](#), [98](#)
- `ph_location_label()`, [103](#)
- `ph_location_left`, [85–88](#), [88](#), [89](#), [91](#), [92](#), [98](#)
- `ph_location_right`, [85–89](#), [89](#), [91](#), [92](#), [98](#)
- `ph_location_template`, [85–89](#), [90](#), [92](#), [98](#)
- `ph_location_type`, [85–89](#), [91](#), [91](#), [98](#)
- `ph_location_type()`, [88](#), [89](#), [103](#)
- `ph_remove`, [83](#), [93](#), [95](#)
- `ph_remove()`, [113](#)
- `ph_slidelink`, [83](#), [93](#), [94](#)
- `ph_with`, [54](#), [81](#), [95](#)
- `ph_with()`, [6](#), [11](#), [53](#), [55](#), [79](#), [82–84](#), [90](#), [93](#), [95](#), [101](#), [111](#), [113](#), [133](#), [142](#)
- `phs_with`, [6](#), [81](#), [98](#)
- `phs_with()`, [6](#)
- `plot_instr`, [9–11](#), [13–15](#), [55](#), [101](#), [114](#), [142](#)
- `plot_instr()`, [11](#), [24](#), [115](#)
- `plot_layout_properties`, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [102](#), [132](#), [133](#)
- `plot_layout_properties()`, [6](#), [71](#), [86](#), [92](#), [111](#)
- `pptx_summary`, [104](#)
- `print.fp_cell (fp_cell)`, [58](#)
- `print.fp_par (fp_par)`, [60](#)
- `print.fp_text (fp_text)`, [63](#)
- `print.rdocx (read_docx)`, [109](#)
- `print.rpptx`, [104](#)
- `print.rpptx()`, [6](#), [111](#), [130](#)
- `print.rtf`, [105](#)
- `print.rtf()`, [116](#)
- `print.xlsx (read_excel)`, [112](#)
- `print.sp_line (sp_line)`, [135](#)
- `print.sp_lineend (sp_lineend)`, [136](#)
- `prop_section`, [13](#), [41](#), [80](#), [81](#), [106](#), [128](#)
- `prop_table`, [108](#), [138–140](#), [142](#)
- `prop_table()`, [14](#)
- `read_docx`, [109](#)
- `read_docx()`, [77](#), [116](#)
- `read_pptx`, [111](#)
- `read_pptx()`, [6](#), [8](#), [76](#), [77](#), [79](#), [104](#), [105](#), [113](#), [130](#)
- `read_excel`, [112](#)
- `regex()`, [36](#), [37](#)
- `remove_slide`, [6](#), [76](#), [79](#), [112](#), [130](#)
- `rtf_add`, [113](#)
- `rtf_add()`, [116](#)
- `rtf_doc`, [116](#)
- `rtf_doc()`, [77](#), [105](#), [114](#)
- `run_autonum`, [9](#), [54](#), [66](#), [67](#), [117](#), [118–127](#)
- `run_Autonum()`, [15](#), [55](#), [77](#), [128](#)
- `run_bookmark`, [54](#), [66](#), [67](#), [118](#), [118](#), [119–127](#)
- `run_columnbreak`, [54](#), [66](#), [67](#), [118](#), [119](#), [120–127](#)
- `run_comment`, [54](#), [66](#), [67](#), [118](#), [119](#), [119](#), [121–127](#)
- `run_footnote`, [54](#), [66](#), [67](#), [118–120](#), [121](#), [122–127](#)
- `run_footnoteref`, [54](#), [66](#), [67](#), [118–121](#), [122](#), [123–127](#)
- `run_linebreak`, [54](#), [66](#), [67](#), [118–122](#), [122](#), [123–127](#)
- `run_pagebreak`, [54](#), [66](#), [67](#), [118–123](#), [123](#), [124–127](#)
- `run_reference`, [54](#), [66](#), [67](#), [118–123](#), [124](#), [125–127](#)
- `run_seqfield (run_word_field)`, [126](#)
- `run_tab`, [54](#), [66](#), [67](#), [118–124](#), [125](#), [126](#), [127](#)
- `run_tab()`, [62](#), [63](#)
- `run_word_field`, [54](#), [66](#), [67](#), [118–126](#), [126](#)
- `run_word_field()`, [55](#)
- `run_wordtext`, [54](#), [66](#), [67](#), [118–125](#), [126](#), [127](#)
- `section_columns`, [80](#), [81](#), [106](#), [107](#), [127](#)
- `set_Autonum_bookmark`, [128](#)
- `set_doc_properties`, [46](#), [48](#), [52](#), [74](#), [129](#), [138](#)
- `set_notes`, [6](#), [76](#), [79](#), [113](#), [130](#)
- `sheet_select`, [131](#)

shortcuts, [132](#)
slide_size, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [103](#), [132](#),
[133](#)
slide_summary, [7](#), [43](#), [52](#), [70](#), [73](#), [74](#), [103](#),
[132](#), [133](#)
slide_summary(), [83](#), [93](#), [95](#)
slide_visible (slide_visible<-), [134](#)
slide_visible<-, [134](#)
slip_in_column_break (officer-defunct),
[78](#)
slip_in_footnote (officer-defunct), [78](#)
slip_in_seqfield (officer-defunct), [78](#)
slip_in_text (officer-defunct), [78](#)
slip_in_xml (officer-defunct), [78](#)
sp_line, [135](#), [137](#)
sp_line(), [84](#)
sp_lineend, [136](#), [136](#)
styles_info, [46](#), [48](#), [52](#), [74](#), [129](#), [137](#)
styles_info(), [42](#)

table_colwidths, [109](#), [138](#), [139](#), [140](#), [142](#)
table_colwidths(), [109](#)
table_conditional_formatting, [109](#), [138](#),
[139](#), [140](#), [142](#)
table_conditional_formatting(), [97](#), [109](#)
table_layout, [109](#), [138–140](#), [140](#), [142](#)
table_layout(), [109](#)
table_stylenames, [109](#), [138–140](#), [140](#), [142](#)
table_stylenames(), [25](#), [109](#)
table_width, [109](#), [138–140](#), [141](#)
table_width(), [109](#)
to_wml(), [10](#)

unordered_list, [9–11](#), [13–15](#), [55](#), [101](#), [142](#)
unordered_list(), [97](#)
update.fp_border (fp_border), [56](#)
update.fp_cell (fp_cell), [58](#)
update.fp_par (fp_par), [60](#)
update.fp_text (fp_text), [63](#)
update.fpar (fpar), [54](#)
update.sp_line (sp_line), [135](#)
update.sp_lineend (sp_lineend), [136](#)

write_elements_to_context
 (body_append_start_context), [27](#)