

# Package ‘twotrials’

June 6, 2025

**Version** 0.6

**Date** 2025-06-04

**Author** Samuel Pawel [aut, cre] (ORCID:  
[<https://orcid.org/0000-0003-2779-320X>](https://orcid.org/0000-0003-2779-320X))

**Maintainer** Samuel Pawel <[samuel.pawel@uzh.ch](mailto:samuel.pawel@uzh.ch)>

**Title** Compatible Point Estimates, Confidence Intervals, and P-Values  
for Two Trials

**Description** Implements combined p-value functions for two trials along with compatible combined point and interval estimates as described in Pawel, Roos, and Held (2025) [<doi:10.48550/arXiv.2503.10246>](https://doi.org/10.48550/arXiv.2503.10246).

**License** GPL-3

**Encoding** UTF-8

**Suggests** roxygen2, tinytest

**NeedsCompilation** no

**RoxygenNote** 7.3.1

**URL** <https://github.com/SamCH93/twotrials>

**BugReports** <https://github.com/SamCH93/twotrials/issues>

**Repository** CRAN

**Date/Publication** 2025-06-06 12:40:02 UTC

## Contents

mu2TR . . . . .	2
muEdginton . . . . .	3
muFisher . . . . .	4
muMA . . . . .	5
muPearson . . . . .	6
muTippett . . . . .	7
p2TR . . . . .	8
pEdginton . . . . .	9

pFisher . . . . .	10
plot.twotrials . . . . .	11
pMA . . . . .	12
pPearson . . . . .	13
print.twotrials . . . . .	14
pTippett . . . . .	15
twotrials . . . . .	16

<b>Index</b>	<b>18</b>
--------------	-----------

---

**mu2TR***Combined estimation function from the two-trials rule***Description**

This function computes parameter estimates from the combined estimation function based on the two-trials rule

**Usage**

```
mu2TR(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

**Arguments**

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments (for consistency with other estimation functions)

**Value**

The parameter estimate based on the two-trials rule

**Author(s)**

Samuel Pawel

**See Also**

[p2TR](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
mu2TR(a = c(0.975, 0.5, 0.025), t1 = -0.4942, t2 = -0.1847, se1 = 0.1833,
       se2 = 0.1738, alternative = "less")
```

---

muEdgington

*Combined estimation function from Edgington's method*

---

## Description

This function computes parameter estimates from the combined estimation function based on Edginton's method

## Usage

```
muEdgington(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

## Arguments

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments for stats::uniroot

## Value

The parameter estimate based on Edgington's method

## Author(s)

Samuel Pawel

## See Also

[pEdgington](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
muEdgington(a = c(0.975, 0.5, 0.025), t1 = -0.4942, t2 = -0.1847, se1 = 0.1833,
              se2 = 0.1738, alternative = "less")
```

**muFisher**

*Combined estimation function from Fisher's method*

## Description

This function computes parameter estimates from the combined estimation function based on Fisher's method

## Usage

```
muFisher(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

## Arguments

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments for stats::uniroot

## Value

The parameter estimate based on Fisher's method

## Author(s)

Samuel Pawel

## See Also

[pFisher](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
muFisher(a = c(0.975, 0.5, 0.025), t1 = -0.4942, t2 = -0.1847, se1 = 0.1833,
          se2 = 0.1738, alternative = "less")
```

---

muMA

*Combined estimation function from fixed-effect meta-analysis*

---

## Description

This function computes parameter estimates from the combined estimation function based on fixed-effect meta-analysis

## Usage

```
muMA(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

## Arguments

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments (for consistency with other estimation functions)

## Value

The parameter estimate based on fixed-effect meta-analysis

## Author(s)

Samuel Pawel

## See Also

[muMA](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
muMA(a = c(0.975, 0.5, 0.025), t1 = -0.4942, t2 = -0.1847, se1 = 0.1833,
      se2 = 0.1738, alternative = "less")
```

**muPearson**

*Combined estimation function from Pearson's method*

## Description

This function computes parameter estimates from the combined estimation function based on Pearson's method

## Usage

```
muPearson(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

## Arguments

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments for stats::uniroot

## Value

The parameter estimate based on Pearson's method

## Author(s)

Samuel Pawel

## See Also

[pPearson](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
muPearson(a = c(0.975, 0.5, 0.025), t1 = -0.4942, t2 = -0.1847, se1 = 0.1833,
           se2 = 0.1738, alternative = "less")
```

---

muTippett

*Combined estimation function from Tippett's method*

---

## Description

This function computes parameter estimates from the combined estimation function based on Tippett's method

## Usage

```
muTippett(a = 0.5, t1, t2, se1, se2, alternative = "greater", ...)
```

## Arguments

a	P-value function quantile corresponding to the parameter estimate. Defaults to 0.5, which corresponds to the median estimate. Set to a = c(0.025, 0.975) to obtain limits of a 95% confidence interval
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
...	Additional arguments (for consistency with other estimation functions)

## Value

The parameter estimate based on Tippett's method

## Author(s)

Samuel Pawel

## See Also

[pTippett](#)

## Examples

```
## 95% CI and median estimate for logRR in RESPIRE trials
muTippett(a = c(0.975, 0.5, 0.025), t1 = -0.491, t2 = -0.185, se1 = 0.179,
           se2 = 0.174, alternative = "less")
```

p2TR

*Combined p-value from the two-trials rule*

## Description

This function computes the combined p-value based on two parameter estimates using the two-trials rule (also known as the maximum method)

## Usage

```
p2TR(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

## Arguments

<code>mu</code>	Null value. Defaults to 0
<code>t1</code>	Parameter estimate from trial 1
<code>t2</code>	Parameter estimate from trial 2
<code>se1</code>	Standard error of the parameter estimate from trial 1
<code>se2</code>	Standard error of the parameter estimate from trial 2
<code>alternative</code>	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

## Value

The combined p-value based on the two-trials rule

## Author(s)

Samuel Pawel

## See Also

[mu2TR](#)

## Examples

```
## p-value for H0: logRR = 0 in RESPIRE trials
p2TR(mu = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
      alternative = "less")
```

---

**pEdgington***Combined p-value from Edgington's method*

---

## Description

This function computes the combined p-value based on two parameter estimates using Edgington's method (also known as the sum method)

## Usage

```
pEdgington(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

## Arguments

<code>mu</code>	Null value. Defaults to 0
<code>t1</code>	Parameter estimate from trial 1
<code>t2</code>	Parameter estimate from trial 2
<code>se1</code>	Standard error of the parameter estimate from trial 1
<code>se2</code>	Standard error of the parameter estimate from trial 2
<code>alternative</code>	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

## Value

The combined p-value based on Edgington's method

## Author(s)

Samuel Pawel

## See Also

[muEdgington](#)

## Examples

```
## p-value for H0: logRR = 0 in RESPIRE trials
pEdgington(mu = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
            alternative = "less")
```

**pFisher***Combined p-value from Fisher's method***Description**

This function computes the combined p-value based on two parameter estimates using the Fisher's method (also known as the product method)

**Usage**

```
pFisher(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

**Arguments**

<code>mu</code>	Null value. Defaults to 0
<code>t1</code>	Parameter estimate from trial 1
<code>t2</code>	Parameter estimate from trial 2
<code>se1</code>	Standard error of the parameter estimate from trial 1
<code>se2</code>	Standard error of the parameter estimate from trial 2
<code>alternative</code>	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

**Value**

The combined p-value based on Fisher's method

**Author(s)**

Samuel Pawel

**See Also**

[muFisher](#)

**Examples**

```
## p-value for H0: logRR = 0 in RESPIRE trials
pFisher(mu = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
        alternative = "less")
```

---

plot.twotrials      *Plot method for class "twotrials"*

---

## Description

Plot method for class "twotrials"

## Usage

```
## S3 method for class 'twotrials'
plot(
  x,
  xlim = c(min(x$isummaries$lower), max(x$isummaries$upper)),
  two.sided = FALSE,
  plot = TRUE,
  ...
)
```

## Arguments

x	Object of class "twotrials"
xlim	x-axis limits. Defaults to the confidence interval range of trial 1 and trial 2
two.sided	Logical indicating whether the p-value functions should be converted to a two-sided p-value function via the centrality function $2\min(p, 1 - p)$ . Defaults to FALSE
plot	Logical indicating whether p-value functions should be plotted. Defaults to TRUE
...	Other arguments (for consistency with the generic)

## Value

Plots combined p-value functions and invisibly returns a data frame containing the data underlying the plot

## Author(s)

Samuel Pawel

## See Also

[twotrials](#)

## Examples

```
## logRR estimates from RESPIRE trials
res <- twotrials(null = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
                  alternative = "less", level = 0.95)
plot(res) # one-sided p-value functions
plot(res, two.sided = TRUE) # two-sided p-value functions
```

pMA

*Combined p-value from fixed-effect meta-analysis*

## Description

This function computes the combined p-value based on two parameter estimates using fixed-effect meta-analysis (equivalent to Stouffer's p-value combination method with suitable weights)

## Usage

```
pMA(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

## Arguments

<code>mu</code>	Null value. Defaults to 0
<code>t1</code>	Parameter estimate from trial 1
<code>t2</code>	Parameter estimate from trial 2
<code>se1</code>	Standard error of the parameter estimate from trial 1
<code>se2</code>	Standard error of the parameter estimate from trial 2
<code>alternative</code>	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

## Value

The combined p-value based on fixed-effect meta-analysis

## Author(s)

Samuel Pawel

## See Also

[pMA](#)

## Examples

```
## p-value for H0: logRR = 0 in RESPIRE trials
pMA(mu = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
      alternative = "less")
```

---

pPearson

*Combined p-value from Pearson's method*

---

## Description

This function computes the combined p-value based on two parameter estimates using Pearson's method

## Usage

```
pPearson(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

## Arguments

mu	Null value. Defaults to 0
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

## Value

The combined p-value based on Pearson's method

## Author(s)

Samuel Pawel

## See Also

[muPearson](#)

## Examples

```
## p-value for H0: logRR = 0 in RESPIRE trials
pPearson(mu = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
          alternative = "less")
```

**print.twotrials** *Print method for class "twotrials"*

## Description

Print method for class "twotrials"

## Usage

```
## S3 method for class 'twotrials'
print(x, digits = 3, ...)
```

## Arguments

x	Object of class "twotrials"
digits	Number of digits for formatting of numbers
...	Other arguments (for consistency with the generic)

## Value

Prints text summary in the console and invisibly returns the "twotrials" object

## Author(s)

Samuel Pawel

## See Also

[twotrials](#)

## Examples

```
## logRR estimates from RESPIRE trials
twotrials(null = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
alternative = "less", level = 0.95)
```

---

pTippett	<i>Combined p-value from Tippett's method</i>
----------	---

---

## Description

This function computes the combined p-value based on two parameter estimates using Tippett's method (also known as the minimum method)

## Usage

```
pTippett(mu = 0, t1, t2, se1, se2, alternative = "greater")
```

## Arguments

mu	Null value. Defaults to 0
t1	Parameter estimate from trial 1
t2	Parameter estimate from trial 2
se1	Standard error of the parameter estimate from trial 1
se2	Standard error of the parameter estimate from trial 2
alternative	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"

## Value

The combined p-value based on Tippett's method

## Author(s)

Samuel Pawel

## See Also

[muTippett](#)

## Examples

```
## p-value for H0: logRR = 0 in RESPIRE trials
pTippett(mu = 0, t1 = -0.491, t2 = -0.185, se1 = 0.179, se2 = 0.174,
          alternative = "less")
```

**twotrials***Combined p-value function inference for two trials*

## Description

This function computes combined p-values, point estimates, and confidence intervals based on two parameter estimates using fixed-effect meta-analysis, the two-trials rule, Edgington's, Fisher's, Pearson's, and Tippett's combination methods

## Usage

```
twotrials(null = 0, t1, t2, se1, se2, alternative = "greater", level = 0.95)
```

## Arguments

<code>null</code>	Null value for which p-values should be computed. Defaults to 0
<code>t1</code>	Parameter estimate from trial 1
<code>t2</code>	Parameter estimate from trial 2
<code>se1</code>	Standard error of the parameter estimate from trial 1
<code>se2</code>	Standard error of the parameter estimate from trial 2
<code>alternative</code>	One-sided alternative hypothesis. Can be either "greater" or "less". Defaults to "greater"
<code>level</code>	Confidence interval level. Defaults to 0.95

## Value

Object of class "twotrials", which is a list of the supplied arguments augmented with pfuns and ipfuns (combined and individual p-value functions), mufuns and imufuns (combined and individual estimation functions), and summaries and isummaries (combined and individual confidence intervals, point estimates, p-values, implicit weights) elements

## Author(s)

Samuel Pawel

## See Also

[pEdgington](#), [muEdgington](#), [pMA](#), [muMA](#), [pTippett](#), [muTippett](#), [p2TR](#), [mu2TR](#), [pFisher](#), [muFisher](#), [pPearson](#), [muPearson](#), [plot.twotrials](#), [print.twotrials](#)

**Examples**

```
## logRR estimates from RESPIRE trials
twotrials(null = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
           alternative = "less", level = 0.95)

## compute 99.875% CIs instead
twotrials(null = 0, t1 = -0.4942, t2 = -0.1847, se1 = 0.1833, se2 = 0.1738,
           alternative = "less", level = 0.99875)
```

# Index

mu2TR, 2, 8, 16  
muEdgington, 3, 9, 16  
muFisher, 4, 10, 16  
muMA, 5, 5, 16  
muPearson, 6, 13, 16  
muTippett, 7, 15, 16  
  
p2TR, 2, 8, 16  
pEdgington, 3, 9, 16  
pFisher, 4, 10, 16  
plot.twotrials, 11, 16  
pMA, 12, 12, 16  
pPearson, 6, 13, 16  
print.twotrials, 14, 16  
pTippett, 7, 15, 16  
  
twotrials, 11, 14, 16